

24 VDC Diaphragm Pump

ITEM 2-1444
\$19.95



• New, SHURFLO model 100-030-20 positive displacement wobbler pump. Ryton and EPDM construction. Not self priming. Wire leads. Rubber vibration damper mounting feet.

SPECIFICATIONS

- Voltage 24 VDC
- Amperage 1.5 Amps
- Shut-Off Pressure 15 PSI
- Max Fluid Temp 130°
- Ports 3/8" Hose Barb
- Duty Intermittent
- Mount 2 holes 2" apart
- Flow Rates
 - 1 GPM @ open flow
 - 0.8 GPM @ 5 PSI
 - 0.53 GPM @ 10 PSI
 - 0.10 GPM @ 15 PSI
- Size 3 1/2" x 2 5/8" x 2"
- Shpg. 1 lb.

Simer Water Pump

ITEM 2-1264
\$39.95



• New, SIMER. Flexible impeller pump. Use to pump water, brine solutions and light lubricating oils. WARNING: This pump should never be used to pump flammable fluids! Wired with a 4 ft. power cord with on/off switch and alligator clips. Permanent magnet motor. Includes two garden hose to 1/2" hose barb adapters and instructions.

SPECIFICATIONS

- 1,140 liters/hour (301 GPH)
- 24 VDC
- Self-priming to 9 feet
- 20 PSI max.
- Max 118°F
- Male garden hose thread ports
- Base mount
- Overall size 7 1/8" x 4 1/2" x 4 1/2"
- Shpg. 7 lbs.

Mini Fountain Pump

ITEM 2-1255
\$3.99



• New, OASE. Submersible fountain pump for indoor or outdoor use. Adjustable output flow. Integral 18/3 cord is water resistant with three prong plug. Two suction cups on bottom to hold pump in place. UL Listed. Made in Italy.

SPECIFICATIONS

- 5 1/2 ft. long cord
- Model SP40G
- 4 watts
- 115 VAC
- 1/2" O.D. outlet tube
- 30-55 GPH
- Size 1 7/8" x 1 5/8" x 1 3/4"
- 18" max. head
- Shpg. 1 lb.

12 VDC Submersible Pump



ITEM 2-1443
\$13.95

• New. Submersible, brushless impeller pump. Can be mounted in or under tank. Sold with 115 VAC to 12 VDC adapter with on/off switch (needs alteration to mate with leads from pump). Pump is not self-priming.

SPECIFICATIONS

- Voltage 12 VDC
- Amperage 0.36 Amps @ 12 VDC, Dry
- Flow 6 GPM @ 0' head pressure
- Max Head Pressure 6.5'
- Input 17mm (0.669") O.D. hose
- Output 12mm (0.472") O.D. hose
- Leads 6"
- Size 3 3/4" x 2 1/8" x 1 3/4"
- Shpg. 1 lb.

Hydraulic Driven Centrifugal Pump



ITEM 2-1180



\$1048.70

• Brand new HYPRO model 9303-HM1C. Cast iron centrifugal pump with direct drive hydraulic motor. Power from tractor hydraulic circuit leaving PTO free for other uses.

SPECIFICATIONS

- Maximum Pressure 120 PSI
- Maximum Pump Flow: 112 GPM
- Pump inlet 1 1/2" NPT
- Pump discharge 1 1/4" NPT
- 140° F max. fluid temp
- Hydraulic motor ports 1/2" NPT
- Hydraulic requirements-13 GPM at 2000 PSI
- 11" x 7 3/4" x 8 1/4"
- Shpg. 31 lbs.

3" Trash Pump Head

ITEM 2-1438-A



\$119.95

• New, HYPRO 3" aluminum trash pump head. Simply add your own 6.5 HP engine with 3/4" keyed crankshaft. Removable front cover allows easy cleanout. Cast iron volute and impellor for long life. Will handle solids up to 1" dia. EPDM mechanical shaft seal and inlet valve to retain prime after initial setup.

SPECIFICATIONS

- HP required 6.5 minimum
- Ports 3" NPT
- Input shaft required 3/4" dia. keyed
- Max. head 106 ft.(46 PSI)
- Max. suction lift 23 ft.
- Mtg. pattern to engine 4 holes on 3 5/8" bolt circle
- Furnished with 5/16"-24 bolts
- Base mount slotted 9 1/2" c/c
- Size 12" x 10" x 13"
- Shpg. 40 lbs.

Flow Rate at Ft. of Head (PSI)	
Flow Rate	Ft of Head (PSI)
272 GPM	at 12 Ft. (5 PSI)
179 GPM	at 58 Ft. (25 PSI)
50 GPM	at 93 Ft. (40 PSI)

12 VDC Diaphragm Pump

ITEM 2-1455



\$19.99

• New, DELAVAN automatic demand diaphragm pump. Ideal for spot sprayers or as replacement on existing equipment. Santoprene diaphragm and Viton valves. Automatic shut off switch set to 40 PSI. Pump turns on at 25 PSI. Self priming to 4 foot suction lift. Can run dry intermittently without damage. Wire leads. Rubber vibration damper mounting feet.

SPECIFICATIONS

- Voltage 12 VDC
- Amperage 2.6 Amps
- Shut-Off Pressure 40 PSI
- Flow Rates
 - 1 GPM @ open flow
 - 0.85 GPM @ 10 PSI
 - 0.71 GPM @ 20 PSI
 - 0.61 GPM @ 30 PSI
- 0.42 GPM @ 40 PSI
- Ports 3/8" Hose Barb QA port adapters
- Duty Intermittent
- Temperature 110°F max.
- Mount Four bolt on 3.19" x 2.25" pattern
- Size 7" x 3 5/8" x 2 3/8"
- Shpg. 2 lbs.

120 VAC Submersible Pump

ITEM 2-1467 
\$29.95



• New, DK-5000 submersible water pump. Ideal for fountains, ponds, machine tool coolant. Plastic housing, plastic impeller. Slotted intake cover can be easily removed for cleaning. Four suction cups on base. Includes a brass adapter to 3/8" ID tubing.

SPECIFICATIONS

- Voltage 120 VAC
- Power Consumption 105 Watts
- Flow 20 GPM open flow
- Max Head 15 ft.
- Size 7" x 4" x 5"
- Port 3/4" MGHT (Standard Garden Hose Male) w/ 3/8" ID hose adapter
- Power Cord 15 ft. long, 3-prong plug
- Shpg. 8 lbs.

Tuthill Manual Transfer Pump

ITEM 2-1350
\$19.99



• New, TUTHILL Series 20 hand lever piston pump for pumping fluid into a container. Polypropylene housing, Buna N seals. Economical manual transfer pump ideal for use on barrels, drums and storage tanks. Anti-drip nozzle, check valve and 360° locking ring. Telescoping suction pipe fits up to 36" high container. Compatible with water, gear oils, engine oils, paraffin, fertilizers, mild acids, anti-freeze, hydraulic oils, diesel, degreasers, herbicides and pesticides. Not for use with gasoline, ethanol or methanol.

SPECIFICATIONS

- Flow 11 fl. oz. per stroke
- Viscosity SAE 90 max.
- Bung Adapter 2" NPS
- Inlet 1" NPT
- Outlet Nozzle with strainer
- Size 9 1/4" x 3 1/2" x 12"
- Shpg. 5 lbs.

1/2" IPS Brass Gate Valve

ITEM 20-1657-50
\$4.99



• New, CHAMPION-ARROWHEAD lead-free brass gate valve. Full port. IPS (Iron Pipe Straight) ports.

SPECIFICATIONS

- Ports 1/2" IPS
- Pressure Max 200 PSI
- Size 2" x 1 1/4" x 3 1/4"
- Shpg 1/2 lb.

12 VDC Centrifugal Pump

ITEM 2-1155
\$338.90



• Brand new HYPRO "Aqua-Tiger" Bronze centrifugal pump. Use for ag chemical transfer, live well aeration, circulation, etc. Permanent magnet motor. Not self-priming.

SPECIFICATIONS

- 12 Volt DC
- 5.5 amps
- Max. flow 19 GPM
- Max. 7 PSI
- Max 140°F
- Ports 3/4" NPT
- 7" x 4 1/2" x 4"
- Shpg. 8 lbs.