

Peerless Six Speed Transaxles

ITEM 13-1620
\$285.75

• Brand new. PEERLESS MST-206-545C six speed transaxle. Push brake lever to actuate brake. This "Axle-Rearward" style transaxle is designed to be mounted at the rear end of the machine, behind the engine, with the transaxle axles towards the rear of the machine and the gearbox portion of the transaxle towards the front of the vehicle. Transaxles are shipped pre-filled with oil from the factory.

SPECIFICATIONS

- Brand Peerless
- Model MST-206-545C
- Speeds: Six forward, Reverse, and Neutral
- Gear ratios First 60.25:1, second 47.46:1, third 30.92:1, fourth 20.67:1, fifth 15.24:1, sixth 13.71:1, reverse 47.46:1
- Input Speed 2,000 RPM max
- Input Rotation CW
- Output Torque 225 ft-lbs max
- Load Rating 525 lbs max
- Input Shaft 3/8" dia. x 1 3/16" w/ 3/16" keyway and snap ring groove
- Overall Axle Width 29 1/8"
- Axles 3/4" dia. x 4 3/4" long w/ 3/16" x 2 3/4" long keyway and snap ring groove
- Overall Axle Width 29 1/8"
- Tire Diameter 20" max
- Gear Shift Shaft 3/8" square, tapped 1/4"-28
- Inner Mount Four 1 1/32" bolt holes on 13" x 1 3/4" centers
- Outer Mount Four 1 1/32" bolt holes on 16 1/4" x 2 1/2" centers
- Housing Size 19 3/4" x 12 1/2" x 6 1/2"
- Brake Lever 3 3/4" x 1 1/2" w/ 5/16" hole for linkage
- Size 29 1/8" x 12 1/2" x 8"
- Shpg 33 lbs.

w/Pull Brake Lever

ITEM 13-1621 **\$284.95**

w/Pull Brake Lever/Axle Forward

ITEM 13-1622 **\$259.35**

Hydrogear T2 Hydrostatic Transaxle

ITEM 13-1632
\$349.95

• New HYDRO-GEAR model T2. Hydrostatic transaxle. Part #T2-BDBE-1X2B-18X1. Vertical input for belt drive. External disc brake. Bypass lever allows vehicle to be moved without power. Recommended engine size 19 HP.

SPECIFICATIONS

- Husvarna Part 587392201
- Input speed 3600 RPM max (no load) 1800 RPM min (loaded)
- Max speed 5.5 mph
- Pump/Motor Displacement 8/10 cc
- Gear Ratio 27.5:1
- Axle Torque 230 lb.ft. Continuous 445 lb.ft. Intermittent
- Max axle wt. 540 lbs. with 18" dia. tires
- Input Direction CW
- Pulley 4" dia.
- Axles 1" diam. x 5" w/ keyway and snap ring groove
- Max Tire Size 23" dia.
- Recommended Oil 5W-50 Synthetic
- Two four-bolt mounts Inner mntg. centers: 1 3/4" x 13 3/4"
- Outer mntg. centers: 2 1/2" x 16 1/4"
- Overall Size 29 1/4" x 15" x 10"
- Actual wt. 42 lbs.
- Shpg. 60 lbs.

96:1 Inline Gear Reducer

ITEM 13-1586 **\$39.95**

• New, THOMSON MICRON inline speed reducer. Aluminum housing.

SPECIFICATIONS

- Nominal Ratio 96:1
- Actual Ratio 95.98:1
- Output RPM @ 1800 RPM Input 18.75 RPM
- Input Shaft 1/4" dia. x 1 1/2" (no keyway or flat)
- Motor Mount 2" ID housing
- Output Shaft 1/2" dia. x 5/8" long with dual flats
- Base Mount Four 0.35" holes on 5.12" x 4.33" centers
- Size 7 3/16" x 3 1/8" x 4"
- Shpg. 3 lbs.



Right Angle Gearboxes

• Brand new. Right angle gearboxes. One piece cast iron gear case and bearing caps. Roller bearings. Ships without oil, user must add 1/3 quart of 80-90 W oil prior to use.

SPECIFICATIONS FOR ALL

- Ratio 1:1
- Input Power: 40 HP intermittent 32 HP continuous
- Input Speed 1800 RPM max.



- Size 5 7/8" x 6 1/4" x 4 1/8"
- Output Shaft: 1" diam. x 2 1/4" w/ 1/4" keyway
- Mount: Four 3/8"-16 tapped holes on 4 1/4" square centers
- Shpg. 23 lbs.

ITEM	Input Shaft	Output rotation	Price
13-1423-KC	1" dia. x 2 1/2" w/ 1/4" keyway and 5/16" crosshole	Opposite of input	\$211.30
13-1423-SKC	1" diam. x 2 1/2" w/ 5/16" crosshole and 1/4" keyway	Same as input	\$211.30
13-1423-3KC	1" diam. x 2 1/2" w/ 5/16" crosshole and 1/4" keyway	Dual Shaft	\$251.75

Peerless Differential Axles



ITEM 13-1618 **\$112.90**
3/4" Diameter

• Brand new. PEERLESS differential. Can be used with PEERLESS 700 series transmission, a gas engine, or electric motor (sold separately) for residential or commercial use. Axle is not heat treated. Used with related PEERLESS drive sprockets (sold separately).

SPECIFICATIONS

- Model 100-007B
- Axles 3/4" dia. x 16" smooth shaft
- Tire Diameter 18" max
- Output Torque 150 ft-lb max
- Load Rating 400 lb max
- Size 39 3/8" x 3 5/8" x 3 5/8"
- Shpg 11 lbs.

ITEM 13-1619 **\$174.70**
1" Diameter

SPECIFICATIONS

- Model 100-224
- Axles 1" dia. x 14" w/ 1/4" x 6" keyway and 1/4" x 1" woodruff keyway. Axle end threaded 3/4"-16 UNF x 1 1/8"
- Tire Diameter 20" max
- Load Rating 600 lb max
- Size 38" x 3 5/8" x 3 5/8"
- Shpg 14.5 lbs.

Aluminum High Speed Gearboxes

ITEM 13-1616-A
\$151.35

• Brand new. Peerless 1000-014-D gearbox. Cast aluminum gearbox and ships with oil. Shafts rotate in same direction when viewed from end.

SPECIFICATIONS FOR ALL

- Ratio 1:1
- Input Power 10 HP continuous
- Input Speed 3600 RPM max.
- Output Torque 360 in-lbs.
- Size 5 1/2" x 4 3/4" x 7"
- Input Shaft: 7/8" dia. x 1 1/2" w/ 3/16" woodruff keyway
- Output Shaft: 7/8" dia. x 1 1/4" w/ 3/32" woodruff keyway and 3/8"-24 tapped end
- Mount: Two 1 3/32" bolt holes on 4" centers, 2.92" dia. pilot
- Shpg. 8 lbs.

ITEM 13-1616-B

\$157.55

• Peerless 1000-015 gearbox. Shafts rotate in opposite directions when viewed from end. Shpg. 8 lbs.

3 Shaft Gearbox

ITEM 13-1616-C
\$153.90

• Brand new. Peerless 1000-007 gearbox. Solid output shaft extends from both sides of case. Shpg. 9 lbs.

Peerless Differential Sprockets

• Brand new. PEERLESS sprocket for differential

SPECIFICATIONS

- Bolt Holes Four 0.35" dia.
- Bolt Hole Pattern 0.941" x 1.81"

ITEM	Pitch	Bore	Teeth	O.D.	Shpg.	Price
13-1623-35-36	35	2 1/8"	36	4.51"	1/2	\$56.75
13-1623-40-45	40	2 1/8"	45	7.45"	2.5	\$67.10
13-1623-41-40	41	2 1/8"	40	6.81"	2	\$41.90
13-1623-41-48	41	2 1/8"	48	7.93"	2	\$56.00
13-1623-41-60	41	2 1/8"	60	9.84"	5	\$57.50

Cast Iron High Speed Gearboxes

ITEM 13-1617-A **\$199.95**

• Brand new. Peerless gearbox. Cast iron gearbox housing ships filled with oil. Shafts rotate in opposite direction when viewed from end.

SPECIFICATIONS

- Brand Peerless
- Model 1050-009A
- Ratio 1:1
- Rotation Opposite
- Input Power 10 HP max continuous
- Input Speed 3600 RPM max.
- Output Torque 360 in-lb max
- Input Shaft 3/4" dia. x 1 5/8" w/ 3/16" woodruff keyway
- Output Shaft 3/4" dia. x 1 5/8" w/ 5/32" woodruff keyway
- Mount Two 3/8"-16" bolt holes on 4" centers and 2.9" dia. pilot
- Size 7" x 5 3/4" x 4 3/4"
- Shpg. 13 lbs.

ITEM 13-1617-B **\$199.95**

• **SPECIFICATIONS SAME AS ABOVE EXCEPT**
• Model 1015-012 • Ratio 1.2:1 • Rotation Same

Right Angle Gearbox

ITEM 13-1423-SK-G
\$149.95

• New. Right angle gearbox. One piece cast iron gear case and bearing caps. Roller bearings. Shafts rotate in same direction when viewed from end. Ships without oil, user must add 1/3 quart of 80-90 W oil prior to use.

SPECIFICATIONS

- Ratio 1:1
- Input Power 40 HP intermittent 32 HP continuous
- Size 5 7/8" x 6 1/4" x 4 1/8"
- Input Shaft: 1" diam. x 2 1/2" w/ 5/16" crosshole and 1/4" keyway
- Output Shaft: 1" diam. x 2 1/4" w/ 5/16" crosshole and 1/4" keyway
- Input Speed 1800 RPM max.
- Mount: Four mounting holes tapped 3/8"-16 on 4 1/4" square centers
- Shpg. 23 lbs.

ITEM 13-1423-S-G

\$149.95

• Same except Input Shaft is 1" diam. x 2 1/2" w/ 5/16" w/crosshole and output shaft is 1" diam. x 2 1/4" w/keyway

