



184 TC Frame

Leeson Single Phase Face & Base Mount TEFC Motors

• Brand new, LEESON general purpose electric motor. Face mount allows for direct coupling to pumps and gearboxes. Capacitor start and run. Steel housing. Manual reset thermal overload protection.

SPECIFICATIONS

- Rotation reversible
- TEFC
- Phase 1



213TC & 215TC Frame

1800 RPM * Products drop-shipped from the manufacturer are not returnable.

| ITEM | Catalog Number | HP | Voltage | Amps | Frame | Shaft Dia. | Service Factor | Overload Prot. | Size | Shpg. | Price |
|----------|----------------|-------|---------|------|-------|------------|----------------|----------------|-----------------------------|----------|-----------|
| 10-2888* | 131633.00 | 5 | 230 | 23 | 184TC | 1 1/8" | 1.0 | Manual | 13 15/16" x 11" x 11 5/16" | 86 lbs. | \$1081.30 |
| 10-2890 | 141429 | 7 1/2 | 230 | 33.6 | 215TC | 1 3/8" | 1.15 | None | 17 1/8" x 13 1/4" x 11 3/4" | 171 lbs. | \$1779.35 |
| 10-2892* | 140678.00 | 10 | 230 | 40 | 215TC | 1 3/8" | 1.15 | None | 17 5/8" x 13 1/4" x 11 3/4" | 159 lbs. | \$1694.70 |

3600 RPM **

| ITEM | Catalog Number | HP | Voltage | Amps | Frame | Shaft Dia. | Service Factor | Overload Prot. | Size | Shpg. | Price |
|-----------|----------------|-------|---------|---------|-------|------------|----------------|----------------|---------------------------------|----------|-----------|
| 10-2885** | 121060.00 | 3 | 230 | 13 | 145TC | 7/8" | 1.0 | Manual | 10 7/8" x 8 7/8" x 8 5/8" | 51 lbs. | \$888.05 |
| 10-2887 | 131632.00 | 5 | 230 | 19.8 | 184TC | 1 1/8" | 1.15 | Manual | 13 15/16" x 11" x 11 5/16" | 103 lbs. | \$1249.70 |
| 10-2889* | 140694.00 | 7 1/2 | 208-230 | 36-32 | 213TC | 1 3/8" | 1.0 | None | 15 15/16" x 13 1/8" x 11 11/16" | 150 lbs. | \$1466.45 |
| 10-2891* | 140695.00 | 10 | 208-230 | 44-41.5 | 215TC | 1 3/8" | 1.0 | None | 18 3/4" x 13 1/8" x 11 11/16" | 152 lbs. | \$1750.05 |

2 HP Washdown Motor

ITEM 10-3124
\$319.95

• New, Designed to handle high-pressure washdowns. Stainless steel fan and junction box cover. Steel construction. Solid state encapsulated starting switch.

SPECIFICATIONS

- Model 182TCWW7026
- Power 2 HP
- Amperage 21/11-10.5
- Speed 1740 RPM
- Frame 182T
- Size 10.5" x 10" x 11"
- Thermal Overload Protection None
- Base Mount: Four 3/8"-16 tapped holes on 5 7/8" diameter bolt circle
- Shpg. 70 lbs.



1/2 HP 3450 RPM Pool Pump Motor

ITEM 10-3216
\$79.95

• New, pool pump motor. Ideal replacement motor for pool pumps. Square flange 4 bolt pump mount on 7 1/8" bolt circle. Stainless steel shaft 5/8" diameter with 1/2"-20 UNF-2A RH threaded end. Thermally protected.

SPECIFICATIONS

- Power 1/2 HP
- Voltage 208-230/460 AC
- Amps 3/1.5
- RPM 3450
- Rotation CCW
- Phase 3
- Service Factor 1.9
- Enclosure TEFC
- Duty continuous
- Frame 56Z
- Shaft 5/8" diameter with 1/2"-20 UNF-2A threaded end
- Size 10 1/2" x 6 1/2" x 8 1/2"
- Shpg 18 lbs.



1/3 HP 1075 RPM 208/230 VAC Motor

ITEM 10-3334
\$39.95

• New. BALDOR. Requires 8 MFD 370 volt run capacitor (sold separately).

SPECIFICATIONS

- Brand Baldor
- Model CFC2614A
- Power 1/3 HP
- Voltage 208-230 AC
- Amperage 1.9
- Speed 1075 RPM
- Rotation CW
- Phase 1
- Enclosure OPAO
- Thermal Overload Protection Automatic
- Duty Continuous
- Frame 48YZ
- Face Mount Four #8-32 bolts on 3 5/8" centers
- Shaft 1/2" dia. x 5 1/2" long w/ two flats
- Size 9" x 5 1/2" x 5 1/2"
- Shpg. 22 lbs.



1/3 HP 1200 RPM Motor

ITEM 10-3388
\$149.95

• New, CENTURY electric motor. Resilient base mount. Steel construction.

SPECIFICATIONS

- Model F420
- Power 1/3 HP
- Voltage 120/230 AC
- Phase 1
- Frequency 60 Hz
- Amperage 6.2/3.1 Amps
- Speed 1140 RPM
- Rotation Reversible
- Service Factor 1.35
- Bearings Ball
- Enclosure ODP
- Thermal Overload Protection None
- Duty Continuous
- Frame 56
- Base Mount Four 5/16" wide slots on 4 7/8" to 5 3/4" x 3" centers
- Shaft 5/8" dia. x 1 7/8" overall length w/ 3/16" wide x 1 1/2" long keyway
- Size 10" x 6 5/8" x 6 3/4"
- Shpg. 30 lbs.



1 1/2 HP, 115/230 VAC Grain Stirring Motor

ITEM 10-2769*
\$559.45

• Brand new, LEESON Model P6K17-FB18H grain stirring motor. High torque design. Designed for use in grain bins. Vertical shaft up with drain hole. Capacitor start and run motor. Steel construction. Manual overload protection.

SPECIFICATIONS

- Power 1 1/2 HP
- Voltage 115/208-230 AC
- Amperage 17.2/8.8-8.6
- Speed 1800 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.0
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 56HZ
- Base mount 6 hole mount on 4 7/8" x 3" to 5" centers
- Shaft 7/8" dia. x 1.31" w/ 3/16" keyway
- Size 11" x 8.89" x 8.56"
- Shpg. 45 lbs.



3/4 HP 3450 RPM 115/230 VAC Motor

ITEM 10-3344
\$65.95

• New, MARATHON electric motor capacitor-run.

SPECIFICATIONS

- Brand Marathon
- Model 056C34D1169E
- Power 3/4 HP
- Voltage 115/230 AC
- Phase 1
- Frequency 60 Hz
- Amperage 9.8/4.9
- Speed 3450 RPM
- Rotation CCW
- Service Factor 1.5
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Frame 56C
- Face Mount Four 3/8"-16 holes on 5 7/8" Bolt Circle
- Shaft 5/8" dia. x 1 7/8" w/ 3/16" keyway
- Size 11" x 6" x 7"
- Shpg. 20 lbs.



1/2 HP Electric Motor

ITEM 10-3127
\$49.99

• New, AO Smith Electric motor.

SPECIFICATIONS

- Model J218-582A-LS
- Power 1/2 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 11.5/5.75 Amps
- Speed 3450 RPM
- Rotation CCW
- Service Factor 1.3
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 5/8" dia. x 1 1/2" long with 1/2"-20 threaded end
- Size 12" x 6 1/2" x 6 1/2"
- Shpg. 17 lbs.



3/4 HP Electric Motor

ITEM 10-3128
\$49.99

• New, AO Smith Electric model# J218-590B.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 11.5/5.75 Amps
- Speed 3600 RPM
- Rotation CCW
- Service Factor 1.25
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 5/8" dia. x 1 1/2" long with 1/2"-20 threaded end
- Size 10 1/2" x 6 1/2" x 6 1/2"
- Shpg. 22 lbs.

