

TECO
©Westinghouse

TECO - Westinghouse Base Mount Motors

• New, TECO-WESTINGHOUSE general purpose electric motors. Capacitor start and run. Steel housing. Automatic reset overload protection.

1/4 HP

ITEM 10-3357

\$69.95

SPECIFICATIONS

- Model Number SPO/22
- Power 1/4 HP
- Voltage 115/208-230 AC
- Amperage 2.6 /1.45-1.31
- Speed 3500 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball



- Enclosure ODP
- Duty Continuous
- Frame 48
- Rigid Base Mount: Four slotted holes on 4 1/2" x 2 3/4" centers
- Shaft 1/2" diam. x 1 1/2" w/ flat
- Size 9" x 7 1/2" x 7 1/4"
- **Shpg. 22 lbs.**

1/4 HP

ITEM 10-3358

\$69.95

SPECIFICATIONS

- Model Number SPT0/22
- Power 1/4 HP
- Voltage 115/208-230 AC
- Amperage 2.56/1.42-1.28
- Speed 3500 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball



- Enclosure TEFC
- Duty Continuous
- Frame 48
- Rigid Base Mount: Four 0.34" wide slots on 4 1/4" to 5" x 2 3/4" centers
- Shaft 1/2" diam. x 1 1/2" w/ Flat
- Size 9 1/4" x 7 3/4" x 7 1/4"
- **Shpg. 23 lbs.**

1/4 HP

ITEM 10-3359

\$59.95

SPECIFICATIONS

- Model Number SPH0/22
- Power 1/4 HP
- Voltage 115/208-230 AC
- Amperage 2.62/1.45-1.31
- Speed 3500 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball



- Enclosure ODP
- Duty Continuous
- Frame 56
- Rigid Base Mount: Four 0.34" wide slots on 4 7/8" to 5 3/4" x 3" centers
- Shaft 5/8" diam. x 1 7/8" w/ 3/16" keyway
- Size 9" x 8" x 7 3/4"
- **Shpg. 22 lbs.**

1/3 HP

ITEM 10-3360

\$69.95

SPECIFICATIONS

- Model Number SPO/32
- Power 1/3 HP
- Voltage 115/208-230 AC
- Amperage 3.42/1.89-1.71
- Speed 3500 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball



- Enclosure ODP
- Duty Continuous
- Frame 48
- Rigid Base Mount: Four 0.34" wide slots on 4 1/4" to 5" x 2 3/4" centers
- Shaft 1/2" diam. x 1 1/2" w/ Flat
- Size 9" x 7 3/4" x 7 1/4"
- **Shpg. 23 lbs.**

1/3 HP

ITEM 10-3361

\$74.95

SPECIFICATIONS

- Model Number SPH0/32
- Power 1/3 HP
- Voltage 115/208-230 AC
- Amperage 3.42/1.89-1.71
- Speed 3500 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball



- Enclosure ODP
- Duty Continuous
- Frame 56
- Rigid Base Mount: Four 0.34" wide slots on 4 7/8" to 5 3/4" x 3" centers
- Shaft 5/8" diam. x 1 7/8" w/ 3/16" keyway
- Size 9" x 8" x 7 3/4"
- **Shpg. 23 lbs.**

1/3 HP

ITEM 10-3362

\$79.95

SPECIFICATIONS

- Model Number SPHT0/32
- Power 1/3 HP
- Voltage 115/208-230 AC
- Amperage 3.36/1.86-1.68
- Speed 3500 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball



- Enclosure TEFC
- Duty Continuous
- Frame 56
- Rigid Base Mount: Four 0.34" wide slots on 4 7/8" to 5 3/4" x 3" centers
- Shaft 5/8" diam. x 1 7/8" w/ 3/16" keyway
- Size 9 3/8" x 8" x 7 3/4"
- **Shpg. 24 lbs.**

1/2 HP

ITEM 10-3363

\$89.95

SPECIFICATIONS

- Model Number SPO/52
- Power 1/2 HP
- Voltage 115/208-230 AC
- Amperage 4.94/2.73-2.47
- Speed 3510 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball



- Enclosure ODP
- Duty Continuous
- Frame 48
- Rigid Base Mount: Four 0.34" wide slots on 4 1/4" to 5" x 2 3/4" centers
- Shaft 1/2" diam. x 1 7/16" w/ Flat
- Size 9 1/2" x 7 3/4" x 7 1/4"
- **Shpg. 25 lbs.**

3/4 HP

ITEM 10-3364

\$96.95

SPECIFICATIONS

- Model Number SPT0/72
- Power 3/4 HP
- Voltage 115/208-230 AC
- Amperage 6.76/3.74-3.38
- Speed 3510 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball



- Enclosure TEFC
- Duty Continuous
- Frame 48
- Rigid Base Mount: Four 0.34" wide slots on 4 1/4" to 5" x 2 3/4" centers
- Shaft 1/2" diam. x 1 7/16" w/ Flat
- Size 10 3/8" x 8" x 7 3/8"
- **Shpg. 30 lbs.**

3/4 HP 3600 RPM Motor

ITEM 10-3120

\$59.95

• New, BLUFFTON MOTOR WORKS model B1244 pool pump motor. Smooth portion of shaft measures 1 9/16" from the bearing overall length 2 1/16". Automatic thermal overload protection.



SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 AC
- Amperage 12.8/6.4 Amps
- Speed 3450 RPM
- Rotation CCW
- Phase 1
- Service Factor 1.27
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 56Y
- Mount Square flange 4 bolt on 7 1/8" diam. B.C.
- Shaft 5/8" diam. x 2 1/16" w/ 1/2"-20 RH threaded end
- Size 10 7/8" x 6 5/8" x 6 5/8"
- **Shpg. 24 lbs.**

3/4 HP 3450 RPM Jet Motor

ITEM 10-3019

\$89.95

• New, Myers model# F48Y05A03 (25051A008) thermally protected, capacitor start jet pump motor. Automatic thermal overload protection.



SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 AC
- Amperage 10.0/5.0 Amps
- Speed 3450 RPM
- Rotation Counterclockwise
- Phase 1
- Service Factor 1.30
- Enclosure ODP
- Duty Continuous
- Frame 48Y
- Mount Face Mount w/ Four 3/8" Holes on 7 1/4" Bolt Circle
- Shaft 5/8" dia. x 2 1/8" Overall Length, 1/2"-20 x 1/4" Long RH Threaded End
- Size 12 1/8" x 5 3/4" x 8"
- **Shpg. 25 lbs.**

3/4 HP Electric Motor

ITEM 10-3126

\$39.95

• New, AO Smith Electric model# J218-1006.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 12.5/3 Amps
- Speed 3600 RPM
- Rotation CCW
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 12mm dia. tapered x 3/4" long with M10-1.0 threaded end
- Size 12" x 8" x 8"
- **Shpg. 23 lbs.**



2 HP Air Compressor Motor

ITEM 10-3192

\$139.95

• New, Marathon Electric model 5KCR48TN2699Y motor. High torque design for compressor duty applications. Overload protection with manual reset. Steel frame and base. Welded base. Capacitor start/capacitor run.



SPECIFICATIONS

- Power 2 HP Special
- Voltage 115/230 VAC
- Amperage 15/7.5 Amps
- Speed 3450 RPM
- Phase 1
- Rotation CCW
- Service Factor 1.0
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 56
- Mount Base
- Shaft 5/8" diam. x 1 7/8" w/ 3/16" keyway
- Size 10 1/4" x 8" x 6 1/2"
- **Shpg. 35 lbs.**