



12 VDC Powerpack Motors



\$134.85

ITEM 10-2438
Model KMD1 (1787-AC)

SPECIFICATIONS

- Voltage 12 DC
- Amperage 270 amps (max.)
- Rotation CW
- Enclosure TENV
- Mount 2 studs, 3 1/2" c/c

- Duty Intermittent 8% duty (24 seconds on/276 seconds off in 5 minutes at full load).
- Shaft 0.48" dia 9 tooth spline
- Size 4 1/2" dia. x 3.94"
- Shpg. 17 lbs.

ITEM 10-2508

Model KMD3 (1789-AC) Heavy Duty
• Same as ITEM 10-2438 above except 300 Amps, 13% Intermittent Duty (39 seconds on/ 261 seconds off in 5 min. at full load), Size 4.5" dia. x 7.52". **Shpg. 18 lbs.**

\$158.25

185 RPM 24 Volt DC Gearmotor



ITEM 5-1921
\$18.95


• New, AMETEK PITTMAN model# GM9234E992-R1 parallel-shaft gearmotor. Operates at 1/2 speed on 12 volt DC power.

SPECIFICATIONS

- Shaft Speed 185 RPM
- Voltage 24 VDC
- Amperage 0.15 Amps @ No Load
- Torque 41 oz/in peak
- Gear Ratio 5.9:1
- Rotation Reversible
- Duty Intermittent
- Enclosure TENV

- Face Mount Two 10-32 tapped holes on 1 1/2" centers
- Rear Mount Four 6-32 tapped holes on 1 1/16" square centers
- Shaft 3/16" dia. x 5/8" w/ cross pin hole
- Size 3 3/16" x 2" dia.
- Shpg. 2 lbs.

5 RPM, 24 VDC Inline Gearmotor



ITEM 5-1840

\$129.95


• New take-off, SolFocus P/N 350-000062-000 permanent magnet inline gearmotor. Rated for 24 volts but will operate on 12 volts at reduced speed and output.

SPECIFICATIONS

- Speed 5 RPM
- Voltage 24 VDC
- Amperage 4.2 Amps
- Power 1/10 HP
- Torque 109 Nm (964.8 in.lbs.)
- Gear Ratio 266.3:1
- Rotation Reversible

- Duty Continuous
- Enclosure TENV
- Face Mount 2 bolt, 106mm (4.173") bolt circle
- Mount Pilot 68mm (2.677")
- Shaft 25mm (0.984") dia. x 1 1/2" long 18T spline DIN 5480
- Size 18 5/8" x 5 3/16" x 6 1/4"
- Shpg. 40 lbs.

109 RPM 24 VDC GearMotor



ITEM 5-1693
\$14.95


• New, Mabuchi inline parallel shaft gearmotor. Die-cast gear housing. Mounting holes are drilled and tapped with 10-32 thread.

SPECIFICATIONS

- Speed 109 RPM
- Voltage 24 DC
- Amperage 78 mA (no load)
- Rotation Reversible
- Duty Intermittent

- Enclosure Open
- Mount 4 bolt face on 2 5/8" x 2 1/2" centers
- Shaft 5/16" dia. x 3/8" w/ flat
- Size 2 7/8" x 2 3/4" x 3 3/16"
- Shpg. 2 lbs.

40 RPM, 12 VDC Right-Angle Gearmotors



• Brand new, BUYERS PRODUCTS. High torque, right-angle gearmotor built to fit common truck and trailer tarp systems. Forged drive gear, aluminum gearbox housing and motor end-cap, steel motor housing. Gearbox is sealed to prevent contamination. Includes a chromed plastic bolt-on cover and mounting hardware. Shaft has two 3/16" cross-holes spaced 3/4" apart. Five mounting holes in face of gearbox tapped 5/16"-18.

ITEM 5-1719

SPECIFICATIONS

- P/N 5541095
- Speed 40 RPM
- Voltage 12 DC
- Amperage 33-50 Amps
- Power .53 HP
- Torque 836 in-lbs.
- Gear ratio 90:1

\$215.20

- Rotation reversible
- Duty intermittent
- Totally enclosed
- Mount five tapped holes
- Shaft 3/4" x 3 1/8" w/ two cross-holes
- Size 10" x 6" x 3 3/8"
- Shpg. 14 lbs

ITEM 5-1720


SPECIFICATIONS

- P/N 5541895
- Speed 40 RPM
- Voltage 12 DC
- Amperage 33-75 Amps
- Power 1.2 HP
- Torque 1890 in-lbs.
- Gear ratio 90:1

\$227.10

- Rotation reversible
- Duty intermittent
- Totally enclosed
- Mount five tapped holes
- Shaft 3/4" x 3 1/8" w/ two cross-holes
- Size 11 1/8" x 6" x 3 3/8"
- Shpg. 16 lbs

100 RPM, 12 VDC Gearmotor



ITEM 5-1649
\$157.90

• Brand new, STATURE ELECTRIC Model RA-AFSL-30AN-35 right-angle gearmotor. Ball bearings and bronze bushings, steel worm gear, brass output gear and die cast aluminum gearbox. Two pole, permanent magnet motor with internal brushes. Three mounting holes tapped for M6 machine screws. Rated to withstand 300 in-lbs. max back-drive torque.

SPECIFICATIONS

- Speed 100 RPM
- Voltage 12 DC
- Amperage 3.0 no load, 6.0 cont., 62 peak
- HP 1/30 cont.
- Torque 20 in-lbs. cont.
- Gear ratio 35:1

- Rotation reversible
- Duty intermittent
- Fully enclosed, IP54
- Face mount, tapped holes
- Shaft 7/16" dia. x 2 7/16" w/flat
- Size 7 3/8" x 3 1/8" x 4 3/8"
- Shpg. 7 lbs.

25 RPM, 24 VDC Gearmotor



ITEM 5-1796
\$11.95

• New, SEI Model 37JB270G/32ZYT30-2468 compact inline gearmotor. Operates on 12-24 VDC.

SPECIFICATIONS

- Speed 25 RPM (no load)
- Voltage 24 DC
- Amperage 60 mA (no load)
- Torque 8 in. lbs.
- Gear ratio 270:1

- Rotation reversible
- Duty continuous
- Mount four M3 holes face
- Shaft 6mm x 0.6" w/flat
- Size 1.45" dia. x 2.2"
- Shpg. 1/2 lb.

12 VDC Seven Channel Wireless Remote Control



ITEM 11-3305

\$164.05

• Brand new. Wireless remote control receiver/transmitter combination. Each circuit is controlled separately from transmitter.

• Code learning feature on receiver for easy programming. Select activation as long as transmitter button is depressed or momentary pulse for channels 1, 2, 6 and 7.

• Ignition lockout option disables channels 1-4. Channels 1 and 2 allow for manual switch (not included) to activate in addition to remote transmitter.

• Operate from 12 Volt DC power supply or battery. Only draws 0.15 amps.


• 100 ft. range with clear line of sight. Includes 2 keychain 4-pushbutton transmitters and full instructions.

SPECIFICATIONS

- Voltage 12 VDC
- Channel 1-2 Output Relay
- Relay Contacts Rating 30 Amp max
- Relays SPDT (common N.O. connection)
- Channels 3-7 Output 500 mA

- Connections: Channel 1-2, spade terminals
- Channel 3-7 and power, 10 Pin Connector
- Mount Two hole, 3 7/8" c/c
- Size 4 1/8" x 4" x 1 1/4"
- Shpg. 2 lbs.

12 Volt DC Reversing Wireless Remote Control



ITEM 11-3395

\$143.00

• Brand new. Wireless remote control to reverse polarity to equipment. Ideal for linear actuators or other permanent magnet motors. Waterproof receiver. Remotes have 2 buttons to control output. Code learning button on receiver with LED indicator. Very low current draw in standby. Heavy duty leads. High power radio gives over 150 foot range with a clear line of sight. Includes two keychain remote transmitters.

SPECIFICATIONS

- Input Voltage 12 VDC
- Output 12 VDC polarity reversing
- Momentary Contacts

- Output current 30 Amp max
- Mount 2 tabs
- Size 3" x 3" x 1"
- Shpg. 3 lbs.

140 RPM, 12 VDC Gearmotor



ITEM 5-1765
\$9.95

• New, compact inline permanent magnet gearmotor.

SPECIFICATIONS

- Speed 140 RPM
- Voltage 12 DC
- Amperage 0.13 Amps (no load)
- Rotation reversible
- Duty intermittent

- Mount 3 M3 tapped holes on face
- Shaft 5mm dia. x 10mm w/flat
- Size 1 1/4" dia. x 2 7/16"
- Shpg. 1/2 lb.