

Humphrey Multi-Mount Air Cylinders

• New, HUMPHREY. Multi-mount style air cylinders. Aluminum construction, rated to 100 PSI working pressure. 10-32 ports.

Bore - Rod Dimensions

$\frac{1}{4}'' = 0.118''$ $\frac{3}{8}'' = 0.197''$ $\frac{5}{8}'' = 0.236''$

Single Acting
Push Only



ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10621	1/4"	1/4"	2.14"	1/2 lb.	\$5.95
4-10622	3/8"	1/4"	2.337"	3/4 lb.	\$5.95
4-10633	3/8"	1/2"	2.587"	3/4 lb.	\$5.95
4-10640	5/8"	1/4"	2.533"	1/2 lb.	\$6.95
4-10647	5/8"	1/2"	2.783"	3/4 lb.	\$6.95

Double Acting

ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10618	1/4"	1/2"	2.193"	1/2 lb.	\$5.95
4-10613	1/4"	3/4"	2.443"	1/2 lb.	\$5.95
4-10631	3/8"	3/4"	2.64"	1/2 lb.	\$5.95
4-10637	5/8"	3/4"	2.837"	1 lb.	\$7.99

Double Acting
Double Rod



ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10627	3/8"	1/2"	3.4375"	1/4 lb.	\$16.95
4-10630	3/8"	3/4"	3.902"	1/2 lb.	\$8.95
4-10649	5/8"	1/2"	3.677"	3/4 lb.	\$9.95
4-10636	5/8"	3/4"	4.177"	3/4 lb.	\$9.95

12 mm x 2 3/4" DA Air Cylinder



ITEM 4-1630 **\$5.95**

• New, FESTO Model DO-12-74-PP-SA air cylinder. Stainless steel tubing with aluminum end-caps. 10-32 ports with adapters to 1/16" hosebarbs. Rod end threaded 4 mm, 0.70" pitch. Base end-cap tapped 4 mm, 0.70" pitch. Cushions at both ends of stroke.

SPECIFICATIONS

- Press. 8 Bar (116 PSI) max
- Double Acting
- Bore 12 mm (0.472")
- Stroke 2 3/4"
- Rod dia. 4 mm (0.156")
- Ports 1/16" hosebarbs
- Retracted lgth. 6 3/4" end-to-end
- Shpg. 1 lb.

3/4" Bore Air Cylinder



ITEM 4-1761-A **\$4.95**

• Used BIMBA stainless steel. Extend port in base, retract port in rod end. P/N 53E743. Stroke 3/4", retracted lgth. 5" (rod end to base end).

SPECIFICATIONS

- Double acting
- Bore 3/4"
- PSI max. 250
- Rod diam. 1/4"
- Ports 1/8" NPT
- Threaded rod end 1/4"-28 x 1/2" long
- Nose mount threaded 5/8"-18
- Flat base 0.81" O.D.
- Shpg. 1 lb.

Double Acting Pneumatic Cylinders

• New. BUYERS double acting pneumatic cylinder. Has a cushion valve on each end. H Models have hinge mount accessory kit. Ideal for remote tailgate latches.

SPECIFICATIONS

• Double Acting

• Gland Retainer Tie-Rod
• Pressure 200 PSI

• Ports 1/4" NPT
• Rod End Clevis w/ Jam Nut

• Base End Clevis
• Pin Holes 1/2"

ITEM	Rod				Shpg.	Price
	Bore	Stroke	Dia.	R. Lgth.		
4-1968-6	2.5"	6"	0.75"	14.5"	8.5 lbs.	\$91.40
4-1968-8	2.5"	8"	0.75"	16.5"	8.5 lbs.	\$91.80
4-1968-8-H	2.5"	8"	0.75"	16.5"	9.5 lbs.	\$103.25
4-1969-6	3.25"	6"	1"	16.25"	11 lbs.	\$112.35
4-1969-8	3.25"	8"	1"	18.25"	13 lbs.	\$132.45
4-1969-8-H	3.25"	8"	1"	18.25"	14 lbs.	\$150.05




4-1968-6



4-1968-8-H

7.5 CFM, Single Stage Air Compressor



ITEM 4-1916
\$149.95

• New, V-twin cylinder single stage air compressor. Cast iron block and cylinder with aluminum head. Oil level sight glass.

SPECIFICATIONS

- One stage, two cylinders
- Flywheel 10 1/2" A belt
- Flow: 7.5 CFM open flow
- Port 1/2" OD tube
- 4.28 CFM at 110 PSI
- Pressure 115 PSI max.
- 1st stage bore/stroke 55mm x 45mm
- Power reqd. 2 HP max.
- Mount 6 7/8" x 3 5/8"
- Speed 980 RPM max.
- Size 13" x 10 1/2" x 10 1/2"
- Rotation CCW
- Shpg. 37 lbs.

Air Filter Pair



ITEM 4-1930 **\$4.95**

• New, pair of plastic housing air filters for air compressors. Uses paper element.

SPECIFICATIONS

1/2" NPT connection 4" dia x 2"
1/2" inlet tube Shpg 1 lb.

2" x 8" Air Cylinder



ITEM 4-1971 **\$89.95**

• New, BIMBA, TRD, model CYL-9929418 double acting air cylinder. Tie-rod construction. Foot mounted. Cylinder has a integrated cushion valve on each end.

SPECIFICATIONS

- Model CYL-9929418
- Double Acting
- Bore/Stroke 2" x 8"
- Rod 5/8" dia.
- Pressure 250 PSI max
- Ports 3/8" NPT Ports
- Rod 7/16"-20 UNF thread
- Mounting Pattern 10 7/8" x 3 1/4"
- Overall Retracted Length 13 3/4"
- Shpg 6 lbs.

7/16" x 1" Double Ended



ITEM 4-1705 **\$5.95**

• New, BIMBA. Nose mount each end. Spring loaded to one end, only moves to one side.

SPECIFICATIONS

- Double Acting
- Rod diam. 3/16" w/10-32 UNF threaded ends
- w/spring return
- Mtg. threads 3/8"-24
- Bore/stroke 7/16" x 1"
- Mtg. distance 4 1/4"
- 250 PSI
- Overall length 8 1/4"
- Ports 10-32
- Shpg. 1/2 lb.

115 VAC Solenoid Valve

ITEM 4-1922

\$8.95

• New PARKER model 15-200470-001B solenoid valve. Normally closed, furnished with brass right angle hose barb adapters (1/4" ID on inlet and 1/8" ID on outlet). Stainless steel body.

SPECIFICATIONS

- Voltage 115 VAC
- Power consumption 6 Watts
- Pressure Rating 10 PSI
- Orifice 1/8"
- Ports 1/8" NPT
- Size 2" x 1 3/8" x 2 1/4"
- Shpg. 1 lb.



1/4 NPT Vacuum Regulator

ITEM 4-1962

\$39.95

• New, FAIRCHILD, model 17132NNKN, vacuum regulator. High accuracy independent of vacuum supply and flow demand. Gauges not included. Aluminum housing.

SPECIFICATIONS

- Vacuum Supply 30" Hg max.
- Temperature Range -40° to 200°F
- Vacuum Range 0-30 inHg
- Gauge Ports Two 1/4" NPT (plugs installed)
- In/Out Ports 1/4" NPT
- Size 2 1/8" dia. x 6"
- Flow Capacity 3 cfm@ 25" Hg supply
- Shpg. 2 lbs.



1/4" NPT Mini Air Regulator w/gauge

ITEM 4-9094

• New, Campbell Hausfeld part number RE206901AV. Inline air pressure regulator with gauge.

SPECIFICATIONS

- Inlet Pressure 200 PSI max.
- Gauge Port 1/8" NPT
- Outlet Pressure Range 0-135 PSI
- Ports 1/4" NPT
- Gauge Port 1/8" NPT
- Size 3 5/8" x 1 1/2" x 2 3/4"
- Shpg. 1/2 lb.



\$5.95

24 VAC Solenoid Valve

ITEM 20-1311

\$9.99

• New, ASCO. Operates on 24 VAC, 6 watts. Ports 1/8" NPT. Pressure ratings air 275 PSI, water 200 PSI, oil 150 PSI. Normally open two ways. Brass body. Size 3 1/4" x 2" x 1 1/2". Shpg. 1 1/2 lbs.

