

### 20 x 8.00-8 Wheel Assembly

ITEM 1-5783

**\$54.95**

• New, Carlisle Turf Saver tire on gray painted steel wheel. Not for Highway service.

**SPECIFICATIONS**

- Size 20x8.00-8
- O.D. 18"
- Tread Turf
- Tread width 6 1/2"
- Cross Section 9"
- Bore 3/4" dia. keyed
- Bore Thru-Length 4 1/2"
- Load Capacity 600 lbs.
- Pressure 10 PSI
- Hub Offset 3/4"
- Bushing Steel
- Tube Type
- Ply Rating 2 Ply
- Acutal wt. 17 lbs.
- Shpg 30 lbs.



### 20 x 10.00-8 Turf Tire and Wheel

ITEM 1-5816

**\$44.95**

• New CARLISLE Turfsaver tire on steel rim. OEM part number 634-04295 for Cub Cadet LT Tractors and RZT mowers. Ideal replacement for many types of mowers. Not for Highway Service

**SPECIFICATIONS**

- Size 20x10.00-8
- O.D. 19.5"
- Tread Turf
- Tread Width 9"
- Backspace 3 1/4"
- Tubeless
- Mount: 4 hole on 4" B.C. 2 1/2" dia. pilot
- Ply Rating 2
- Ply Material Nylon
- Actual weight 22 lbs.
- Shpg. 30 lbs.



### 18 x 10.50-10 Smooth Tire and Wheel

ITEM 1-5511

**\$59.95**

• New CARLISLE SMOOTH model 1L0169 tire on yellow 4 bolt steel rim. Not for Highway Service.


**SPECIFICATIONS**

- Size 18X10.50-10
- O.D. 18.4"
- Tread Smooth
- Tread Width 6 1/2"
- Mount: 4 hole on 4" B.C. 2 1/2" dia. pilot
- Backspace 4"
- Tubeless
- Load Rating 1100 lbs. @ 24 PSI
- Ply Rating 4
- Ply Material Nylon
- Actual weight 22 lbs.
- Shpg. 30 lbs.



### Trailer Bearing Kits

• Brand new, DURA-ROLL replacement trailer bearing kit. Use with boat, camping, utility and snowmobile trailers. 1 kit per wheel required. Bearings must be packed with grease before installation. Kit contents available at [www.surpluscenter.com](http://www.surpluscenter.com). Fully tested and exceeds VESC regulations. Installation instructions included.



ITEM	Typical Axle Bearing Bore		Rating (lbs.)	Shpg.	Price
	Inner	Outer			
1-3535	1"	1"	2000	1 lb.	\$14.85
1-3536	3/4"	3/4"	2000	1 lb.	\$11.90
1-3537	1 1/4"	1 1/4"	2000	1 1/2 lbs.	\$14.35
1-3538	1 3/8"	1 1/16"	3500	1 lb.	\$15.00
1-3539	1 1/16"	1 1/16"	2000	1 lb.	\$14.50

### 18 x 6.50-8 Wheel Assembly

ITEM 1-5725

**\$32.99**

• New, WANDA pneumatic tire mounted on steel rim. NOT for Highway Service.

**SPECIFICATIONS**

- Size 18x6.50-8
- Outside Diameter 18" dia.
- Cross Section 6 1/2" Wide
- Tread Knobby
- Tread Width 5 1/2"
- Bore 1"
- Bore Thru-Length 3"
- Hub Type Centered
- Tire Tubeless
- Load Rating 330 lbs. @ 10 PSI
- Ply Rating 2
- Shpg. 16 lbs.



### 15 x 5.00-6 Pair of Snowblower Tires

ITEM 1-5841

**\$49.95**

• New pair of CARLISLE model X-TRAC tires mounted on gray painted steel wheels. Built for snow blowers. Directional lug tread mounted with 3/16" diameter cross-hole to outside. Not for Highway Service.

**SPECIFICATIONS**

- Size 15X5.00-6
- O.D. 14"
- Tread Directional lug
- Tread width 4 1/4"
- Bore 3/4" diam.
- Bore Thru-Length 4 1/2"
- Load Range 395 lbs.
- Max. Pressure 20 PSI
- Outside Rim Width 3 1/2"
- Bearing Type None
- Hub Offset
- Inner hub to crosshole length 4.950"
- Offset 1 1/2"
- Tubeless
- Ply Rating 2 Ply
- Shpg. 20 lbs.



### 13 x 5.00-6 Wheel Assembly

ITEM 1-4068-O

**\$19.99**

• New, tubeless tires on orange painted steel wheel. Grease zerk for axle. Not for Highway Service.

**SPECIFICATIONS**

- Size 13X5.00-6
- O.D. 12"
- Tread Turf
- Tread width 4"
- Bore 3/4" diam.
- Bore Thru-Length 3"
- Pressure 30 PSI
- Hub Offset 3/4"
- Bushing Steel
- Tube Type InnerTube
- Ply Rating 2 Ply
- Shpg. 8 lbs.



### Hi-Speed Wheel Hubs



• Brand new. Use with a 1" diameter spindle to mount high speed wheels on small trailers. Includes grease cap, tapered roller bearings and seal. **7 lbs.**

ITEM	Bolt			Price
	Bolts	Circle	Type	
1-1133	4	4"	Lug Bolt	\$43.95
1-1134	5	4 1/2"	Lug Bolt	\$46.70
1-4884	4	4"	Stud	\$45.05
1-4885	5	4 1/2"	Stud	\$48.00

### 1" Trailer Spindle

ITEM 1-1128

• Brand new steel trailer spindle with castle nut. 1" diam. x 8 1/2" long. **Shpg. 4 lbs.**



### 13 X 5.00-6 Pair Snowblower Wheels

ITEM 1-5833

**\$36.95**

• New pair of CARLISLE model X-TRAC tires mounted on black painted steel wheels. Built for snow blowers. Directional lug tread mounted with 1/4" diameter cross-hole to outside. Not for highway service.

**SPECIFICATIONS**

- Size 13X5.00-6
- O.D. 12"
- Tread Directional lug
- Tread width 4 1/2"
- Bore 3/4" diam.
- Bore Thru-Length 4 1/2"
- Max. Pressure 20 PSI
- Offset None
- Crosshole Diameter 1/4"
- Load Range 290 lbs. (per tire)
- Hub Smooth w/crosshole
- Inner hub to crosshole length 4 1/4"
- Tubeless
- Ply Rating 2 Ply
- Shpg. 19 lbs.



### 4.80-8 Trailer Wheel Assembly

ITEM 1-5711

**\$19.95**

• New, WANDA JOURNEY pneumatic tire mounted on steel rim. Ideal replacement log splitter and small trailer wheel for high speed trailer use. Small trailer use only DOT R2A3 max. Grease seal and roller bearings in the hub. Dust cover NOT included.

**SPECIFICATIONS**

- Size 4.80-8
- Outside Diameter 15 3/4"
- Cross Section 4 1/2" Wide
- Tread Sawtooth
- Tread Width 3"
- Bore 1"
- Bore Thru-Length 4 3/16"
- Bearing Thru-Length 3 1/2"
- Hub Type Centered
- Bearing Roller Bearing
- Tire Tubeless
- Load Rating 590 lbs. at 60 PSI, load range B
- Ply Rating 4
- Shpg. 14 lbs.



### 4.80-12 Trailer Wheel Assembly

ITEM 1-5717

**\$32.99**

• New, WANDA pneumatic tire mounted on steel rim. Ideal replacement log splitter and small trailer wheel for high speed trailer use.

**SPECIFICATIONS**

- Size 4.80-12
- Outside Diameter 20" dia.
- Cross Section 5" Wide
- Tread Turf
- Tread Width 3 1/4"
- Hub Type Offset
- Mount: 5 hole on 4 1/2" B.C. 2 3/4" dia. pilot
- Tire Tubeless
- Load Rating 785 lbs. @ 60 PSI max (DOT-R2B5)
- Ply Rating 4
- Shpg. 20 lbs.



### 8" x 5.5" Steel Wheel Rim w/Bearings

ITEM 1-5079

**\$5.99**

• New take-offs, black steel rim with dual ball bearings for 8" tires.

**SPECIFICATIONS**

- Wheel Rim Size 8" X 5.5"
- O.D. 8 7/8"
- Width 6 5/16"
- Hub 3/4" Bore x 3 1/16" wide
- Hub Type Offset
- Shpg. 8 lbs.

