

### Rigid Caster Yokes



• New, TENTE rigid plate caster yoke.

#### SPECIFICATIONS

- Wheel Width 2"
- Brake None
- Top Plate 4 1/2" x 4" x 1/4" thick
- Mount 4 holes on 3 3/4"-3" x 3 1/8"-2 5/8" centers
- Bolt Holes 7/16" dia.
- Wheel Bore 1/2"
- Shpg. 3 lbs.

#### ITEM 1-5381

4" Wheel Rigid Plate Caster Yoke

**\$1.49**

#### ITEM 1-5382

6" Wheel Rigid Plate Caster Yoke

**\$1.49**

### 6" x 2" Rigid Plate Caster



#### ITEM 1-5798

**\$4.95**

• New, ER Wagner caster. Polyolefin wheel with thread guards. Plain bearing.

#### SPECIFICATIONS

- Wheel Size 6" dia. x 2"
- Load Capacity 400 lbs.
- Top Plate 2 3/4" x 3 3/4"
- Mounting height 7 1/2"
- Mount 1 3/4" x 2 5/8" slotted to 3"
- Bolt Holes 5/16"
- Shpg. 3 lbs.

### 6" x 2" Rigid Plate Caster



#### ITEM 1-4067-R

**\$10.95**

• New, JARVIS rigid plate caster with Triton polypropylene wheel. Steel caster yoke. Travel in height 0.486".

#### SPECIFICATIONS

- Wheel Size 6" x 2"
- Load Capacity 1250 lbs.
- Top Plate 4" x 4 1/2"
- Mounting height 7 1/2"
- Mount 2 5/8" x 3 5/8" slotted to 3" x 3"
- Bolt Holes 3/8"
- Shpg. 6 lbs.

### 5 15/16" x 1 1/4" Rigid Plate Caster



#### ITEM 1-4425

**\$5.95**

• New, RHOMBUS rigid plate caster. Thermoplastic polyurethane tire on steel rim. Ball bearings in hub. Plated steel yoke. Steel thread guard.

#### SPECIFICATIONS

- Wheel Size 5 15/16" dia. x 1 1/4"
- Load Capacity 242 lbs.
- Top Plate 3 3/4" x 2 3/4"
- Mounting height 7 7/16"
- Mount 4 bolt holes on 2 1/8" x 1 3/4" to 3" x 2 1/8" centers
- Bolt Holes 5/16" dia.
- Shpg. 3 lbs.

### 5" x 1 1/2" Swivel Plate Caster



#### ITEM 1-5865

**\$5.95**

• New, TENTE swivel plate caster with elastic-tire tread on polyamide wheel. Swivel plate has double-row ball bearings.

#### SPECIFICATIONS

- Wheel Diameter 5" dia. (4.92" dia.)
- Wheel Width 1-1/2" (1.57") Wide
- Load Capacity 550 lbs.
- Mounting Height 6.34"
- Brake None
- Top Plate 5.39" x 4.13" x 0.15" thick
- Mount 4 slots on 4.13" x 3.15" to 2.95" centers
- Bolt Holes 0.433" dia.
- Wheel Tread Material Black Elastic-Tire
- Caster Wheel Core Material Polyamide
- Caster Wheel Bearing Roller
- Shpg. 5 lbs.

### 5" x 1 1/4" Swivel Plate Caster



#### ITEM 1-5238

**\$5.95**

• New, COLSON swivel plate caster with soft rubber wheel. Swivel plate has double-row ball bearings. Zinc plated caster yoke.

#### SPECIFICATIONS

- Model Number FG5SP01052GSSM
- Wheel Diameter 5" dia.
- Wheel Width 1 1/4" Wide
- Load Capacity 200 lbs.
- Mounting Height 6 1/8"
- Brake None
- Top Plate 3 5/8" x 2 1/2" x 1/8" thick
- Mount 4 holes on 2 15/16" x 1 1/4" centers
- Bolt Holes 5/16" dia.
- Wheel Tread Material Soft Rubber
- Wheel Tread Color Black
- Caster Wheel Core Material Soft Rubber
- Caster Wheel Bearing Roller
- Shpg. 3 lbs.

### 5" x 1 1/4" Scaffold Caster w/Brake



#### ITEM 1-5237

**\$9.95**

• New, swivel grip ring stem caster with solid rubber wheel. Originally intended for use on scaffolds. Circular mounting face has two ends bent upwards 90 degrees on either side of the stem, inside width of 1 1/16". Wheel and swivel lock. Swivel has double-row ball bearings. Zinc plated caster yoke.

#### SPECIFICATIONS

- Wheel Diameter 5" dia.
- Wheel Width 1 1/4" Wide
- Load Capacity 264 lbs.
- Mounting Height 6 3/8"
- Brake Wheel and Swivel Lock
- Mount 26mm (1.025") dia. x 2 3/4" w/ circlip
- Stem through Holes 7/16" dia.
- Wheel Tread Material Black Rubber
- Caster Wheel Core Material Rubber
- Caster Wheel Bearing None
- Shpg. 4 lbs.

### 5" x 1 1/4" Swivel Plate Caster w/ Swivel Lock



#### ITEM 1-3287-A

**\$6.99**

• New, RHOMBUS swivel plate caster. Metal lever single position swivel lock (does not lock wheel). Thermoplastic polyurethane wheel with plastic wheel center.

#### SPECIFICATIONS

- Wheel size 5" x 1 1/4"
- Load capacity 220 lbs.
- Top plate 2 3/4" x 3 3/4" x 1/8"
- Mounting height 6 3/8"
- Mount four bolt on 1 7/8" x 2 7/8" ctrs.
- Bolt holes 5/16" diam.
- Shpg. 3 lbs.

### 5" x 1 1/4" Swivel Plate Caster w/Brake



#### ITEM 1-5244

**\$4.95**

• New, COLSON swivel plate caster with hard plastic wheel. Swivel plate has double-row ball bearings. Zinc plated steel yoke.

#### SPECIFICATIONS

- Wheel Size 5" dia. x 1 1/4" w.
- Load Capacity 125 lbs.
- Mounting Height 5 13/16"
- Brake Wheel Lock
- Top Plate 3 5/8" x 2 1/2" x 3/32" thick
- Mount 4 holes on 3 1/16" x 1 1/4" centers
- Bolt Holes 5/16" dia.
- Wheel Tread Gray Thermoplastic Rubber
- Shpg. 1 1/2 lbs.

### 5" x 1 1/4" Swivel Stem Caster



#### ITEM 1-5685

**\$2.95**

• New, TENTE round stem caster threadguards.

#### SPECIFICATIONS

- Wheel Diameter 5"
- Wheel Width 1 1/4"
- Load Capacity 220 lbs.
- Mounting Height 6 3/8"
- Mount 3/4" x 1 1/2" long round stem w/ M8-1.25 threaded crosshole
- Brake None
- Wheel Tread Material Grey Thermoplastic Rubber
- Caster Wheel Core Material Polypropylene
- Caster Wheel Bearing Ball
- Shpg. 2 lbs.

#### ITEM 1-5685-B

w/Brake and Swivel Lock

**\$3.95**

### 5" x 1 1/4" Swivel Plate Caster



#### ITEM 1-5868

**\$3.95**

• New, TENTE swivel plate caster. Swivel plate has double-row ball bearings.

#### SPECIFICATIONS

- Wheel Diameter 5" dia.
- Wheel Width 1 1/4" Wide
- Load Capacity 220 lbs.
- Mounting Height 6.34"
- Top Plate 3.03" x 2.64" x 0.11" thick
- Mount 4 slots on 2.42 to 2.2" x 2.03" to 1.83" centers
- Brake None
- Bolt Holes 5/16" dia.
- Wheel Tread Material Grey TENTEprene (Thermoplastic Rubber)
- Caster Wheel Core Material Polypropylene
- Caster Wheel Bearing Ball
- Shpg. 2 lbs.

### 4" x 1" Rigid Plate Caster



#### ITEM 1-4460

**\$1.95**

• New, RHOMBUS plate caster.

#### SPECIFICATIONS

- Wheel Diameter 4"
- Wheel Width 1"
- Load Capacity 150 lbs.
- Mounting Height 5"
- Brake None
- Top Plate 4 1/16" x 3 5/16" x 3/32"
- Mount Four slots
- Bolt Holes 14mm (0.551") x 9mm (0.354")
- Wheel Tread Material Solid Black Rubber
- Caster Wheel Core Material Plastic
- Caster Wheel Bearing Roller
- Shpg. 2 lbs.

### 3" x 1 1/4" Swivel Plate Caster



#### ITEM 1-4065

**\$4.95**

• New JARVIS adjustable height swivel plate caster. Polyolefin wheel. Steel caster yoke. Travel in height 0.486".

#### SPECIFICATIONS

- Wheel Size 3" dia. x 1 1/4"
- Load Capacity 180 lbs.
- Top Plate: 3 1/4" x 2 1/16" x 3/16" thick
- Bolt Holes 5/16" dia.
- Mounting height 5 7/8" up to 6 3/8"
- Mount: 4 bolt on 2 5/8" x 1 1/8" centers
- Shpg. 3 lbs.

### 3" x 1 13/16" Swivel Plate Caster



#### ITEM 1-1195

**\$3.99**

• Removed from service. FAULTLESS heavy duty swivel plate caster. Low profile design. Glass filled nylon wheel. Roller wheel bearing with swivel ball bearing plate.

#### SPECIFICATIONS

- Wheel size 3" diam. x 1 13/16" wide
- Load capacity 700 lbs.
- Top plate 3 1/8" x 4 1/8" x 3/16" thick
- Mounting height 3 3/16"
- Mount four bolt on 3 3/8" x 2 3/8" centers
- Bolt holes 5/16" diam.
- Shpg. 3 lbs.