

5" x 1 1/2" Swivel Stem Caster

w/ Swivel & Wheel Lock

ITEM 1-3311

\$19.99

• New, FAULTLESS swivel stem caster. Originally intended for scaffold. Swivel and wheel lock. Solid hard rubber wheel. Zinc plated steel yoke.

SPECIFICATIONS

- Wheel size 5" x 1 1/2"
- Load capacity 325 lbs.
- Mounting height 6 1/4"
- Stem friction grip stem mount 1" dia. x 2 1/2"
- Shpg. 6 lbs.



5" x 1 5/16" Threaded Stem Swivel Caster

ITEM 1-4751

\$3.95

• New, FAULTLESS model# 30807 threaded stem caster. Ball bearing in swivel head.

SPECIFICATIONS

- Wheel Diameter 5"
- Wheel Width 1 9/16"
- Load Capacity 125 lbs.
- Mounting Height 5 3/4"
- Wheel Tread Grey TPR
- Mount 1/2"-13 x 1 1/2" long threaded stem
- Caster Wheel Core Polypropylene
- Caster Wheel Bearing Plain
- Shpg. 2 1/2 lbs.



3" x 1 3/16" Rigid Stem Caster

ITEM 1-3394

\$1.99

• New, FAULTLESS rigid stem caster. "DYNA-TRED II" thermoplastic rubber on polypropylene. Zinc plated caster yoke.

SPECIFICATIONS

- Wheel size 3" x 1 3/16"
- Load capacity 90 lbs.
- Mounting height 3 1/2"
- Stem grip ring 7/16" dia. x 2"
- Shpg. 1 lb.



5" x 1 1/4" Swivel Plain Stem Caster

ITEM 1-4538

\$4.95

• New, MEDCASTER model# HC05RPP125TLCL02 plain stem caster with sheet metal threadguards and central total brake. Intended for use with hospital beds. Braking mechanism is operated by rotating 11mm (0.433") hex.

SPECIFICATIONS

- Wheel Size 5" x 1 1/4"
- Load Capacity 260 lbs.
- Mounting Height 6 7/8"
- Brake Wheel and Swivel Caster Wheel Bearing Ball
- Mount 32mm x 2" long plane stem w/ two M6-1.0 tapped bolt holes
- Wheel Tread Grey TPR
- Caster Wheel Core Material Polypropylene
- Shpg. 5 lbs.



5" x 1 5/16" Threaded Stem Swivel Caster w/ Brake

ITEM 1-4234

\$3.95

• New, FAULTLESS swivel threaded stem caster with brake. Zinc plated steel yoke. Solid polypropylene wheel.

SPECIFICATIONS

- Wheel Size 5" dia. x 1 5/16" wide
- Load Capacity 150 lbs.
- Stem Threaded
- Mounting height 5 13/16"
- Mount: 1/2"-13 x 1 1/2"
- Shpg. 1 1/2 lbs.



3" x 1/2" Swivel Stem Caster w/ Brake

ITEM 1-5146

\$1.99

• New, TENTE swivel threaded stem caster with wheel brake.

SPECIFICATIONS

- Wheel Diameter 3" (2.95")
- Wheel Width 1/2" tread, 2" overall
- Load Capacity 110 lbs.
- Mounting Height 3"
- Mount M10-1.5 x 5/8" long threaded stem
- Brake Wheel
- Wheel Tread Material Black Elastic Tire
- Caster Wheel Core Material Polyamide
- Caster Wheel Bearing Plain
- Shpg. 1 lb.



5" x 1 1/8" Swivel Stem Caster

ITEM 1-1591

\$6.95

• New. Ball bearing swivel stem caster with 5" diam. x 1 1/8" wide cushion rubber wheel. 7/16" diam. x 1 1/2" stem with retention ring. 150 lb. capacity. Shpg. 4 lbs.



4" x 2 1/2" Swivel Stem Caster w/ Brake

ITEM 1-4635

\$2.95

• New, threaded stem swivel caster.

SPECIFICATIONS

- Wheel Diameter 4" dia.
- Wheel Width 2 1/2" Wide
- Load Capacity 100 lbs.
- Mounting Height 4 1/2"
- Brake Wheel lock
- Mount 1/2"-13 threaded stem, 1" long
- Wheel Tread Material Black Plastic
- Caster Wheel Core Material Plastic
- Caster Wheel Bearing Plain
- Shpg. 2 lbs.



3" x 7/16" Swivel Stem Caster w/ Brake

ITEM 1-4758

\$2.99

• New, SHEPHERD threaded stem caster with total brake.

SPECIFICATIONS

- Wheel Diameter 3"
- Wheel Width 7/16" tread, 2 5/16" overall
- Load Capacity 165 lbs.
- Mounting Height 3 3/4"
- Mount 1/2"-13 x 1" long threaded stem
- Brake Wheel and Swivel
- Wheel Tread Material Gray Urethane
- Caster Wheel Core Material Polyolefin
- Caster Wheel Bearing Plain
- Shpg. 1.5 lbs.



5" x 1 5/16" Swivel Stem Caster w/ Wheel Lock

ITEM 1-3307

\$5.99

• New FAULTLESS swivel stem caster with wheel lock. Thermoplastic tire on black polypropylene wheel.

SPECIFICATIONS

- Wheel size 5" x 1 5/16"
- Load capacity 125 lbs.
- Mounting height 5 3/4"
- Stem threaded 1/2"-13 x 1 1/2"
- Shpg. 1 1/2 lbs.



4" x 1" Grip Ring Caster

ITEM 1-3766

\$2.99

• New, JARVIS swivel grip ring stem caster. Solid polyolefin wheel. Plated steel caster yoke.

SPECIFICATIONS

- Wheel size 4" dia. x 1"
- Load capacity 150 lbs.
- Mounting height 4 9/8"
- Stem grip ring 0.845" dia. x 2"
- Shpg. 3 lbs.



2" x 7/16" Dual Wheel Swivel Stem Caster

ITEM 1-5290

39¢

• New, COLSON swivel grip ring stem dual wheel caster. Nylon frame.

SPECIFICATIONS

- Wheel Diameter 2" (50mm) dia.
- Wheel Width Each tread 1/2" Wide 1 1/8" Overall Width
- Load Capacity 75 lbs.
- Mounting Height 2 1/4"
- Pivot Boss Diameter 1 3/4"
- Brake None
- Mount 7/16" dia. x 7/8" long
- Wheel Tread Material Black Nylon
- Caster Wheel Core Material Nylon
- Caster Wheel Bearing None
- Shpg. 1/2 lb.



Grip Ring Caster Sockets



1-3667 1-3668 1-5361 1-4898

• Brand new, use to mount grip ring casters with 7/16" dia. stem into steel tubing. Shpg. 1/10 lb.

ITEM	Fits into	Length	Price
1-3667	1" OD 16 gauge tubing	1 1/2"	\$.45
1-3668	3/4" OD 16 gauge tubing	1 1/2"	\$2.55
1-5361	9/16" OD 16 gauge tubing	1 3/8"	\$.39
1-4898	Steel Corner Bracket	1 5/8"	\$.59

3" x 1 1/4" Stem Swivel Caster

ITEM 1-2404

\$5.99

• New. Swivel stem caster with 3" diam. x 1 1/4" wide solid polypropylene wheel. 1"-12 diam. x 5 1/8" threaded stem. Working height 4 1/4" (floor to base of stem). Load capacity 100 lbs. Shpg. 5 lbs.



1.5" Dual Wheel Swivel Caster Set

ITEM 1-4718

99¢

• New, set of 4 nylon hooded swivel casters with dual plastic wheels and grip ring stem. Two casters have wheel rotation locks. Independent wheel rotation in each caster.

SPECIFICATIONS

- Wheel size 1 1/2" dia. x 3/8" (2 per caster)
- Load Capacity 50 lbs. ea. (200 lbs. per set)
- Mounting height 2 1/16"
- Mount 7/16" dia. x 1" grip ring stem
- Shpg. 1/2 lb.

