

## Top Link Cylinders Control with Tractor Remote



• Brand new, AMA category 1 top link cylinder. Use in place of top link on three point hitches for adjusting implement. Built-in lock valve to prevent cylinder drift. Ships with two 3/8" BSPPM to 3/8" NPTM connectors.

### ITEM 9-7682-08 **\$219.85**

#### **SPECIFICATIONS**

- Double Acting
- Bore x Stroke 2" x 8 1/4"
- Pressure 3000

- Rod Dia. 1 3/16"
- Ports 3/8" BSP
- Retracted Length 18 1/8"
- Shpg. 18 lbs.

### ITEM 9-7682-11 **\$230.55**

#### **SPECIFICATIONS**

- Double Acting
- Bore x Stroke 2" x 11"
- Pressure 3000

- Rod Dia. 1 3/16"
- Ports 3/8" BSP
- Retracted Length 20 7/8"
- Shpg. 20 lbs.

#### **END MOUNTINGS**

- Rod End Swivel
- Outside Width 1 3/4"
- Pin Hole 3/4"

- Base End Swivel
- Outside Width 1 3/4"
- Pin Hole 3/4"

### 3" x 8" x 1 1/2"



### ITEM 9-5196 **\$358.95**

• Brand new. Use on tractors in place of top link on three point hitches to adjust implement. Double swivel adapter on base of cylinder to provide vertical and horizontal movement of hitch.

#### **SPECIFICATIONS**

- Double acting
- Bore/stroke 3" x 8"
- 3000 PSI
- Rod diam. 1 1/2"
- Ports 1/2" NPT

- Retracted Length 22"
- Self aligning swivel eye on rod, 1 3/4" wide
- Double swivel base assembly width 2"
- Pin holes 1"
- Shpg. 29 lbs.

### 3" x 8" x 1 1/2"



### ITEM 9-5152 **\$335.25**

• Brand new. Self aligning swivel eye at each end.

#### **SPECIFICATIONS**

- Double acting
- Bore/stroke 3" x 8"
- 3000 PSI
- Rod diam. 1 1/2"

- Ports 1/2" NPT
- Retracted lgth. 19 1/2"
- Swivel eye ends 1 3/4" wide
- Pin holes 1"
- Shpg. 27 lbs.

### 1" x 4" x 0.625"



### ITEM 9-7257-4 **\$139.95**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 1" x 4"
- Pressure 3000 PSI
- Rod Dia. 5/8"
- Ports SAE 6

- Retracted Length 10"
- Swivel Ball Ends
- Swivel Ball outside width 1"
- Pin Holes 1/2"
- Shpg. 5 lbs.

### 1" x 6" x 0.625"




### ITEM 9-7257-6 **\$145.05**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 1" x 6"
- Pressure 3000 PSI
- Rod Dia. 5/8"
- Ports SAE 6

- Retracted Length 12"
- Swivel-Ball Ends
- Ball width 1"
- Ball O.D. 2"
- Pin Holes 1/2"
- Shpg. 5 lbs.

### 1" x 8" Single Acting Cylinder w/ Plunger Pump



### ITEM 9-8026 **\$89.99**

• New. Originally intended for use in barber chairs. Both ports at base end of cylinder. 1/8" NPT breather in rod end gland. Spring plunger assembly mounted to cartridge block acts as pump to extend and retract cylinder. Retract cylinder by pushing plunger in at any time

#### **SPECIFICATIONS**

- Single Acting
- Bore x Stroke 1" x 8"
- Pressure 925 PSI max.
- Rod Dia. 3/4"
- Cylinder and Pump Ports: SAE 4

- Retracted Length 14 1/2"
- Rod End Threaded
- Thread size-Pitch 5/8"-18
- Base End Four Tapped Mounting Holes
- Shpg. 12 lbs.

### 1.25" x 6" x 0.75"



### ITEM 9-12885 **\$59.95**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore/Stroke 1 1/2" x 6"
- Pressure 3000 PSI
- Rod dia. 0.75
- Ports SAE 6

- Retracted Length 16.25"
- Clevis Ends
- Inside Widths 0.86"
- Pin Holes 3/4"
- Shpg. 55 lbs.

### 1.5" x 4" x 1"




### ITEM 9-7258-4 **\$120.90**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 1 1/2" x 4"
- Pressure 3000 PSI
- Rod Dia. 1"
- Ports SAE 6

- Retracted Length 11 1/4"
- Swivel-Ball Ends
- Ball width 1"
- Pin Holes 0.75"
- Shpg. 6 lbs.

### 1.5" x 6" x .5"



### ITEM 9-8651 **\$59.95**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 1 1/2" x 6"
- Pressure 1500 PSI max.
- Rod Dia. 1/2"
- Ports JIC 6 Male

- Retracted Length 12 1/2"
- Rod End Crosstube
- Width 1"
- Base End Tang
- Shpg. 7 lbs.

### 1.5" x 6" x .75"



### ITEM 9-8841 **\$69.99**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 1 1/2" x 6"
- Clevis Ends
- Outside Width 1 1/2"
- Pin Hole 1/2"

- Pressure 3000 PSI max.
- Rod Dia. 3/4"
- Ports SAE 6
- Retracted Length 13"
- Shpg. 8 lbs.

### 1.5" x 6" x 1"



### ITEM 9-7258-6 **\$142.80**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 1 1/2" x 6"
- Pressure 3000 PSI
- Rod Dia. 1"
- Ports SAE 6

- Retracted Length 13 1/4"
- Swivel-Ball Ends
- Ball width 1"
- Ball O.D. 2"
- Pin Holes 0.75"
- Shpg. 7 lbs.

### 1.5" x 8" x 1"



### ITEM 9-7258-8 **\$151.35**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 1 1/2" x 8"
- Pressure 3000 PSI
- Rod Dia. 1"
- Ports SAE 6

- Retracted Length 15 1/4"
- Swivel-Ball Ends
- Ball width 1"
- Ball O.D. 2"
- Pin Holes 0.75"
- Shpg. 9 lbs.

### 1.5" x 24" x .75"



### ITEM 9-8294 **\$69.99**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore/Stroke 1 1/2" x 24"
- Pressure 1500 PSI max.
- Rod dia. 3/4"
- Ports SAE 4

- Retracted Length 48 3/8"
- Threaded ends rod 3/4-16 x 7" base 3/4-16 x 2 1/2"
- Shpg. 15 lbs.

### 1.5" x 32" x .75"



### ITEM 9-12693 **\$79.95**

#### **SPECIFICATIONS**

- Double Acting
- Unused old inventory
- Bore x Stroke 1.5" x 32"
- Pressure 2500 PSI
- Rod Dia. 0.75"
- Ports SAE 4
- Retracted Length 47.25"

- Threaded Ends
- Thread Size-Pitch 3/4"-10
- Rod End: Thread Length 6.875"
- Base End: Thread Length 2.5"
- Shpg. 16 lbs.

### 1.75" x 14.25" x 1"



### ITEM 9-8917 **\$79.95**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 1 3/4" x 14 1/4"
- Crosstube Ends
- Width 1 7/8"
- O.D. 2"

- Pin Hole 3/4"
- Pressure 3000 PSI max.
- Rod Dia. 1"
- Ports SAE 6
- Retracted Length 28 1/4"
- Shpg. 18 lbs.



### 1" x 4" x 0.625"



### ITEM 9-7257-4 **\$139.95**

#### **SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 1" x 4"
- Pressure 3000 PSI
- Rod Dia. 5/8"
- Ports SAE 6

- Retracted Length 10"
- Swivel Ball Ends
- Swivel Ball outside width 1"
- Pin Holes 1/2"
- Shpg. 5 lbs.