

3" x 10" x 1.5"



ITEM 9-16105
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 10"
- Pressure 3000 PSI max.
- Rod Dia. 1.5"

- Ports SAE 8
- Retracted Length 18"
- Swivel-Ball Ends
- Pin Holes 1"
- Shpg. 26 lbs.

\$189.95

3" x 11.625" x 1.375"



ITEM 9-9464
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 11 5/8"
- Pressure 3000 PSI max.
- Rod Dia. 1 3/8"

- Ports SAE 6
- Retracted Length 31 3/4"
- Clevis Ends
- Pin Holes 1 1/4"
- Shpg. 43 lbs.

\$159.95

3" x 15" x 1.5"



ITEM 9-7339
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"

- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- Shpg. 60 lbs.

\$109.99

3" x 15" x 1.5"



ITEM 9-7340
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"

- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- Shpg. 60 lbs.

\$109.99

3" x 15" x 1.5"



ITEM 9-7341
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"

- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- Shpg. 60 lbs.

\$109.99

3" x 16" x 1.5"



ITEM 9-12924
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Pressure 2500 PSI
- Rod Dia. 1.5"
- Ports SAE 8

- Retracted Length 36"
- Swivel Eye Ends
- Rod End: Width 1.71"
- Base End: Width 1.76"
- Swivel Eye Width 1.375"
- Pin Holes 1 1/2"
- Shpg. 66 lbs.

\$149.95

3" x 16" x 1.75"



ITEM 9-10314

• Two independent 3" x 16" x 1.75" welded cylinders joined in the middle. Four SUN model CACA-LHN adjustable, atmospherically-referenced, vented counterbalance valves.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Rod Ends Tapped
- Thread size-Pitch 1 1/8"-12
- Thread Depth 3"
- Pressure 2500 PSI max.
- Rod Dia. 1 3/4"
- Ports SAE 6, See Above
- Overall Length 92 1/2"
- Shpg. 190 lbs.

Truck freight only

\$69.95

3" x 16" x 1.75"



ITEM 9-10315

• Two independent 3" x 16" x 1.75" welded cylinders joined in the middle. Four SUN model CACA-LHN adjustable, counter balance valves.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Rod Ends Tapped
- Thread size-Pitch 1 1/8"-12
- Thread Depth 3"
- Pressure 2500 PSI max.
- Rod Dia. 1 3/4"
- Ports SAE 6, See Above
- Retracted Length 92 1/2"
- Shpg. 190 lbs.

Truck freight only

\$69.95

3" x 16" x 1.75"



ITEM 9-10009

• Tandem welded cylinder. Two independent cylinders joined in the middle. Four counterbalance valves. Each cylinder has two bleeder valves.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Pressure 3000 PSI max.
- Rod dia. 1 3/4"
- Ports SAE 6
- Overall lgth. 62"
- Rod tapped 1 1/8"-12 x 3"
- Shpg. 107 lbs.

Truck freight only

\$69.95

3" x 19.5" x 1.5"



ITEM 9-4789
SPECIFICATIONS

- New, double acting
- Bore x Stroke 3" x 19 1/2"
- Pressure 2500 PSI max.
- Rod dia. 1 1/2"
- Ports SAE 12
- Retracted lgth. 34"
- Clevis ends 3 3/4" w.
- Pin holes 1 3/4"
- Shpg. 78 lbs.

\$99.50

3" x 20" x 1.5"



ITEM 9-16136
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 20"
- Pressure 3000 PSI max.
- Rod Dia. 1 1/2"
- Ports SAE 8
- Retracted Length 28.125"
- Rod End: Threaded
- Thread size-Pitch 1 1/4"-12"
- Base End: Clevis
- Pin Hole 1"
- Shpg. 43 lbs.

\$89.95

3" x 46" x 2"



ITEM 9-20332

SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 46.5"
- Pressure 3000 PSI max.
- Rod Dia. 2"
- Extend Port SAE 8
- Retract Port SAE 6
- Retracted Length 56.375"
- Crosstube Ends
- Pin Holes 1 1/2"
- Shpg. 123 lbs.

Truck freight only

\$229.95

3" x 46" x 2.5"



ITEM 9-9014

SPECIFICATIONS

- New, old inventory
- Double acting
- Bore x Stroke 3" x 46"
- Pressure 3000 PSI max.
- Rod dia. 2 1/2"
- Counter-balance valve with 3:1 pilot ratio.
- Wall thickness 3/16"
- Ports SAE 6
- Retracted lgth. 60"
- Crosstube ends 10 5/8" wide
- Pin holes 1 1/2"
- Shpg. 220 lbs.

Truck freight only

\$229.95

3" x 46" x 2.5"



ITEM 9-9016

SPECIFICATIONS

- New, old inventory
- Double acting
- Bore x Stroke 3" x 46"
- Pressure 3000 PSI max.
- Rod dia. 2 1/2"
- Counter-balance valve with 1.5:1 pilot ratio.
- Ports SAE 6
- Retracted lgth. 60 1/8"
- Crosstube ends 10 5/8" wide
- Pin holes 1 1/2"
- Shpg. 220 lbs.

Truck freight only

\$229.95

3" x 46.5" x 2"



ITEM 9-20294

SPECIFICATIONS

- Double Acting
- Unused old inventory
- Bore x Stroke 3" x 46.5"
- Pressure 3000 PSI
- Rod Dia. 2"
- Extend Port SAE 8
- Retract Port SAE 6
- Retracted Length 56.25"
- Crosstube Ends
- Width 6.375"
- Pin Hole 1 1/2"
- Shpg. 122 lbs.

Truck freight only

\$229.95

3" x 49.25" x 2.5"



ITEM 9-9034

SPECIFICATIONS

- New, old inventory
- Double acting
- Bore x Stroke 3" x 49 1/4"
- Pressure 3000 PSI max.
- Rod dia. 2 1/2"
- Counter-balance valve with 1.5:1 pilot ratio.
- Ports SAE 6
- Retracted lgth. 63 1/8"
- Crosstube ends rod 3 1/8" w., base 4 5/8" w.
- Pin holes 1 3/4"
- Shpg. 139 lbs.

Truck freight only

\$294.95

- Bore** - Inside diameter of cylinder
- Stroke** - How far a cylinder extends out
- R-length** - Distance in inches between pin centers when cylinder is retracted
- Rod Diameter** - Diameter of cylinder rod
- Single Acting** - Cylinder is powered one way

- Double Acting** - Cylinder is powered both ways (two way)
- Crosstube End** - Round tube welded perpendicular to cylinder
- Single Eye End** - For mounting between two mounting ears.
- Clevis End** - Two mounting ears