

### 13.5 HP Briggs & Stratton Engine

ITEM 28-2011   
**\$649.95**



• New, BRIGGS & STRATTON XR Professional series horizontal shaft engine. Engine feature overhead valves, cast iron sleeve liner, ball bearing supported crankshaft, muffler, mechanical governor, electronic ignition, fuel valve and easy to use controls. Not for sale in California.

**SPECIFICATIONS**

- Model 25T2370085F1
- Engine Family XR Professional
- Power 13.5 HP (Gross)
- Torque 21.0 ft-lbs (Gross)
- Disp. 420 cc
- Speed 3600 RPM
- Start 12 Volt Electric Start and Recoil
- Charging System 10 Amps
- Fuel Tank 1.709 Gallon
- Shaft Horizontal
- Shaft 1" dia. x 3<sup>31</sup>/<sub>64</sub>" keyed, tapped 7<sup>16</sup>/<sub>64</sub>"-20 UNF
- Accessory Mount
- Inner 4 bolt on 5" B.C.
- Outer 4 bolt on 6.5" B.C.
- Size 12<sup>1</sup>/<sub>4</sub>" X 20<sup>3</sup>/<sub>8</sub>" x 18<sup>1</sup>/<sub>2</sub>"
- Shpg. 131 lbs.

Truck freight only.

### Engine and Compressor Mounting Plate

ITEM 1-3609-B  
**\$29.95**



• Unused old inventory. Engine and air compressor mounting plate for air reservoir. Some surface rust and abrasions from storage. Two 3/4" dia. notches for accomodating a handle on the compressor mount side of mounting plate. Constructed of 11 gauge unpainted steel.

**SPECIFICATIONS**

- Primary Mounting Side
- Engine Mount Four Slots for 5/16" dia. bolt
- Engine Mount Dimensions 6<sup>7</sup>/<sub>8</sub>" to 7<sup>1</sup>/<sub>4</sub>" x 3<sup>1</sup>/<sub>8</sub>" centers
- Size 16" x 9" x 3<sup>1</sup>/<sub>16</sub>"
- Compressor Mount Four 1/4" dia. holes
- Compressor Mount Dimensions 5<sup>3</sup>/<sub>4</sub>" x 2<sup>1</sup>/<sub>2</sub>" centers
- Shpg. 10 lbs.

### Magnetic Engine Block Heaters

• Brand new, KAT'S MAGNUM HAN-DI-HEAT magnetic heaters. General application usage includes hydraulic reservoirs, thawing frozen locks, pipes, gutters and live stock feeders.

 **200 Watt**

ITEM 11-3396  
**\$84.95**



• Ideal for small engine blocks. Thermostatically controlled.

**SPECIFICATIONS**

- Voltage 120 VAC
- Power 200 W
- Cord Length 43"
- Heated surface dimension 3<sup>3</sup>/<sub>4</sub>" x 2<sup>1</sup>/<sub>4</sub>"
- Size 6<sup>1</sup>/<sub>2</sub>" x 2<sup>1</sup>/<sub>4</sub>" x 2"
- Shpg. 1 lb.

 **300 Watt**

ITEM 11-3397  
**\$141.00**



• Ideal for car and truck engine blocks.

**SPECIFICATIONS**

- Voltage 120 VAC
- Power 300 W
- Cord Length 42"
- Heated surface dimension 4<sup>1</sup>/<sub>8</sub>" x 5"
- Size 7" x 5" x 2"
- Shpg. 1 1/2 lbs.

### 11.7 HP 389cc Honda Engine

ITEM 28-1914-B   
**\$679.95**



• New, HONDA GX series. Engines feature overhead valves, cast iron sleeve liner, ball bearing supported crankshaft, mechanical governor, low-oil sensor, electronic ignition, fuel valve and easy to use controls. Meets EPA and CARB emission regulations for all states.

**SPECIFICATIONS**

- Model GX390T2QAPW
- Engine Family GX
- Power 11.7 HP
- Torque 19.51 ft-lbs
- Disp. 389 cc
- Speed 3600 RPM
- Start Recoil
- Fuel Tank 6.4 quarts
- Shaft Horizontal
- Shaft 1" dia. x 3<sup>21</sup>/<sub>32</sub>" keyed, tapped 7<sup>16</sup>/<sub>64</sub>"-20 UNF
- Accessory Mount
- Inner 4 bolt on 5" B.C.
- Outer 4 bolt on 6.5" B.C.
- Size 14" X 18" X 17<sup>1</sup>/<sub>2</sub>"
- Shpg. 81 lbs.

### 8.5 HP Honda Engine

ITEM 28-2005  
**\$449.95**



• New, HONDA GX series horizontal shaft engine. Replacement engine for generator use and other applications using a tapered shaft. Engines feature overhead valves, cast iron sleeve liner, ball bearing supported crankshaft, mechanical governor, low-oil sensor, electronic ignition, ON/OFF switch and solenoid operated Eco Throttle to control engine RPM from idle to rated speed. No muffler or fuel tank.

**SPECIFICATIONS**

- Model GX270 RT1 VMT2
- Engine Family GX
- Power 8.5 HP at 3600 RPM
- Torque 14.1 ft-lbs at 2500 RPM
- Disp. 270 cc
- Speed 3600 RPM
- Start Recoil
- Fuel Tank None
- Shaft Horizontal
- Shaft 22mm dia. x 4<sup>1</sup>/<sub>16</sub>" tapered 2<sup>1</sup>/<sub>4</sub>" ft tapped 5<sup>16</sup>/<sub>64</sub>"-24 UNF
- Accessory Mount
- Inner 4 bolt on 5" B.C.
- Outer 4 bolt on 6.5" B.C.
- Size 12<sup>1</sup>/<sub>2</sub>" X 17" X 16<sup>1</sup>/<sub>2</sub>"
- Shpg 60 lbs.

### Stem Thermometers

• New, TelTru thermometers. Various temperature ranges and stem lengths. Additional sizes at [www.surpluscenter.com](http://www.surpluscenter.com). Shpg 1 lb.



ITEM	Range	Face Dia.	Stem Dia.	Stem Lgth.	Mount	Price
21-1732	-20 to 120	5"	9"	1/2"	NPT	\$16.95
21-1670-B	-80 to 120	5"	*6"	1/2"	NPT	\$37.95
21-1732	-20 to 120	5"	9"	1/2"	NPT	\$16.95
21-1682-K	0 to 150	1 3/4"	5"	None		\$20.95
21-1682-A	50 TO 500	1 3/4"	2 1/2"	None		\$20.95

\*Adjustable

### 1/2" NPT Brass Ball Valve

ITEM 20-1661  
**\$1.49**



• New brass ball valve. 1/2" orifice. Stainless ball and teflon seal. Compact design. Use for tank drains, etc.

**SPECIFICATIONS**

- Size 1" dia. x 1"
- Ports 1/2" NPT male/female • Shpg. 1/2 lb.

### 4.4 HP Honda Engine

ITEM 28-2004  
**\$179.95**



• New, HONDA vertical shaft engine. Fuel shutoff valve and engine ON/OFF switch. Manual choke. Fixed throttle at rated speed.

**SPECIFICATIONS**

- Model GCV160LA0 N5B NH1
- Displacement 160 cc
- HP 4.4 @ 3600 RPM
- Torque 6.9 lb-ft @ 2500 RPM
- Start Recoil
- Shaft 7/8" diameter x 1.75" with 3/16 keyway. Not tapped.
- Mount 4 hole, 8" bolt circle
- Fuel Tank 1 quart
- Size 15<sup>1</sup>/<sub>2</sub>" x 13" x 11"
- Shpg. 40 lbs.

### 300 F VDO Oil Temp Gauge



ITEM 21-1819-B

**\$19.95**

• New VDO model 310-030-024 oil temperature gauge. Metal case with black bezel and face. Scale with white graduations. Includes mounting bracket and 12 volt DC illumination. Requires external sensor, not included.

**SPECIFICATIONS**

- Scale 120°F-300°F & 50°C-150°C
- Gauge type Oil Temperature
- Sensor 322-18 ohm (not included)
- Bezel Color Black
- Bezel Dia. 2 1/8" dia.
- Illumination 12 VDC
- Terminals 1/4" Spade
- Mount 2 1/8" dia. opening
- Shpg. 1/2 lb.

### 4-Bolt Engine To Pump Mount



ITEM 1-5580

**\$14.95**

• New, SPEECO model S40081200 aluminum pump mount for connecting gas engines with 3/8" bolt circle and 1 5/8" pilot to hydraulic pumps with 4F17 flange (2" sq. bolt pattern and 1.78" dia.)

**SPECIFICATIONS**

- Engine Mount 3 5/8" bolt circle
- Engine HP Range 3-6.5 HP
- Pump Mount 4F17
- Total Length 4 1/8"
- Size 4 1/8" x 4" x 4"
- Shpg. 1 lb.

### Cast Iron

ITEM 1-5580-C

**\$14.95**

### 30 Cal Ammo Box

ITEM 1-1121-A  
**\$8.95**



• Genuine U.S. military surplus used ammo box. Rubber gasketed lid provides a watertight seal. Handle on top of lid. Steel construction. Functional hinges and handles. May have some light surface rust, water staining, small dents, sun fading and tape indicating the can is empty.

**SPECIFICATIONS**

- Caliber 30 7.62mm
- Hinge end
- Size 11" x 4" x 7"
- Shpg 5 lbs.

### Brass Ball Valves

• New, BIANCH lead-free brass ball valves

ITEM	Model Number	Ports	PSI Max.	Length x Width x Height with Handle	Shpg.	Price
20-1668	425B00041A	1/2" NPT	360	4 3/4" x 4 1/8" x 2 3/8"	0.4 lb.	\$5.99
20-1669-B	537000050A	0.86" (22mm) Press-Fit	600	5 3/4" x 4 3/4" x 2 3/4"	0.8 lb.	\$7.99
20-1670-A	460L00061F	1" NPT	600	2 7/8" x 1 1/2" x 2 5/8"	0.8 lb.	\$8.99
20-1670-B	537000060A	1.1" (28mm) Press-Fit	600	6 1/8" x 5 1/2" x 3 1/2"	2 lbs.	\$8.99

