




• New Danfoss White Drive Products low speed high torque motors. Interchangeable with many different brands of similar type motors. Pictures are representative of motors. More information including pictures and additional specifications can be found on website.

4 Bolt Circle Mount



2 Bolt Mount

Item	Model	Displ cu. In.	PSI Cont.	Torque Cont.	RPM Cont.	GPM Cont.	Mount	Shaft	Ports	Shpg.	Price
9-12922-C	276090W3114AAAE	5.4	2000	1430	520	12	4-bolt circle	1" tapered keyed	SAE 10	19 lbs.	\$119.95
9-8672-H	281130A6321BAAAA	7.9	2000	2135	350	12	2-bolt SAE A	32mm keyed	½" BSPP and Manifold	18 lbs.	\$139.99
9-12921-E	255200A1K02AAAAAP	12.1	2500	3540	304	16	2-bolt SAE A	1" 6T spline	Manifold	22 lbs.	\$139.95

### Flow Control Valves

**\$86.40 Each**



• Brand new WOLVERINE by PRINCE. Pressure compensated flow control to vary the speed of hydraulic motors. Rotate lever to vary flow to controlled flow port. Can be locked in place. Excess flow port may be plugged for use in closed center systems.

**SPECIFICATIONS**

- Pressure 3000 PSI max.
- Size 4.56" x 4.69" x 1.89"
- Mount Two ¼" holes thru body, 3.87" c/c
- Shpg. 9 lbs.

ITEM	Model	Ports	GPM
9-8994-50-8	W-1950-8	½" NPT	0-8
9-8994-50-16	W-1950-16	½" NPT	0-16
9-8994-8-8	W-1908-8	SAE 8	0-8
9-8994-12-30	W-1912-30	SAE 12	0-30
9-8994-75-30	W-1975-30	¾" NPT	0-30

### Hydraulic Brake

ITEM 9-12918-A

**\$89.95**



• New. DANFOSS 9225650K3031AAAAAS hydraulic brake. Shaft length measurement is measured from back mounting face to end of shaft.

**SPECIFICATIONS**

- Holding Torque 5750 in. lbs.
- Release Pressure 290 PSI
- Max Pressure 3,000 PSI
- Release Volume 0.55 cu.in.
- Speed 250 RPM max.
- Port SAE 4
- Shaft 1½" tapered dia. x 5.925" long w/ ⅜" keyway and 1½"-18 threaded w/ castle nut
- Mount Four, 0.53" holes on 6.25" B.C. w/ 4" pilot
- Size 7" x 7" x 6.25"
- Shpg. 26 lbs.

ITEM 9-12918-B

**\$69.95**

**SPECIFICATIONS SAME AS ABOVE EXCEPT**

- Shaft 32mm tapered dia. x 5.689" long w/ ⅜" keyway and 1½"-18 threaded w/ castle nut

### 0.835 cu. in. Hydraulic Motor

ITEM 9-7871

**\$29.95**



• New, MARZOCCHI model 1AMS20ST-NGP043 uni-directional hydraulic motor. Side ports.

**SPECIFICATIONS**

- Disp. 0.835 cu. in./rev.
- Motor Type Gear
- Rotation CCW
- Mount 4 bolt USA 4F17
- Pressure: 2200 PSI cont. 2800 PSI peak
- Speed: 1725 rpm @ 6.234 GPM 2000 rpm max
- Shaft 0.172" thick tang
- Ports SAE 10
- Case Drain N/A
- Size 5½" x 2½" x 3½"
- Shpg. 6 lbs.

### 7 cu. in. Hydraulic Motor

ITEM 9-8633  
**\$394.95**



• New, RINEER model# M015-71-1S-007-31-B1-TV-100 roller vane motor. Intended for high-speed, low-torque applications. Tapered roller bearings for radial and axial loading.

**SPECIFICATIONS**

- Brand Rineer Hydraulics
- Model M015-71-1S-007-31-B1-TV-100
- Family 15 Series
- Displacement 7 cu. in. / rev.
- Motor Type Vane
- Rotation Reversible
- Flow 57.6 GPM @ 1900 RPM
- Pressure: 3000 PSI cont. 3500 PSI int.
- Torque: 230 in-lbs. cont. 312 in-lbs.
- Speed: 1900 RPM cont. 2600 RPM int.
- Mount Four-bolt SAE C
- Shaft 1¼" dia. x 2½" long 14T spline
- Ports SAE 16
- Case Drain SAE 6
- Size 9" x 6½" x 6½"
- Shpg. 61 lbs.

### 12.2 cu. in. Hydraulic Motor

ITEM 9-7567  
**\$148.95**



• New, BUCHER Hydraulics.

**SPECIFICATIONS**

- Model BRGL200A18
- Disp. 12.2 cu. in. / rev.
- Motor Type Geroler
- Pressure: 2000 PSI cont. 2750 PSI int.
- Torque: 3350 in-lbs. cont. 4650 in-lbs. int.
- RPM 220 cont., 280 int
- Rotation Reversible
- Flow: 12 GPM cont. 15 GPM int.
- Mount 2 bolt SAE A
- Shaft 25 MM dia x 1½" keyed
- Ports ½ BSPP
- Size 7¾" x 5¼" x 4"
- Shpg. 21 lbs.

### 14.1 cu. in. Hydraulic Motor

ITEM 9-12499-I  
**\$229.95**



• New. DANFOSS WG series low speed high torque hydraulic motor.

**SPECIFICATIONS**

- Brand Danfoss
- Model 276230W31R1AAAAA
- Family WG Series
- Displacement 14.1 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 1250 PSI cont. 2400 PSI int.
- Torque: 3380 in-lbs. cont. 4680 in-lbs. int.
- Speed: 240 RPM cont. 330 RPM int.
- Flow: 15 GPM cont. 20 GPM int.
- Mount 4 bolt wheel mount on 5.125" b.c.
- Shaft 1" tapered x 3.64" long w/ ¼" keyway, threaded ¾"-24 w/ castle nut
- Ports SAE 10
- Case Drain None
- Size 5.63" x 4.85" x 4.85"
- Shpg. 22 lbs.

### 14.83 cu. in. Hydraulic Motor

ITEM 9-12804  
**\$199.95**



• New. EXTREME hydraulic motors. Gerolor power element. Low speed high torque hydraulic motor.

**SPECIFICATIONS**

- Brand Extreme
- Model EXT-M153WNB
- Displacement 14.83 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 2900 PSI cont. 3265 PSI int.
- Torque: 6265 in-lbs. cont. 7142 in-lbs. int.
- Size 8½" x 5¾" x 4½"
- Speed: 300 RPM cont. 360 RPM int.
- Flow: 19.8 GPM cont. 23.7 GPM int.
- Mount 4 bolt magneto
- Shaft 1¼" dia x 2.05" long 14T splined, tapped ⅜"-16
- Ports SAE 10
- Case Drain SAE 4
- Shpg. 29 lbs.

### 25.07 cu. in. Hydraulic Motor

ITEM 9-16139  
**\$449.95**



• New, SAUER DANFOSS model TMT 400 V hydraulic motor. Heavy duty with high flow capacity.

**SPECIFICATIONS**

- Family TMT
- Displacement 25.07 cu. in. / rev.
- Motor Type Orbital
- Rotation Reversible
- Pressure: 3360 PSI cont. 5080 PSI int.
- Power: 50 Hp cont. 68 Hp int.
- Torque: 13450 in-lbs. cont. 18760 in-lbs. int.
- Speed: 305 RPM cont. 360 RPM int.
- Flow: 33 GPM cont. 39.6 GPM int.
- Mount 4 bolt SAE C 6.375" bolt circle, 5" pilot dia.
- Shaft 1½" dia. 17 tooth spline, tapped ⅜"-16 x 1.12"
- Ports SAE 12
- Case Drain SAE 6
- Size 9¾" x 6¾" x 6¾"
- Shpg. 69 lbs.

### 1.53 cu in Hydraulic Motor

ITEM 9-8915  
**\$129.95**



• New, SALAMI model# 2,5MB25R-R55S3-MOTOR hydraulic motor. Aluminum body.

**SPECIFICATIONS**

- Displacement 1.53 cu. in. / rev.
- Motor Type Gear
- Rotation Reversible
- Inlet Port SAE 16
- Outlet Port SAE 12
- Pressure: 3625 PSI cont. 4060 PSI int.
- Torque: 883 in-lbs. @ 3625 PSI 989 in-lbs. @ 4060 PSI
- Speed: 3000 RPM max. 500 RPM min.
- Flow: 24 GPM @ 3625 RPM 26.9 GPM @ 4060 RPM
- Mount Two-bolt SAE B
- Shaft ⅞" dia. x 1½" long 13T spine
- Case Drain SAE 4
- Size 4¾" x 6¾" x 5½"
- Shpg. 11 lbs.