



## Water System Automatic Pressure Switches

• Brand new, LEFOO automatic pressure switch for automatic water systems. Automatically turns pump ON or OFF at set values. Adjustable differential. Sturdy plastic housing. Single port.

ITEM 4-1822

**\$13.95**

### SPECIFICATIONS

- Contact ratings
  - 1½ HP at 120 VAC
  - 2 HP at 230 VAC
  - 3 HP at 240 VAC 3Ph
- Factory setting
  - ON (cut-in) 40 PS
  - OFF (cut-out) 60 PSI



- Min. ON (cut-in) 20 PSI
- Max. OFF (cut-out) 80 PS
- Differential 15-35 PSI
- Port ¼" NPT
- Size 3¾" x 2½" x 3¾"
- Shpg. 1½ lbs.

ITEM 4-1821

**\$13.95**

### SPECIFICATIONS

- Contact ratings
  - 1½ HP, 20 amps at 120 VAC
  - 2 HP, 12 amps at 240 VAC
  - 3 HP, 9.6 amps at 240 VAC 3Ph
- Factory setting
  - ON (cut-in) 30 PSI
  - OFF (cut-out) 50 PSI



- Min. ON (cut-in) 30 PSI
- Max. OFF (cut-out) 100 PS
- Differential 20-35 PSI
- Port ¼" NPT
- Size 3½" x 2¼" x 3½"
- Shpg. 1½ lbs.

## Windshield Washer Pump

ITEM 2-1442

**\$8.99**

• New, windshield washer pump. Mounts thru grommet on side of reservoir (not included). Recessed two prong electrical connection.

### SPECIFICATIONS

- Pump Voltage 12 VDC
- Mount 0.65 OD barb for grommet
- Outlet ¾" hose barb
- Size 1¾" dia. x 3¾"
- Shpg. 1 lb.



## Hydraulic Driven Centrifugal Pump

ITEM 2-1180

**\$1048.70**

• Brand new HYPRO model 9303-HM1C. Cast iron centrifugal pump with direct drive hydraulic motor. Power from tractor hydraulic circuit leaving PTO free for other uses.

### SPECIFICATIONS

- Maximum Pressure 120 PSI
- Maximum Pump Flow: 112 GPM
- Pump inlet 1½" NPT
- Pump discharge 1¼" NPT
- 140° F max. fluid temp
- Hydraulic motor ports ½" NPT
- Hydraulic requirements-13 GPM at 2000 PSI
- 11" x 7¾" x 8¼"
- Shpg. 31 lbs.



## 140 GPM Centrifugal Pump


ITEM 2-1222

**\$472.95**

• Brand new, HYPRO 9203C cast iron centrifugal pedestal mount pump. Ideal for high volume spraying systems. Viton seals.

### SPECIFICATIONS

- Model 9203C
- Max. 6000 RPM
- 1½" NPT inlet port
- 1¼" NPT outlet port
- Rotation CCW
- Max. temp. 140° F
- 2 bolt pedestal mount on 3" centers
- Shaft ¾" outside dia. x 2½" long w/ ¾" keyway
- Size: 7¾" x 7¼" x 8¼"
- Shpg. 21 lbs.



## ½ HP Shallow Well Jet Pump

ITEM 2-1466

**\$249.95**

• New. Red Lion RL-SWJ50-SP Shallow well jet pump. Ideal for use in depths of 25 feet or less. Cast iron construction. Preset 30/50 pressure switch produces up to 50 PSI w/ automatic shutoff. 115/230 volt heavy duty TEFC motor.

### SPECIFICATIONS

- Voltage 115/230
- Amperage 8.4 @ 115V 4.2 @ 230V
- Pressure 64 PSI MAX
- Power ½ HP
- Gallons 12.6 GPM MAX
- Inlet Port 1¼" NPTF
- Discharge Port 1" NPTF
- Gauge Port ½" NPTF
- Flow Rates for shallow well:
  - 13.6 GPM @ 5 ft. of lift
  - 9.7 GPM @ 15 ft. of lift
  - 4.7 GPM @ 25 ft. of lift
- Size 12" x 17.25" x 11.75"
- Shpg 25 lbs.



## Line Strainers

• Brand new HYPRO. Keeps debris from being drawn thru pump. Provides longer component life and less downtime.

### SPECIFICATIONS

- Polypropylene construction
- EPDM gasket
- 80 PSI at 70 degrees F.
- 50 mesh stainless steel screen
- Shpg. 1 lb.



ITEM 20-997

**\$14.60**

- ½" NPT, 7.7 sq. in. open area, 3.6" x 2.95" x 5.35"

ITEM 20-998

**\$15.75**

- ¾" NPT, 7.7 sq. in. open area, 3.6" x 2.95" x 5.35"

ITEM 20-999

**\$21.45**


- 1" NPT, 13.5 sq. in. open area, 5" x 4.1" x 6.35"

## Shurflo Diaphragm Pumps

• Brand new, SHURFLO automatic demand diaphragm pumps. Ideal for spot sprayers. Santoprene diaphragm and Viton valves. Can run dry intermittently. Rubber mounting feet. Intermittent duty. Automatic on/off pressure switch. Use adapters shown below for ½" MSPT ported items (metal fittings and rigid pipe are not recommended). Wire leads on DC models, 6 ft. power cord on AC model.



2-1361



2-1360



2-1362  
2-1363

ITEM	Model	Volts	Amps	Open Flow	Max. GPM at PSI	PSI	Ports	Switch Settings on/off	Self Priming Lift max.	Size	Shpg.	Price
2-1361	SLV10-AA41	12 DC	4	1 GPM	0.49 at 30	50	¾" hosebarb	25/40 PSI	2½ ft.	7" x 3¾" x 2¾"	3 lbs.	\$69.95
2-1360	8000-543-236	12 DC	6.4	1.8 GPM	1.4 at 40	50	¾" NPTF	30/50 PSI	8 ft.	8¼" x 4" x 4½"	6 lbs.	\$124.60
2-1362	2088-343-135	12 DC	7.7	3 GPM	2.05 at 40	40	½" MSPT	25/45 PSI	12 ft.	8¾" x 6" x 4½"	6 lbs.	\$148.70
2-1363	2088-394-144	115 AC	0.9	3 GPM	1.6 at 40	40	½" MSPT	25/45 PSI	12 ft.	9" x 5¼" x 47/8"	6 lbs.	\$226.75

## Shurflo Hosebarb to Pipe Fittings

• Brand new Shurflo polypropylene hosebarb to pipe fittings.

ITEM	Style	Description	Hose ID	NPT Fitting	Shpg.	Price
2-1366	A	Straight	¾"	½" NPTF Swivel	¼ lb.	\$1.10
2-1367	A	Straight	½"	½" NPTF Swivel	¼ lb.	\$1.00
2-1364	A	Straight	¾"	½" NPTF Swivel	¼ lb.	\$2.05
2-1365	A	Straight	¾"	½" NPTF Swivel	¼ lb.	\$1.25
2-1369	B	Elbow	¾"	½" NPTF Swivel	¼ lb.	\$1.00

ITEM	Style	Description	Hose ID	NPT Fitting	Shpg.	Price
2-1368	B	Elbow	½"	½" NPTF Swivel	¼ lb.	\$1.00
2-1371	B	Elbow	¾"	½" NPTF Swivel	¼ lb.	\$1.75
2-1370	B	Elbow	¾"	½" NPTF Swivel	¼ lb.	\$1.25
2-1372	C	Straight	¾"	¾" NPTM	¼ lb.	\$0.50
2-1374	C	Straight	½"	½" NPTM	¼ lb.	\$2.55