

24 VDC Diaphragm Pump

ITEM 2-1444
\$19.95



• New, SHURFLO model 100-030-20 positive displacement wobbler pump. Ryton and EPDM construction. Not self priming. Wire leads. Rubber vibration damper mounting feet.

SPECIFICATIONS

- Voltage 24 VDC
- Amperage 1.5 Amps
- Shut-Off Pressure 15 PSI
- Max Fluid Temp 130°
- Ports 3/8" Hose Barb
- Duty Intermittent
- Mount 2 holes 2" apart
- Flow Rates
 - 1 GPM @ open flow
 - 0.8 GPM @ 5 PSI
 - 0.53 GPM @ 10 PSI
 - 0.10 GPM @ 15 PSI
- Size 3 1/2" x 2 5/8" x 2"
- Shpg. 1 lb.

Simer Water Pump

ITEM 2-1264
\$39.95



• New, SIMER. Flexible impeller pump. Use to pump water, brine solutions and light lubricating oils. WARNING: This pump should never be used to pump flammable fluids! Wired with a 4 ft. power cord with on/off switch and alligator clips. Permanent magnet motor. Includes two garden hose to 1/2" hose barb adapters and instructions.

SPECIFICATIONS

- 1,140 liters/hour (301 GPH)
- 24 VDC
- Self-priming to 9 feet
- 20 PSI max.
- Max 118°F
- Male garden hose thread ports
- Base mount
- Overall size 7 1/8" x 4 1/2" x 4 1/2"
- Shpg. 7 lbs.

Mini Fountain Pump

ITEM 2-1255
\$3.99



• New, OASE. Submersible fountain pump for indoor or outdoor use. Adjustable output flow. Integral 18/3 cord is water resistant with three prong plug. Two suction cups on bottom to hold pump in place. UL Listed. Made in Italy.

SPECIFICATIONS

- 5 1/2 ft. long cord
- Model SP40G
- 4 watts
- 115 VAC
- 1/2" O.D. outlet tube
- 30-55 GPH
- Size 1 7/8" x 1 5/8" x 1 3/4"
- 18" max. head
- Shpg. 1 lb.

12 VDC Submersible Pump



ITEM 2-1443
\$13.95

• New. Submersible, brushless impeller pump. Can be mounted in or under tank. Sold with 115 VAC to 12 VDC adapter with on/off switch (needs alteration to mate with leads from pump). Pump is not self-priming.

SPECIFICATIONS

- Voltage 12 VDC
- Amperage 0.36 Amps @ 12 VDC, Dry
- Flow 6 GPM @ 0' head pressure
- Max Head Pressure 6.5'
- Input 17mm (0.669") O.D. hose
- Output 12mm (0.472") O.D. hose
- Leads 6"
- Size 3 3/4" x 2 1/8" x 1 3/4"
- Shpg. 1 lb.

115 VAC Coolant Recirculating Pump

ITEM 2-1436
\$27.95



• New, BECKETT model BJ5A coolant recirculating pedestal pump. Ideal replacement or use with evaporative coolers, displays, laboratories and other water transfer applications. Features include polystyrene column and cap, ABS base plate and a 1/2" OD PVC adapter. ODP motor with fan and cover.

SPECIFICATIONS

- Voltage 115 VAC
- Amperage 0.9 Amps
- Power 1/70 HP
- Flow Rates
 - 340 GPH @ 1 ft. head
 - 255 GPH @ 4 ft. head
 - 200 GPH @ 6 ft. head
 - 130 GPH @ 8 ft. head
 - 40 GPH @ 10 ft. head
- Speed 3000 RPM
- Shut-off @ 10.1 ft. head
- Duty Continuous
- Power Cord 3 foot 18/3
- Inlet Base
- Discharge 1/2" hose barb with adapter
- Size 4 1/2" diameter x 9" high
- Shpg. 5 lbs.

Tuthill Manual Transfer Pump

ITEM 2-1350
\$19.99



• New, TUTHILL Series 20 hand lever piston pump for pumping fluid into a container. Polypropylene housing, BUNA N seals. Economical manual transfer pump ideal for use on barrels, drums and storage tanks. Anti-drip nozzle, check valve and 360° locking ring. Telescoping suction pipe fits up to 36" high container. Compatible with water, gear oils, engine oils, paraffin, fertilizers, mild acids, anti-freeze, hydraulic oils, diesel, degreasers, herbicides and pesticides. Not for use with gasoline, ethanol or methanol.

SPECIFICATIONS

- Flow 11 fl. oz. per stroke
- Viscosity SAE 90 max.
- Bung Adapter 2" NPS
- Inlet 1" NPT
- Outlet Nozzle with strainer
- Size 9 1/4" x 3 1/2" x 12"
- Shpg. 5 lbs.

12 VDC Diaphragm Pump

ITEM 2-1455
\$19.99



• New, DELAVAN automatic demand diaphragm pump. Ideal for spot sprayers or as replacement on existing equipment. Santoprene diaphragm and Viton valves. Automatic shut off switch set to 40 PSI. Pump turns on at 25 PSI. Self priming to 4 foot suction lift. Can run dry intermittently without damage. Wire leads. Rubber vibration damper mounting feet.

SPECIFICATIONS

- Voltage 12 VDC
- Amperage 2.6 Amps
- Flow Rates
 - 1 GPM @ open flow
 - 0.85 GPM @ 10 PSI
 - 0.71 GPM @ 20 PSI
 - 0.61 GPM @ 30 PSI
 - 0.42 GPM @ 40 PSI
- Shut-Off Pressure 40 PSI
- Ports 3/8" Hose Barb QA port adapters
- Duty Intermittent
- Temperature 110°F max.
- Mount Four bolt on 3.19" x 2.25" pattern
- Size 7" x 3 5/8" x 2 3/8"
- Shpg. 2 lbs.

120 VAC Submersible Pump

ITEM 2-1467
\$29.95




• New, DK-5000 submersible water pump. Ideal for fountains, ponds, machine tool coolant. Plastic housing, plastic impeller. Slotted intake cover can be easily removed for cleaning. Four suction cups on base. Includes a brass adapter to 3/8" ID tubing.

SPECIFICATIONS

- Voltage 120 VAC
- Power Consumption 105 Watts
- Flow 20 GPM open flow
- Max Head 15 ft.
- Size 7" x 4" x 5"
- Port 3/4" MGHT (Standard Garden Hose Male) w/ 3/8" ID hose adapter
- Power Cord 15 ft. long, 3-prong plug
- Shpg. 8 lbs.

Polypropylene Barrel Pump

ITEM 2-1451
\$36.95



• New, Funnel King Fluid Control Products by WirthCo model 32462 plunger style hand pump. Use to transfer antifreeze, detergent, windshield fluid. Polypropylene with steel rod and Viton seals. Includes 2" bung adapter and angled discharge spout.

SPECIFICATIONS

- Flow Rate 1 gal. @ 10 full strokes
- Rotation CW
- Mount 2" Tank Bung
- Suction Pipe Length 38"
- Shpg. 3 lbs.

1/2" IPS Brass Gate Valve

ITEM 20-1657-50
\$4.99



• New, CHAMPION-ARROWHEAD lead-free brass gate valve. Full port. IPS (Iron Pipe Straight) ports.

SPECIFICATIONS

- Ports 1/2" IPS
- Pressure Max 200 PSI
- Size 2" x 1 1/4" x 3 1/4"
- Shpg 1/2 lb.

12 VDC Centrifugal Pump

ITEM 2-1155
\$338.90



• Brand new HYPRO "Aqua-Tiger" Bronze centrifugal pump. Use for ag chemical transfer, live well aeration, circulation, etc. Permanent magnet motor. Not self-priming.

SPECIFICATIONS

- 12 Volt DC
- 5.5 amps
- Max. flow 19 GPM
- Max. 7 PSI
- Max 140°F
- Ports 3/4" NPT
- 7" x 4 1/2" x 4"
- Shpg. 8 lbs.