

## Double Roller Chain Couplers

• Brand new. Three piece chain coupler consist of two sprockets connected together with double roller chain. Sold as individual halves and chain. Purchase two halves and one coupler chain to make a complete coupling.



Pitch & Tooth Count	Max. RPM	Max. Torque Ft.-Lbs.	Max HP at RPM	Coupling O.D.	Coupled Length
	40 Pitch 16 Tooth	5000	80.5	73.6 at 4800 RPM	3.03"
50 Pitch 16 Tooth	4000	159.6	109.4 at 3600 RPM	3.78"	3.92"
60 Pitch 18 Tooth	3000	407.5	194.5 at 2500 RPM	5"	4.86"

### Keyed Half • Furnished with standard keyway and setscrews.

Bore Size	40 Pitch 16 Tooth	50 Pitch 16 Tooth	60 Pitch 18 Tooth
	ITEM	ITEM	ITEM
5/8"	1-4050-B	1-4051-B	—
3/4"	1-4050-C	1-4051-C	—
7/8"	1-4050-D	1-4051-D	—
1"	1-4050-E	1-4051-E	1-4053-E
1 1/8"	1-4050-F	1-4051-F	1-4053-F
1 3/16"	—	1-4051-G	1-4053-G
1 1/4"	—	1-4051-H	1-4053-H
1 3/8"	—	1-4051-I	1-4053-I
1 7/16"	—	1-4051-J	—
1 1/2"	—	1-4051-K	1-4053-K
1 5/8"	—	1-4051-L	1-4053-L
1 15/16"	—	—	1-4053-O
2"	—	—	1-4053-P
2 1/8"	—	—	1-4053-Q
2 1/4"	—	—	1-4053-R
2 3/8"	—	—	1-4053-S
2 7/16"	—	—	1-4053-T
<b>Shpg. Price</b>	<b>2 lbs. \$16.10</b>	<b>3 lbs. \$20.00</b>	<b>7 lbs. \$34.70</b>



### Smooth Bore Half • Plain bore, no keyway or setscrews.

Machinable Bore Range	40 Pitch 16 Tooth	50 Pitch 16 Tooth	60 Pitch 18 Tooth
	ITEM	ITEM	ITEM
5/8" - 1 1/8"	1-4050-SB	—	—
5/8" - 1 5/8"	—	1-4051-SB	—
1" - 2 7/16"	—	—	1-4053-SB
<b>Shpg. Price</b>	<b>2 lbs. \$13.95</b>	<b>3 lbs. \$17.35</b>	<b>7 lbs. \$31.20</b>



### Double Roller Chain with Connecting Link

	40 Pitch 16 Tooth	50 Pitch 16 Tooth	60 Pitch 18 Tooth
ITEM	1-4050-X	1-4051-X	1-4053-X
Shpg. Price	1/2 lb. \$5.10	1 1/2 lbs. \$9.05	3 lbs. \$16.10



### Coupling Covers

• Brand new. Shock coupling covers recommended to obtain maximum coupling life. Aluminum covers are made as halves for easy installation.

	40 Pitch 16 Tooth	50 Pitch 16 Tooth	60 Pitch 18 Tooth
ITEM	1-4050-CC	1-4051-CC	1-4053-CC
Shpg. Price	1 lb. \$26.40	1 1/2 lbs. \$35.80	3 lbs. \$47.40



## Splined PTO Adapters



• Brand new, G & G Mfg. Co. Adapts keyed shaft to 1 3/8" 6 tooth spline. **Shpg 4 lbs.**

ITEM	Female Bore	Size	Price
1-2241	1"	2" dia. x 5 3/4"	<b>\$37.60</b>
1-2242	1 1/4"	2" dia. x 5 7/8"	<b>\$37.55</b>
1-2970	1 1/2"	2 1/4" dia. 5 7/8"	<b>\$42.85</b>

## Tractor PTO Adapter



**ITEM 1-1655 \$53.35**

• New. Use to connect hydraulic or water pumps direct to tractor PTO.

### SPECIFICATIONS

- Splined end 1 3/8" 6 tooth spline, 2 1/2" deep
- Keyed end 7/8" dia. x 2 1/2" deep, 3/16" keyway
- Overall size 1 3/4" dia. x 5"
- **Shpg. 3 lbs.**

## Snap Hitch Pump Adapters



• Brand new G & G. Snap hitch adapters. Slides onto standard 1 3/8" splined PTO shaft and spring-loaded retention pin holds adapter onto PTO shaft retention groove. Painted steel construction. Size 4 1/8" x 2 1/2" x 2 1/8". **Shpg. 4 lbs.**

ITEM # 6T	ITEM # 21T	Round Bore	Keyway	Price
1-2455	1-2462	5/8"	3/16"	<b>\$49.75</b>
1-2456	1-2465	3/4"	3/16"	<b>\$49.75</b>
1-2457	1-2466	7/8"	3/16" & 1/4"	<b>\$49.75</b>
1-2458	1-2467	1 5/16"	1/4"	<b>\$49.75</b>
1-2459	1-2468	1"	1/4"	<b>\$49.75</b>

## U-Joint Assembly



**ITEM 1-2738 \$4.99**

• New, universal joint assembly originally made for use in automotive steering applications. Ideal for low torque, low speed projects. Gray rubber boot. Rubber boot end accepts a round shaft 0.645" in diameter x 1 5/16" long with two flats, 0.58" across the flats. Other end accepts a 7/8" diameter shaft with two flats (0.667" across). 14" overall length, tip-to-tip. Tube outside diameter 7/8". **Shpg. 3 lb.**

## 12 VDC Electric Clutch/Brake



**ITEM 1-5724 \$78.99**

• New. Ogura model GT1-CH03L(D) 12 volt DC clutch/brake. Ideal replacement for mowers. Triangular back plate. Note: Crankshaft does not extend fully thru clutch.

### SPECIFICATIONS

- Voltage 12 DC
- Pulley 5 1/4" dia. 1 groove
- Belt Width 5/8"
- Mount 2 slots
- Back Plate 6" x 6 1/4"
- Hub 25mm bore
- Size 6 1/2" x 3" x 5 3/4"
- **Shpg. 10 lbs.**