

Leeson Three Phase Motors

- Brand new LEESON fractional horsepower three phase motors with steel motor frame and base.

SPECIFICATIONS

- Voltage 208-230/460
- Service factor 1.15
- Shaft 5/8" with keyway
- RPM 1725
- Enclosure TEFC
- Electrically reversible rotation
- Enclosure TEFC
- No overload protection
- Ball bearings
- Continuous duty



2 HP 1745 RPM Motor
ITEM 10-3391
\$499.95

* ** **Marathon**

ITEM	Model	HP	Amps	Frame	Shpg	Price
10-3383**	5K49FN4136	1/3	1.5-1.6/0.8	56	22 lbs.	\$340.75
10-3382**	5K42FN4035	1/3	1.5-1.6/0.8	56C	20 lbs.	\$384.60
10-3374**	5K35MNB117	1/2	2.2/1.1	56	22 lbs.	\$381.85
10-2711*	110034	3/4	2.8/1.4	56	22 lbs.	\$241.05
10-3091	116757	1	3.2/1.6	56	32 lbs.	\$345.40
10-3093	116745	1	3.2/1.6	56C	34 lbs.	\$376.55
10-3092	116759	1 1/2	4.8/2.4	56	43 lbs.	\$378.10
10-3101*	116747	2	5.8/2.9	56C	48 lbs.	\$949.60

- New, LEESON motor.

SPECIFICATIONS

- Model Number C145T17FK27E
- Vendor Number 121181.00
- Power 2 HP
- Voltage 230/460 & 190/380 VAC
- Phase 3
- Frequency 60 & 50 Hz
- Amperage 5.8/2.9 & 6.8/3.4 Amps
- Speed 1745 & 1435 RPM
- Rotation Reversible
- Service Factor 1.25
- Bearings Ball
- Thermal Overload Protection None
- Enclosure TEFC
- Duty Continuous
- Frame 145TC
- Base Mount: Six, 0.334" x 1" slotted holes on 3" x 5-6" centers
- Face Mount: Four 3/8"-16 threaded holes in motor face on 5 7/8" B.C., 4 1/2" pilot
- Shaft 7/8" dia. x 2 1/4" overall length w/ 3/4" wide x 1 1/2" long keyway
- Size 13 3/4" x 9" x 7 1/4"
- Shpg. 53 lbs.



100 RPM 230 VAC 3 PH Gearmotor
ITEM 5-1909
\$109.95

- New, BODINE parallel-shaft gearmotor.

SPECIFICATIONS

- Model 34Y68VFP-Z2
- Speed 100 RPM
- Horsepower 1/3
- Voltage 230 VAC, 60 Hz 3 Phase
- Amperage 1.4 Amps
- Torque 35 lb. in.
- Ratio 16:1
- Rotation Reversible
- Duty Continuous
- Enclosure TEAO
- Mount Four 10-32. holes on 3 3/4" bolt circle
- Shaft 1/2" dia. x 1 1/4" long w/ 3/16" keyway & flat
- Size 8 1/4" x 4" x 6"
- Shpg. 14 lbs.




1 1/2 HP 3400 RPM Motor
ITEM 10-3398
\$129.95

- New, WEG model# TOOC040J0000100646 motor.

SPECIFICATIONS

- Power 1 1/2 HP
- Voltage 208-230/460 AC
- Phase 3
- Frequency 60 Hz
- Amperage 4.50-4.18/2.09 Amps
- Speed 3400 RPM
- Rotation CCW
- Service Factor 1.30
- Bearings Unknown
- Thermal Overload Protection None
- Enclosure ODP
- Duty Continuous
- Frame E56J
- Base Mount: Four 1 3/16" x 5/16" elliptical slots on 3" x 3 7/8" to 6 7/8" centers
- Face Mount: Four 3/8"-16 threaded holes in motor face on 5 7/8" B.C., 4 1/2" pilot
- Shaft 5/8" dia. x 2 1/2" overall length w/ 7/16"-20 thread 1/2" long
- Size 9 9/8" x 6 1/2" x 6 1/2"
- Shpg. 28 lbs.



3 HP 3510 RPM Motor
ITEM 10-2901
\$169.95

- New, TECHTOP NEMA premium inverter duty motor. Heavy finned cast iron housing.

SPECIFICATIONS

- Model GR3-CI-TF-182T-2-B-B-3-X1
- Power 3 HP
- Enclosure TEFC
- Voltage 208/230 AC
- Duty continuous
- Amperage 8.4/7.6
- Frame 182T
- Speed 3510 RPM
- Mount rigid welded base
- Rotation reversible
- Shaft 1 1/8" dia. x 2 3/4" w/ 5/16" keyway
- Phase 3
- Service factor 1.25
- Size 12 1/2" x 8 1/2" x 9"
- Bearings ball
- Shpg 92 lbs.

Truck freight only.



3/4 HP 3455 RPM Motor
ITEM 10-3397
\$99.95

- New, WEG model# W01.TO01C0X0X motor.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 208-230/460 AC
- Phase 3
- Frequency 60 Hz
- Amperage 2.98-2.70/1.36 Amps
- Speed 3455 RPM
- Rotation CCW
- Service Factor 1.5
- Bearings Unknown
- Thermal Overload Protection None
- Enclosure ODP
- Duty Continuous
- Frame W56J
- Base Mount: Four 1 3/16" x 5/16" elliptical slots on 3" x 4" to 6 7/8" centers
- Face Mount: Four 3/8"-16 threaded holes in motor face on 5 7/8" B.C., 4 1/2" pilot
- Shaft 5/8" dia. x 2 5/8" overall length w/ 7/16"-20 thread 1/2" long
- Size 7 3/4" x 6 1/2" x 6 5/8"
- Shpg. 19 lbs.



1 1/2 HP 3400 RPM Motor
ITEM 10-3399
\$159.95

- New, WEG model# W01.TO01C0X0X.

SPECIFICATIONS

- Power 3 HP
- Voltage 230/460 AC
- Phase 3
- Frequency 60 Hz
- Amperage 7.78/3.89
- Speed 3400 RPM
- Rotation CCW
- Service Factor 1.15
- Bearings Ball
- Thermal Overload Protection None
- Enclosure ODP
- Duty Continuous
- Frame 56HJ
- Base Mount: Six 1 3/16" x 5/16" elliptical slots on 2" to 5" x 3 7/8" to 6 7/8" centers
- Face Mount: Four 3/8"-16 threaded holes in motor face on 5 7/8" B.C., 4 1/2" pilot
- Shaft 5/8" dia. x 2 1/2" overall length w/ 7/16"-20 thread 1/2" long
- Size 10 5/8" x 6 1/2" x 6 1/2"
- Shpg. 36 lbs.



3 HP 3532 RPM Motor
ITEM 10-3352
\$179.95

- New, MARATHON three phase, motor. Inverter-rated, speed range 10:1.

SPECIFICATIONS

- Model 182TTFB6004
- Power 3 HP
- Voltage 208-230/460 AC
- Amperage 7.9-7.6/3.8
- Speed 3532 RPM
- Rotation Reversible
- Phase 3
- No Thermal Overload
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 184TC
- Size 15 1/2" x 12" x 10 1/2"
- Shpg. 90 lbs.

Truck freight only.



1 HP 3510 RPM Motor
ITEM 10-3305
\$229.95

- New, WEG three phase motor.

SPECIFICATIONS

- Model W01-TE01C0X0X
- Power 1 HP
- Voltage 230/460 AC
- Phase 3
- Frequency 60 Hz
- Amperage 2.88/1.44 Amps
- Speed 3510 RPM
- Rotation Reversible
- Service Factor 1.15
- Enclosure TEFC
- Duty Continuous
- Frame 56J
- Face Mount: Four 3/8"-16 tapped holes on 5 7/8" diameter bolt circle
- Rigid Base Mount: Four 0.34" diam. holes on 4 7/8" x 3"
- Shaft 5/8" dia. x 1 7/8" smooth w/ 7/16"-20 thread and 1 1/4" long
- Size 12 1/2" x 9 1/2" x 7 1/4"
- Shpg. 27 lbs.



2 HP 3460 RPM Motor
ITEM 10-3275
\$179.95

- New, WEG three phase motor.

SPECIFICATIONS

- Model TOOC040J0000101746
- Power 2 HP
- Voltage 208-230/460 AC
- Phase 3
- Frequency 60 Hz
- Amperage 5.65-5.3/2.65
- Speed 3460 RPM
- Rotation Reversible
- Service Factor 1.2
- Enclosure ODP
- Duty Continuous
- Frame E56C
- Face Mount: Four 3/8"-16 tapped holes on 5 7/8" diameter bolt circle
- Rigid Base Mount: Four 0.34" diam. holes on 4 7/8" x 3" centers
- Shaft 5/8" dia. x 1 3/4" w/ 7/16"-20 thread 1 1/4" long
- Size 12 1/2" x 6 1/2" x 6 5/8"
- Shpg. 33 lbs.



7.5 HP 3450 RPM Motor
ITEM 10-3089
\$199.95

- New, CENTURY inverter duty rated motor. 1" I.D. lifting tab included.

SPECIFICATIONS

- Model# TCP71006
- Power 7 1/2 HP
- Voltage 230/460 VAC
- Amperage 19/9 Amps
- Speed 3500 RPM
- Rotation Reversible
- Phase 3
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 213JM
- Face Mount Four 1/2"-13 tapped holes on 7 1/4" B.C., 8 3/8" pilot
- Base Mount Eight 7/16" holes on 8 1/2" x 1 1/2" x 5 1/2" x 7" centers
- Shaft 1 1/4" dia. x 4 1/4" long, Stepped down to 1" dia., Stepped down to 7/8" dia. w/ 3/16" wide keyway
- Size 16 7/8" x 15" x 10 7/8"
- Shpg. 240 lbs.

Truck freight only.