



General Purpose Motors

• Brand new WORLDWIDE ELECTRIC general purpose motors. Ideal for use in blowers, pumps, conveyors, and many other diverse applications.

SPECIFICATIONS

- 115/208-230 Volt
- 56C Frame
- P43 Protection
- Enclosure TEFC
- Continuous Duty
- Single-Phase
- Reversible Rotation
- Service Factor 1.15
- 5/8" Diameter keyed shaft
- C-Face with Removable Base



**1 HP
1725 RPM
Motor**
ITEM 10-3401
\$149.95



• New, CENTURY capacitor-start motor. Thermal overload protection with manual reset.

SPECIFICATIONS

- Model 7-C56AA80C28-03
- Power 1 HP
- Voltage 115/208-230 AC
- Phase 1
- Frequency 60/50 Hz
- Amperage 6.5-6.3/12.6 Amps
- Speed 1725/1425 RPM
- Rotation Reversible
- Service Factor 1.25
- Bearings Unknown
- Thermal Overload Protection Manual
- Enclosure ODP
- Duty Continuous
- Frame L56C
- Base Mount Four 1 3/16" x 5/16" elliptical slots on 3" x 3 7/8" to 6 7/8" centers
- Face Mount Four 3/8"-16 threaded holes in motor face on 5 7/8" B.C., 4 1/2" pilot
- Shaft 5/8" dia. x 1 1/4" overall length w/ 3/16" wide x 1 1/2" long keyway
- Size 9 7/8" x 6 1/2" x 8"
- Shpg. 36 lbs.

1800 RPM					
ITEM	Model	HP	Amps	Shpg	Price
10-3449	NT13-18-56CB	1/3	5.2/2.6	29 lbs.	\$209.95
10-3447	NT12-18-56CB	1/2	7.2/3.6	32 lbs.	\$221.20
10-3454	NT34-18-56CB	3/4	10.0/5.0	36 lbs	\$240.75
10-3446	NT1-18-56CB	1	13.0/6.5	41 lbs.	\$268.60
10-3444	NT1.5-18-56CB	1 1/2	14.5/7.3	42 lbs.	\$339.25
10-3452	NT2-18-56CB	2	19.6/9.8	50 lbs.	\$412.75
3600 RPM					
ITEM	Model	HP	Amps	Shpg.	Price
10-3450	NT13-36-56CB	1/3	5.4/2.7	29 lbs.	\$204.30
10-3448	NT12-36-56CB	1/2	6.5/3.3	31 lbs.	\$215.65
10-3455	NT34-36-56CB	3/4	9.2/4.6	34 lbs.	\$221.75
10-3451	NT1-36-56CB	1	11.5/5.8	37 lbs.	\$242.60
10-3445	NT1.5-36-56CB	1 1/2	13.0/6.5	37 lbs.	\$303.25
10-3453	NT2-36-56CB	2	17.0/8.5	44 lbs.	\$334.25

Electric Motor Slide Mounts

• Brand new, WORLDWIDE ELECTRIC T-frame motor slide base. Use to mount NEMA standard electric motor. Simplifies alignment and positioning, ideal for tensioning belts. Steel construction with baked-on primer. Washers included.



Find dimensional specifications and drawings for these items online.

ITEM	Compatible Motor		Slide Length	Adjusting Screw	Base Mount Centers	Foot Print	Shpg.	Price
	Frame Size	Slide Length						
10-2431-56	56	3"	1	7 5/8" x 5 3/4"	10 5/8" x 6 1/2"	5 lbs.	\$16.75	
10-2431-143T	143	3"	1	7 1/2" x 6 3/4"	10 1/2" x 7 1/2"	8 lbs.	\$32.25	
10-2431-145T	145	3"	1	7 1/2" x 7 3/4"	10 1/2" x 8 1/2"	9 lbs.	\$32.25	
10-2431-182T	182	3"	2	9" x 8 1/2"	12 3/4" x 9 1/2"	13 lbs.	\$43.85	
10-2431-184T	184	3"	2	9" x 9 1/2"	12 3/4" x 10 1/2"	13 lbs.	\$43.85	
10-2431-213T	213	3 1/2"	2	10 1/2" x 9 1/2"	15" x 11"	18 lbs.	\$65.20	
10-2431-215T	215	3 1/2"	2	10 1/2" x 11"	15" x 12 1/2"	20 lbs.	\$65.20	
10-2431-254T	254	4"	2	12 1/2" x 13 1/4"	17 3/4" x 15 1/8"	22 lbs.	\$88.85	
10-2431-256T	256	4"	2	12 1/2" x 15"	17 3/4" x 16 7/8"	23 lbs.	\$88.85	
10-2431-284T	284	4 1/2"	2	14" x 15"	19 3/4" x 16 7/8"	27 lbs.	\$99.90	
10-2431-286T	286	4 1/2"	2	14" x 16 1/2"	19 3/4" x 18 3/8"	28 lbs.	\$99.90	
10-2431-324T	324	5 1/4"	2	16" x 17"	22 3/4" x 19 1/4"	38 lbs.	\$145.40	
10-2431-326T	326	5 1/4"	2	16" x 18 1/2"	22 3/4" x 20 3/4"	39 lbs.	\$145.40	

1/3 HP 1200 RPM Motor

ITEM 10-3388
\$149.95



• New, CENTURY electric motor. Resilient base mount. Steel construction.

SPECIFICATIONS

- Model F420
- Power 1/3 HP
- Voltage 120/230 AC
- Phase 1
- Frequency 60 Hz
- Amperage 6.2/3.1 Amps
- Speed 1140 RPM
- Rotation Reversible
- Service Factor 1.35
- Bearings Ball
- Enclosure ODP
- Thermal Overload Protection None
- Duty Continuous
- Frame 56
- Base Mount Four 5/16" wide slots on 4 7/8" to 5 3/4" x 3" centers
- Shaft 5/8" dia. x 1 7/8" overall length w/ 3/16" wide x 1 1/2" long keyway
- Size 10" x 6 5/8" x 6 3/4"
- Shpg. 30 lbs.

3/4 HP 1725 RPM Motor

ITEM 10-3400
\$139.95



• New, CENTURY electric motor. Manual thermal overload protection

SPECIFICATIONS

- Model 7-196325-21
- Power 3/4 HP
- Voltage 115/208-230 AC
- Phase 1
- Frequency 60/50 Hz
- Amperage 10.6/5.2-5.3 Amps
- Speed 1725/1425 RPM
- Rotation Reversible
- Service Factor 1.25
- Bearings Ball
- Enclosure ODP
- Thermal Overload Protection Manual
- Duty Continuous
- Frame K56C
- Base Mount Four slots on 4" to 5 3/4" x 3" centers
- Face Mount Four 3/8"-16 threaded holes on 57/8" B.C. w/ 4 1/2" pilot
- Shaft 5/8" dia. x 1 1/8" overall length w/ 3/16" wide x 1 1/2" long keyway
- Size 11 1/2" x 6 1/2" x 9"
- Shpg. 31 lbs.

10 HP 1740 RPM Motor

ITEM 10-1325
\$1712.30



• Brand new, LEESON Extra Hi-Torque farm duty electric motor. Gasketed capacitor case and conduit box covers. Double sealed ball bearings. Extra high starting torque ratings. Steel construction. Capacitor start and run motor. Manual overload protection.

SPECIFICATIONS

- Model P215K17FB6H
- Power 10 HP
- Voltage 230 AC
- Amperage 45 Amps
- Speed 1800 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Farm
- Frame 215T
- Base Mount Six 0.41" dia. holes on 8 1/2" x 5 1/2" to 7" centers
- Shaft 1 3/8" dia. x 3 3/8" w/ 5/16" key
- Size 17.33" x 13.27" x 10"
- Shpg. 197 lbs.

Truck freight only.