

5200 RPM, DC Voltage Motors

\$3.99 each

• New, GLOBE MOTORS. Permanent magnet design.

SPECIFICATIONS FOR ALL

- Speed 5200 RPM
- Rotation reversible
- Mnt. two 6-32 holes 1" c/c
- Bronze sleeve bearings
- Duty continuous
- Enclosure closed



• Shpg. 1/2 lb.

ITEM	Model	Voltage	Amps	Shaft	Size
10-2482	405A100	6 DC	0.2	1/8" dia. x 3/8"	1.27" dia. x 1.85"
10-2492	397A1073	24 DC	0.125	1/8" dia. x 1/4"	1.25" dia. x 2.25"

1/2 HP 2500 RPM 180 Volt DC Electric Motor



ITEM 10-3194
\$49.95

• New, Turdan Electric model# A1K05J.

SPECIFICATIONS

- Power 1/2 HP
- Voltage 180 Volt DC
- Amperage 2.75 Amps
- Speed 2500 RPM
- Rotation Reversible
- Service Factor 1
- Bearings Ball
- Enclosure TENV
- Duty Continuous
- Frame C71
- Face Mount
- Shaft 5/8" dia. x 2" overall length keyed
- Size 8 3/4" x 6 1/2" x 6 1/2"
- Shpg. 23 lbs.

4000 RPM 12 Volt DC Fan Motor



ITEM 10-2032
\$12.99

• Replacement motor for automotive fan. Model 1632F.

SPECIFICATIONS

- Voltage 12 VDC
- Speed 4000 RPM
- Amperage 2.2 Amps @ no load
- Housing Vented
- Rotation CW
- Shaft 5/16" dia. x 1 1/8" w/flat
- Mount 3 holes on 6" B.C.
- Overall size 6 1/4" dia. x 4 1/4"
- Shpg. 5 lbs.

12 Volt DC Permanent Magnet Motor



ITEM 10-2548
\$14.99

• New, MAMCO Model CP-12-132 permanent magnet motor. Designed to fit into a 4.3" dia. opening with O-ring groove in edge of front mounting flange. Shaft is partially recessed in flange, extends 5/8" from face.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 2.5 (no load)
- Speed 4400 RPM (no load)
- Torque 45 in.oz. at 3600 RPM 15 amps
- Rotation reversible
- Bearings bronze sleeve
- Enclosure TENV
- Duty continuous
- Shaft 5/16" dia. x 1" w/threaded end
- Size 4.33" dia. x 4 3/4"
- Shpg. 5 lbs.

14000 RPM 6 Volt DC PM Motor

ITEM 10-3102
\$3.99

• New, permanent magnet motor. Shaft has 0.38" dia. 12 tooth gear on it.

SPECIFICATIONS

- Voltage 6 DC
- Amperage 0.3 amps (no load)
- Speed 14000 RPM
- Rotation Reversible
- Enclosure Open
- Duty Intermittant
- Mount Two tapped holes on face
- Shaft 0.09 dia. x 0.425
- Size 1 1/8" dia. x 2"
- Shpg. 1/2 lb.



6000 RPM, 12 VDC

ITEM 10-2631
\$7.99

• New, permanent magnet motor. Built for use in battery powered weed trimmers. Could also be used as small DC generator.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 1 Amp (no load)
- Speed 6000 RPM
- Rotation reversible
- Bearings bronze bushings
- Enclosure TENV
- Duty intermittent
- Mnt. 2 studs rear 2 1/4" c/c
- Shaft 1/4" dia. x 1" w/flat
- Size 3.15" dia. x 1 3/4"
- Shpg. 3 lbs.



3200 RPM, 12 VDC Motor

ITEM 10-2606
\$2.99

• New, DAEWOO permanent magnet motor. Originally for automotive power seat drive. Accepts 3mm square flex drive cable into each end. Packard 12064750 terminal (3/16" push-on spades).

SPECIFICATIONS

- Voltage 12 DC
- Amperage 1.1 Amps
- Speed 3200 RPM
- Rotation reversible
- Enclosure TENV
- Duty intermittent
- Mount 2 screws each end
- Shaft female 3mm socket at each end
- Size 2" dia. x 4 5/8"
- Shpg. 2 lbs.



4850 RPM 12 VDC Fan Motor

ITEM 10-2033
\$8.95

• Unused, old inventory. Permanent magnet motor. Automotive fan motor.

SPECIFICATIONS

- Voltage 12 VDC
- Amperage 2.5 Amps, No Load
- Speed 4850 RPM @ 12V, No Load
- Rotation Reversible
- Enclosure Open
- Duty Continuous, Air-Over
- Mount None
- Shaft 5/16" dia. x 1 1/8" overall length w/ flat
- Size 5 1/4" W x 6 1/2" dia.
- Shpg. 6 lbs



DC Motor Grab Bag



ITEM 10-2023

\$24.95

• 5 assorted new wound field direct current motors made for automotive fans. Most operate on 12 VDC, some were made to operate on 24 VDC but can run on 12 VDC. Photo shows five motors pulled at random and is intended to give a general representation only. Shpg. 20 lbs.

SPECIFICATIONS

- Voltage 12 DC
- Amps: 1.73, no load
- 90 ohm resistance
- 3600 RPM
- Rotation reversible
- Mount: 6 7/8" B.C.
- Shaft: 5/16" x 1 1/8" w/flat
- Motor Size 3" diam. x 5"
- Size w/mnt.: 7 3/4" dia. x 5"

12 VDC Permanent Magnet Motor

ITEM 10-3096
\$3.99

• New, MABUCHI permanent magnet motor. Model RS-545PH-19185. Leads have Molex connector.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 0.2 Amps
- Speed 1450 RPM
- Torque 1.4 oz.in.
- Rotation Reversible
- Duty Intermittent
- Enclosure Open
- Mount 2 M3x0.5 tapped holes 25mm c/c
- Shaft 1/8" dia x 1/2" long (knurled)
- Size 1.45" dia. x 2"
- Shpg. 1/2 lb.



1/4 HP 1500 RPM 24 VDC Motor

ITEM 10-3403
\$129.95

• New, 24 VDC 1500 RPM motor, model number 730203.

SPECIFICATIONS

- Power 1/4 HP
- Voltage 24 DC
- Amperage 13.5 Amps
- Speed 1500 RPM
- Rotation Reversible
- Thermal Overload Protection none
- Duty S2 60 minutes
- Face Mount Four M6-1.0 threaded holes in motor face on 3 3/8" B.C., 2 3/4" pilot
- Shaft 14mm dia. x 7/8" overall length w/ 5mm wide x 3/4" long keyway
- Size 7 1/2" x 5" x 4 1/2"
- Shpg. 14 lbs.



1/10 HP 4150 RPM 12 Volt DC Motor

ITEM 10-3390
\$24.95

• New, PROTECH model 1-030-015 permanent magnet motor. Heavy duty leads with connectors.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 12 Amps
- Power 0.13 HP
- Torque 13 oz.in.
- Speed 4150 RPM
- Rotation Reversible
- Enclosure TENV
- Duty Intermittent
- Face Mount 3 tapped #10-32 holes on 2 9/16" dia. B.C. w/ 1.146" dia. pilot
- Shaft 3/8" dia. x 3" w/flat
- Size 4 5/8" x 3" x 3"
- Shpg. 5 lbs.

