



16-1525



16-1528

## 12 VDC Fans

- New, axial fans. Provide airflow at very low sound levels. Low power consumption. Easy to mount with holes in each corner.



16-1531

ITEM	CFM	Mfg.	Watts	RPM	# Blades	db	Bearing	Size	Shpg.	Price
16-1525	11.9	Protechnic	2.3	5800	9	34.6	Rifle	50mm x 50mm x 10mm	¼ lb.	<b>\$2.99</b>
16-1527	50	Delta	10.44		7	55	Ball	60mm x 60mm x 25mm	¼ lb.	<b>\$3.49</b>
16-1528	109	Nidec	20.7	8500	7	60	Ball	80mm x 80mm x 38mm	½ lb.	<b>\$3.99</b>
16-1531	110	SanAce	13.2	5000	7	50	Ball	92mm x 92mm x 38mm	½ lb.	<b>\$3.99</b>
16-1558	285	TKFAN	30		7	72	Ball	120mm x 120mm x 38mm	½ lb.	<b>\$4.95</b>

### 10 CFM 12 VDC Blower

ITEM 16-1545  
**\$6.95**

• New, NICEC Gamma28 model A33475-68 centrifugal blower. Brushless design with lubricated ball bearing. Flat mounting on back side. 2 thru holes for mounting.

**SPECIFICATIONS**

- Flow 10 CFM max.
- Voltage 12 DC
- Amperage 0.29 Amps
- Inlet 1 7/8" dia.
- Outlet 1 5/16" x 1 3/8"
- Size 3" x 3" x 1 1/8"
- Shpg. ¼ lb.



### 26 CFM, 48 VDC

ITEM 16-1449  
**\$8.95**

• New, ROTRON Biscuit centrifugal blower. Operating voltage range 24-56 DC. Plastic body.

**SPECIFICATIONS**

- Model BD48B3
- Airflow 26 CFM
- Voltage 48 DC
- Pressure 0.87" H2O
- Inlet 2 3/4" dia.



- Outlet 1" x 2 3/16"
- Blower wheel 3 1/4" diam. x 5/8"
- Mount 4 holes thru body
- Size 4.8" x 4.8" x 1.6"
- Shpg. 2 lbs.

### 12 VDC Heavy Duty Cab Fan

▲ **Cab Fan**  
Two Speed  
Metal Blades

ITEM 16-1458-12

**\$76.40**



• Brand new, SERVICEMATE two speed cab fans. Metal mounting base with swivel ball joint to position air flow. Toggle switch for low/off/high. Aluminum fan blades with chromed steel shroud. Single wire installation (ground thru base).

**SPECIFICATIONS**

- Airflow 285 CFM (high speed)
- Voltage 12 DC
- Amperage 1.6/2.6 Amps
- Blade Dia. 6 1/4"
- Number of Blades 4
- Mount 4 hole pattern 1 3/4" x 1"
- Size 7 1/4" x 5" x 8 3/4"
- Shpg. 5 lbs.


### 32 CFM, 12 VDC Blower

ITEM 16-1455  
**\$8.95**

• New, 12 volt fan. Model 12032HB-TE. Quiet operation. Flat mounting on back side. Three thru holes for mounting with brass inserts.

**SPECIFICATIONS**

- Flow 32 CFM max.
- Voltage 12 DC
- Amperage 0.62 Amps
- Power 7.5 Watts
- Speed 2400 RPM
- Inlet 3" dia.
- Outlet 1 1/8" x 2 1/4"
- Blower Wheel 120mm x 32mm
- Size 4 3/4" x 4 3/4" x 1 1/4"
- Shpg. 1 lb.



### 24 VDC Motorized Impellor

ITEM 16-1482  
**\$7.99**

• New MCCLEAN COOLING Model DB400-2420S6. Backward curved motorized impellor. Use for cabinet cooling, air filtration systems. Air is discharged in 360° pattern around impellor. Narrow profile and vertical or horizontal mount to save space. Plastic construction. Quiet operation with high airflow.

**SPECIFICATIONS**

- Flow 115 CFM
- Voltage 24 VDC
- Amps 1.4
- Speed 5900 RPM (max).
- Mounting Flange Triangular with hole in each corner
- Speed 5900 RPM (max).
- Inlet 2 3/4" dia.
- Outlet 360 degrees around perimeter
- Size 4" dia. x 2"
- Shpg. 2 lbs.



### 12 VDC Cab Fan

ITEM 16-1503  
**\$22.45**

• Brand new, two speed cab fan. Metal mounting base with swivel ball joint to position air flow. Toggle switch for low/off/high. Aluminum fan blades with chromed steel shroud. Two wire installation.

**SPECIFICATIONS**

- Voltage 12 DC
- Amperage 0.6/0.9 Amps
- Blade Dia. 6 1/4"
- Number of Blades 4
- Mount 3 hole pattern 2 3/16" B.C.
- Size 7 1/4" x 4 1/4" x 8 3/4"
- Shpg. 3 lbs.



### 5" Grill 61 CFM 24 VDC Filter Fan

ITEM 16-1546-5-B  
**\$29.95**

• New, Pentair fresh air enclosure filter fan model SF0524514. High airflow and low noise for cooling electrical equipment or general air circulation. Grey plastic grill. Air is pulled through the plastic grill and filter. Metal housing with plastic blades. Click-fit design installs into enclosure wall. Snap over grill with foam filter. 42db rating. Terminal block electrical connection.

**SPECIFICATIONS**

- Pull Type Fan
- Flow 61 CFM max.
- Voltage 24 DC
- Amperage 0.17 Amps
- Power 4.1 Watts
- Operating Temperature Range Min. -4° F to Max. 149° F
- Speed 3050 RPM
- IP Rating 55
- Mount 4 holes on 5 1/4" x 5 1/4"
- Cutout Dimensions 4.92" x 4.92"
- Blade Dia. 4 1/2"
- Number of Blades 5
- Size 5 7/8" x 5 7/8" x 2 3/4"
- Shpg. 3 lbs.



### 12-28 VDC Axial Fan

ITEM 16-1553  
**\$9.95**

• New, PAPST type 6224N/17HT axial fan. Ball bearings. Metal housing with plastic impellor. 12" cord with 5 pin connector plug. Air discharges on motor support side.

**SPECIFICATIONS**

- Air Flow 282.5 CFM max
- Voltage (rated) 24 VDC, useable on 12-28 VDC
- Amperage 1.1 Amps
- Power 26 Watts
- Sound Level 61 dB
- Mount 4 thru-holes
- Blade 5 5/8" dia.
- Number of blades 7
- Size 6 3/4" dia. x 2"
- Shpg. 3 lbs.



### 9 VDC Muffin Fan

ITEM 16-1047  
**\$5.99**

• New ROTRON. Supplied with housing to direct airflow through fan and turn 90° through 1 1/2" x 4 1/2" outlet. Ideal for moving air through cabinets with restricted access. Operates on 9 VDC, 0.6 amps. Approx. 90 CFM airflow. 5 blades, 4 1/4" diam. Size 5" x 3 1/8" x 5". Shpg. 2 lbs.

