

Humphrey Multi-Mount Air Cylinders

• New, HUMPHREY. Multi-mount style air cylinders. Aluminum construction, rated to 100 PSI working pressure. 10-32 ports.

Bore - Rod Dimensions

1/4" = 0.118" 3/8" = 0.197" 5/8" = 0.236"

Single Acting
Push Only



ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10621	1/4"	1/4"	2.14"	1/2 lb.	\$5.95
4-10622	3/8"	1/4"	2.337"	3/4 lb.	\$5.95
4-10633	3/8"	1/2"	2.587"	3/4 lb.	\$5.95
4-10640	5/8"	1/4"	2.533"	1/2 lb.	\$6.95
4-10647	5/8"	1/2"	2.783"	3/4 lb.	\$6.95

Double Acting

ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10618	1/4"	1/2"	2.193"	1/2 lb.	\$5.95
4-10613	1/4"	3/4"	2.443"	1/2 lb.	\$5.95
4-10631	3/8"	3/4"	2.64"	1/2 lb.	\$5.95
4-10637	5/8"	3/4"	2.837"	1 lb.	\$7.99

Double Acting
Double Rod



ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10627	3/8"	1/2"	3.4375"	1/4 lb.	\$16.95
4-10630	3/8"	3/4"	3.902"	1/2 lb.	\$8.95
4-10649	5/8"	1/2"	3.677"	3/4 lb.	\$9.95
4-10636	5/8"	3/4"	4.177"	3/4 lb.	\$9.95

12 mm x 2 3/4" DA Air Cylinder



ITEM 4-1630 **\$5.95**

• New, FESTO Model DO-12-74-PP-SA air cylinder. Stainless steel tubing with aluminum end-caps. 10-32 ports with adapters to 1/16" hosebarbs. Rod end threaded 4 mm, 0.70" pitch. Base end-cap tapped 4 mm, 0.70" pitch. Cushions at both ends of stroke.

SPECIFICATIONS

- Double Acting
- Bore 12 mm (0.472")
- Stroke 2 3/4"
- Rod dia. 4 mm (0.156")
- Press. 8 Bar (116 PSI) max
- Ports 1/16" hosebarbs
- Retracted lgth. 6 3/4" end-to-end
- Shpg. 1 lb.

3/4" Bore Air Cylinder



ITEM 4-1761-A **\$4.95**

• Used BIMBA stainless steel. Extend port in base, retract port in rod end. P/N 53E743. Stroke 3/4", retracted lgth. 5" (rod end to base end).

SPECIFICATIONS

- Double acting
- Bore 3/4"
- PSI max. 250
- Rod diam. 1/4"
- Ports 1/8" NPT
- Threaded rod end 1/4"-28 x 1/2" long
- Nose mount threaded 5/8"-18
- Flat base 0.81" O.D.
- Shpg. 1 lb.

Double Acting Pneumatic Cylinders

• New. BUYERS double acting pneumatic cylinder. Has a cushion valve on each end. H Models have hinge mount accessory kit. Ideal for remote tailgate latches.

SPECIFICATIONS


• Double Acting

- Gland Retainer Tie-Rod
- Pressure 200 PSI


- Ports 1/4" NPT
- Rod End Clevis w/ Jam Nut

- Base End Clevis
- Pin Holes 1/2"

ITEM	Bore	Stroke	Rod Dia.	R. Lgth.	Shpg.	Price
4-1968-6	2.5"	6"	0.75"	14.5"	8.5 lbs.	\$91.40
4-1968-8	2.5"	8"	0.75"	16.5"	8.5 lbs.	\$91.80
4-1968-8-H	2.5"	8"	0.75"	16.5"	9.5 lbs.	\$103.25
4-1969-6	3.25"	6"	1"	16.25"	11 lbs.	\$112.35
4-1969-8	3.25"	8"	1"	18.25"	13 lbs.	\$132.45
4-1969-8-H	3.25"	8"	1"	18.25"	14 lbs.	\$150.05



7.5 CFM, Single Stage Air Compressor



ITEM 4-1916 **\$149.95**

• New, V-twin cylinder single stage air compressor. Cast iron block and cylinder with aluminum head. Oil level sight glass.

SPECIFICATIONS

- One stage, two cylinders
- Flow: 7.5 CFM open flow
- Pressure 115 PSI max.
- Power reqd. 2 HP max.
- Speed 980 RPM max.
- Rotation CCW
- Flywheel 10 1/2" A belt
- Port 1/2" OD tube
- 1st stage bore/stroke 55mm x 45mm
- Mount 6 7/8" x 3 5/8"
- Size 13" x 10 1/2" x 10 1/2"
- Shpg. 37 lbs.

7.1 CFM, Single Stage Air Compressor



ITEM 4-1972 **\$149.95**

• New, B2800 2 HP two cylinder single stage air compressor. Oil level sight glass.

SPECIFICATIONS

- Cylinders 2
- Stages Single
- Flow 7.1 CFM
- Pressure 90 PSI max.
- Power Req'd. 2 HP max.
- Speed 1000 RPM max.
- Rotation CCW
- Flywheel 11" dia. A belt
- Port 1/2" NPT
- 1st Stage Bore/Stroke 2.36"/1.97"
- Mount Four 0.34" dia. holes on 5 1/4" x 6 1/4" centers
- Size 10" x 11" x 12 1/2"
- Shpg. 23 lbs.

Air Filter Pair



ITEM 4-1930 **\$4.95**

• New, pair of plastic housing air filters for air compressors. Uses paper element.

SPECIFICATIONS

- 1/2" NPT connection
- 1/2" inlet tube
- 4" dia x 2"
- Shpg 1 lb.

2" x 8" Air Cylinder



ITEM 4-1971 **\$89.95**

• New, BIMBA, TRD, model CYL-9929418 double acting air cylinder. Tie-rod construction. Foot mounted. Cylinder has a integrated cushion valve on each end.

SPECIFICATIONS

- Model CYL-9929418
- Double Acting
- Bore/Stroke 2" x 8"
- Rod 5/8" dia.
- Pressure 250 PSI max
- Ports 3/8" NPT Ports
- Rod 7/16"-20 UNF thread
- Mounting Pattern 10 7/8" x 3 1/4"
- Overall Retracted Length 13 3/4"
- Shpg 6 lbs.

5" x 12" x 1" Air Cylinder



ITEM 4-9355 **\$199.95**

• Unused old inventory. Tie-rod, double acting pneumatic cylinder.

SPECIFICATIONS

- Double Acting
- Bore x Stroke 5" x 12"
- Pressure 250 PSI max.
- Rod Dia. 1"
- Ports 1/2" NPT
- Retracted Length 21.75"
- Clevis Ends
- Pin Holes 0.75"
- Shpg. 54 lbs.

115 VAC Solenoid Valve



ITEM 4-1923 **\$9.95**

• New PARKER model 15-200339-002E solenoid valve. Normally closed, furnished with brass right angle adapters 7/16"-20 male 45 degree flare on inlet and 1/4" OD tubing on outlet. Stainless steel body.

SPECIFICATIONS

- Voltage 115 VAC
- Power consumption 6 Watts
- Pressure Rating 150 PSI
- Orifice 1/16"
- Ports 1/8" NPT
- Size 2" x 1 3/8" x 2 1/4"
- Shpg. 1 lb.

1/4" NPT Mini Air Regulator w/gauge




ITEM 4-9094 **\$5.95**

• New, Campbell Hausfeld part number RE206901AV. Inline air pressure regulator with gauge.

SPECIFICATIONS

- Inlet Pressure 200 PSI max.
- Outlet Pressure Range 0-135 PSI
- Ports 1/4" NPT
- Gauge Port 1/8" NPT
- Size 3 3/8" x 1 1/2" x 2 3/4"
- Shpg. 1/2 lb.

24 VAC Solenoid Valve



ITEM 20-1311 **\$9.99**

• New, ASCO. Operates on 24 VAC, 6 watts. Ports 1/8" NPT. Pressure ratings air 275 PSI, water 200 PSI, oil 150 PSI. Normally open two ways. Brass body. Size 3 1/4" x 2" x 1 1/2". Shpg. 1 1/2 lbs.