

2.50-4 Wheel Assembly

ITEM 1-5932

\$5.95

• New, rubber tire with tube on steel wheel. Offset hub.

SPECIFICATIONS

- Size 2.50-4
- O.D. 8½"
- Bore ⅝" dia.
- Thru Bore Length 17/16"
- Tread Width 2¾"
- Tube Type
- Load Range 297 lbs. Pressure 30 PSI max.
- Ply Rating 2
- Shpg. 4 lbs.



13 x 4.0-6 Wheel Assembly

ITEM 1-5326

\$17.95

• NEW, Pneumatic tire mounted on gray steel rim w/plastic bushing

SPECIFICATIONS

- Size 13 x 4.0-6
- Outside Diameter 12¾" dia.
- Cross Section 3" Wide
- Tread Knobby
- Tread Width 2¾"
- Bore ⅝"
- Bore Thru-Length 3½"
- Hub Type Offset
- Bearing Plastic Bushing
- Tire Tubeless
- Load Rating 300 lbs.
- Pressure 30 PSI max.
- Ply Rating 2
- Shpg. 5 lbs.



18 x 10.50-10 Smooth Tire and Wheel

ITEM 1-5511

\$59.95

• New CARLISLE SMOOTH model 1L0169 tire on yellow 4 bolt steel rim. Not for Highway Service.


SPECIFICATIONS

- Size 18 x 10.50-10
- O.D. 18.4"
- Tread Smooth
- Tread Width 6½"
- Mount: 4 hole on 4" B.C. 2½" dia. pilot
- Backspace 4"
- Tubeless
- Load Rating 1100 lbs. @ 24 PSI
- Ply Rating 4
- Ply Material Nylon
- Actual weight 22 lbs.
- Shpg. 30 lbs.



Trailer Bearing Kits

• Brand new, DURA-ROLL replacement trailer bearing kit. Use with boat, camping, utility and snowmobile trailers. 1 kit per wheel required. Bearings must be packed with grease before installation. Kit contents available at www.surpluscenter.com. Fully tested and exceeds VESC regulations. Installation instructions included.



ITEM	Typical Axle Bearing Bore		Rating (lbs.)	Shpg.	Price
	Inner	Outer			
1-3535	1"	1"	2000	1 lb.	\$14.85
1-3536	¾"	¾"	2000	1 lb.	\$11.90
1-3537	1¼"	1¼"	2000	1½ lbs.	\$14.35
1-3538	1⅝"	1⅞"	3500	1 lb.	\$15.00
1-3539	1⅞"	2"	2000	1 lb.	\$14.50

18 x 6.50-8 Wheel Assembly

ITEM 1-5725

\$32.99

• New, WANDA pneumatic tire mounted on steel rim. NOT for Highway Service.

SPECIFICATIONS

- Size 18 x 6.50-8
- Outside Diameter 18" dia.
- Cross Section 6½" Wide
- Tread Knobby
- Tread Width 5½"
- Bore 1"
- Bore Thru-Length 3"
- Hub Type Centered
- Tire Tubeless
- Load Rating 330 lbs. @ 10 PSI
- Ply Rating 2
- Shpg. 16 lbs.



4.10/3.50-4 Wheel Assembly

ITEM 1-4932

\$5.95

• New, pneumatic tire mounted on steel rim.

SPECIFICATIONS

- Size 4.00/3.50-4
- Ball bearing
- Outside dia. 10¼"
- Tube type
- Cross section 3¼"
- Load rating 300 lbs.
- Tread Knobby
- Pressure 30 PSI max.
- Hub ⅝" bore x 2¾" wide
- Ply rating 2
- Hub type offset
- Shpg. 5 lbs.



4.10/3.50-4 Wheel Assembly

ITEM 1-4889

\$2.99

• New, pneumatic tire mounted on plastic rim. Tires may be dusty and have some grime on them from warehouse storage.

SPECIFICATIONS

- Size 4.00/3.50-4
- Outside Diameter 10¼"
- Cross section 3¼"
- Tread Knobby
- Hub ⅝" bore x 27/16" wide
- Hub Type Offset
- Bearing Plastic bushing
- Tire Tube type
- Load Rating 300 lbs.
- Pressure 30 PSI max.
- Ply Rating 2
- Shpg. 5 lbs.



Hi-Speed Wheel Hubs



• Brand new. Use with a 1" diameter spindle to mount high speed wheels on small trailers. Includes grease cap, tapered roller bearings and seal. **Shpg. 7 lbs.**

ITEM	Bolts	Bolt Circle	Type	Price
1-1133	4	4"	Lug Bolt	\$43.95
1-1134	5	4½"	Lug Bolt	\$46.70
1-4884	4	4"	Stud	\$45.05
1-4885	5	4½"	Stud	\$48.00

1" Trailer Spindle

ITEM 1-1128

• Brand new steel trailer spindle with castle nut. 1" diam. x 8½" long. **Shpg. 4 lbs.**



13 x 5.00-6 Pair Snowblower Wheels

ITEM 1-5833

\$36.95

• New pair of CARLISLE model X-TRAC tires mounted on black painted steel wheels. Built for snow blowers. Directional lug tread mounted with ¼" diameter cross-hole to outside. Not for highway service.

SPECIFICATIONS

- Size 13 x 5.00-6
- O.D. 12"
- Tread Directional lug
- Tread width 4½"
- Bore ¾" diam.
- Bore Thru-Length 4½"
- Max. Pressure 20 PSI
- Offset None
- Crosshole Diameter ¼"
- Load Range 290 lbs. (per tire)
- Hub Smooth w/crosshole
- Inner hub to crosshole length 4¼"
- Tubeless
- Ply Rating 2 Ply
- Shpg. 19 lbs.



4.80-8 Trailer Wheel Assembly

ITEM 1-5711

\$19.95

• New, WANDA JOURNEY pneumatic tire mounted on steel rim. Ideal replacement log splitter and small trailer wheel for high speed trailer use. Small trailer use only DOT R2A3 max. Grease seal and roller bearings in the hub. Dust cover NOT included.

SPECIFICATIONS

- Size 4.80-8
- Outside Diameter 15¾"
- Cross Section 4½" Wide
- Tread Sawtooth
- Tread Width 3"
- Bore 1"
- Bore Thru-Length 4¾"
- Bearing Thru-Length 3½"
- Hub Type Centered
- Bearing Roller Bearing
- Tire Tubeless
- Load Rating 590 lbs. at 60 PSI, load range B
- Ply Rating 4
- Shpg. 14 lbs.



4.80/4.00-8 Wheelbarrow Wheel

ITEM 1-5684

\$65.60

• New, LOADSTAR wheelbarrow tire on steel wheel with ball bearings. NHS

SPECIFICATIONS

- Size 4.80/4.00-8
- Outside Diameter 16"
- Tread Sawtooth
- Tread Width 3¼"
- Cross section 4"
- Bore ⅝"
- Bore Thru-Length 6"
- Hub Type Centered
- Bearing Ball
- Tire Tubeless
- Load Rating 590 lbs.
- Pressure 30 PSI max.
- Ply Rating 4
- Shpg. 12 lbs.



8" x 5.5" Steel Wheel Rim w/Bearings

ITEM 1-5079

\$5.99

• New take-offs, black steel rim with dual ball bearings for 8" tires.

SPECIFICATIONS

- Wheel Rim Size 8" x 5.5"
- O.D. 8⅞"
- Width 6⅞"
- Hub ¾" Bore x 3⅞" wide
- Hub Type Offset
- Shpg. 8 lbs.

