

8 GPM Wolverine by Prince MB Series Compact Double Acting Directional Control Valves

• Brand new WOLVERINE by PRINCE MB Series directional control valve for operating double acting cylinders. Ideal for small tractor and other low flow applications requiring a compact control valve. Features include monoblock construction, load check, built-in adjustable pressure relief valve, spring centering spool action, open center with enclosed plug to convert to power beyond or closed center, side or top inlet/outlet ports and vertical or horizontal handle mounting.

SPECIFICATIONS

- Flow 8 GPM max.
- Pressure 3500 PSI max.
- Relief valve 2000 PSI, adj. 2000-3500 PSI
- Reqd. filtration ISO 4406 19/17/14
- Mount 3 hole base
- In/Out ports SAE 8
- Work ports SAE 8
- Open center convertible to power beyond or closed ctr.



Motoring Spool Valves can be found on page 31

# Spools	ITEM	Style	Size	Shpg.	Price
One	9-7861	DA spring centered	7 ⁵ / ₈ " x 4" x 2 ¹ / ₄ "	9 lbs.	\$137.05
One	9-7861-F	DA spring centered w/float	9 ¹ / ₈ " x 4" x 2 ¹ / ₄ "	9 lbs.	\$284.20
Two	9-7862	DA spring centered	7 ⁵ / ₈ " x 5 ⁷ / ₁₆ " x 2 ¹ / ₄ "	12 lbs.	\$215.35
Two	9-7862-F*	DA spring centered w/float	9 ¹ / ₈ " x 5 ⁷ / ₁₆ " x 2 ¹ / ₄ "	12 lbs.	\$302.40
Three	9-7863	DA spring centered	7 ⁵ / ₈ " x 6 ¹ / ₁₆ " x 2 ¹ / ₄ "	15 lbs.	\$340.20
Four	9-7864	DA spring centered	7 ⁵ / ₈ " x 8 ⁷ / ₁₆ " x 2 ¹ / ₄ "	18 lbs.	\$392.85
Five	9-7865	DA spring centered	7 ⁵ / ₈ " x 9 ¹³ / ₁₆ " x 2 ¹ / ₄ "	21 lbs.	\$479.95
Six	9-7866	DA spring centered	7 ⁵ / ₈ " x 11 ⁷ / ₁₆ " x 2 ¹ / ₄ "	24 lbs.	\$568.35

* First spool detented float

MB Series Accessories

Power Beyond/Closed Center Conversion Plug

ITEM 9-7867-B \$12.00
• For use with Wolverine MB Series valves. Power beyond plug is necessary to convert valves to closed center. **Shpg. 1/10 lb.**

3 Position Detent Kit

ITEM 9-7867-D \$79.50
• Detent kit for Wolverine MB Series valve. Converts spring centering spools to 3 position manual detent. **Shpg. 1/2 lb.**



Joystick Handle Kit

ITEM 9-7867-J \$298.50
• Brand new, straight joystick handle for use with Wolverine MB Series valves. Allows one lever to control two different adjacent work sections. Spools can be operated independently or simultaneously. If two joysticks are installed on one stack valve, it is recommended that there be two standard work sections between them to prevent handle interference.

SPECIFICATIONS
• Straight handle joystick control • **Shpg. 2 lbs.**



Compact Double Acting Directional Control Valve

• New CHIEF directional control valve for operating double acting cylinders. Ideal for small tractors and other compact applications. Features include monoblock construction, built-in adjustable pressure relief valve, load check, spring centering spool action, open center, side inlet/outlet ports, top work ports and vertical or horizontal handle mounting.

SPECIFICATIONS

- Open Center
- Double Acting
- Spring Centering
- Flow 10 GPM max.
- Pressure 3600 PSI max.
- Relief Valve Set at 2250 PSI, adj. 1500-3600 PSI
- In/Out Ports SAE 10
- Work Ports SAE 8
- Mount 2 hole base

1 Spool
ITEM 9-12460 \$69.95
Size 8¹/₄" x 3⁵/₈" x 2⁷/₁₆" **Shpg. 8 lbs.**

2 Spool
ITEM 9-12461 \$119.95
Size 8¹/₄" x 5⁵/₈" x 2⁷/₁₆" **Shpg. 12 lbs.**

3 Spool Directional Control Valve

ITEM 9-7977 \$384.10

• Brand new, WOLVERINE by PRINCE WVS series monoblock directional control valves. Features cast iron construction, load check, built-in adjustable pressure relief, open center, side or top outlet port and vertical or horizontal handle mounting. Can be converted to closed center or power beyond with the addition of a power beyond sleeve. (sold separately) Item # 9-7998-PB.

SPECIFICATIONS

- Open Center
- Spools Three
- Flow 14 GPM max.
- Pressure 4000 PSI max.
- Relief Valve 2500 PSI, Adj. 2200-3200 PSI
- Reqd. Filtration ISO 4406 19/ 17/ 14
- In/Out Ports SAE 8
- Work Ports SAE 8
- Mount 3 hole base
- Size 8⁵/₁₆" x 6¹/₁₆" x 2³/₄"
- **Shpg. 16 lbs.**

Spool Details:

- Spool 1 DA cylinder spool, spring to center
- Spool 2 DA cylinder spool, spring to center
- Spool 3 DA cylinder spool, spring to center



Compact 6 Spool Double Acting Directional Control Valve

ITEM 9-16147 \$399.95

• New WOLVERINE by PRINCE model W-V-C03, MB series directional control valve for operating double acting cylinders. Ideal for small tractor and other low flow applications requiring a compact control valve. Features include monoblock construction, load check, built-in adjustable pressure relief valve, spring centering spool action, open center with enclosed plug to convert to power beyond or closed center, side or top inlet/outlet ports and vertical or horizontal handle mounting. Painted black.

SPECIFICATIONS

- Open Center Convertible to power beyond or closed center
- Spools Six
- Flow 8 GPM max.
- Pressure 3500 PSI max.
- In/Out Ports SAE 8
- Work Ports SAE 8
- Relief Valve 2500 PSI, adj. 2000-3500 PSI
- Reqd. Filtration ISO 4406 19/17/14
- Mount 3 hole base
- Size 7⁵/₈" x 11⁷/₁₆" x 2¹/₄"
- **Shpg. 26 lbs.**

