


Prince



Prince "Royal" Line Cylinders

Brand new, double acting welded cylinders made by PRINCE MFG. 2500 PSI working pressure. Fully chromed piston rod.



Dimensional Data for Prince "Royal" Cylinders

Bore	A	B	C	Crosstube Width	
				L1	L2
2 1/2"	2 5/16"	9/16"	3/4"	3"	1 3/8"
3"	2 5/16"	1 1/16"	1"	3 1/2"	1 1/2"
3 1/2"	1 11/16"	1 1/16"	1"	4"	1 1/2"
4"	2 1/8"	1 5/16"	1 1/8"	4 1/2"	2"

2 1/2" BORE

SPECIFICATIONS: Ports 3/8" NPT, 3/4" dia. pins.

ITEM	Stroke	Rod Dia.	Retraacted Lgth.	Shpg.	Price
9-1672-08	8"	1 3/8"	16"	20 lbs.	\$279.45
9-1672-12	12"	1 3/8"	20"	23 lbs.	\$285.55
9-1672-16	16"	1 3/8"	24"	27 lbs.	\$296.35
9-1672-20	20"	1 3/8"	28"	30 lbs.	\$303.10
9-1672-24	24"	1 3/8"	32"	35 lbs.	\$315.25
9-1672-30	30"	1 3/8"	38"	40 lbs.	\$342.25
9-1672-32	32"	1 3/8"	40"	42 lbs.	\$345.60
9-1672-36	36"	1 3/8"	44"	45 lbs.	\$362.50
9-1672-42	42"	1 3/8"	50"	52 lbs.	\$390.15

3 1/2" BORE

SPECIFICATIONS: Ports 1/2" NPT, 1" dia. pins.

ITEM	Stroke	Rod Retraacted		Shpg.	Price
		Dia.	Lgth.		
9-062-08	8"	1 1/2"	16"	30 lbs.	\$335.50
9-062-12	12"	1 1/2"	20"	34 lbs.	\$351.00
9-062-16	16"	1 1/2"	24"	40 lbs.	\$370.60
9-062-20	20"	1 1/2"	28"	43 lbs.	\$387.45
9-062-24	24"	1 1/2"	32"	47 lbs.	\$396.90
9-062-30	30"	1 1/2"	38"	51 lbs.	\$430.00
9-062-32	32"	1 1/2"	40"	57 lbs.	\$552.00
9-062-36	36"	1 1/2"	44"	62 lbs.	\$463.05
9-062-40	40"	1 1/2"	48"	66 lbs.	\$443.15
9-062-42	42"	1 1/2"	50"	69 lbs.	\$464.80
9-062-48	48"	1 1/2"	56"	75 lbs.	\$548.80

3" BORE

SPECIFICATIONS: Ports 1/2" NPT, 1" dia. pins.

ITEM	Stroke	Rod Dia.	Retraacted Lgth.	Shpg.	Price
9-1650-08	8"	1 1/2"	16"	25 lbs.	\$324.00
9-1650-12	12"	1 1/2"	20"	30 lbs.	\$324.00
9-1650-16	16"	1 1/2"	24"	33 lbs.	\$330.10
9-1650-20	20"	1 1/2"	28"	37 lbs.	\$344.95
9-1650-24	24"	1 1/2"	32"	41 lbs.	\$352.35
9-1650-30	30"	1 1/2"	38"	47 lbs.	\$378.00
9-1650-32	32"	1 1/2"	40"	50 lbs.	\$366.00
9-1650-36	36"	1 1/2"	44"	53 lbs.	\$411.75
9-1650-40	40"	1 1/2"	48"	59 lbs.	\$400.50
9-1650-42	42"	1 1/2"	50"	61 lbs.	\$427.30
9-1650-48	48"	1 1/2"	56"	69 lbs.	\$475.90

4" BORE

SPECIFICATIONS: Ports 1/2" NPT, 1 1/4" dia. pins.

ITEM	Stroke	Rod Retraacted		Shpg.	Price
		Dia.	Lgth.		
9-030-08	8"	2"	17"	43 lbs.	\$444.15
9-030-12	12"	2"	21"	49 lbs.	\$461.05
9-030-16	16"	2"	25"	56 lbs.	\$479.95
9-030-20	20"	2"	29"	62 lbs.	\$496.80
9-030-24	24"	2"	33"	69 lbs.	\$526.50
9-030-30	30"	2"	39"	81 lbs.	\$536.65
9-030-32	32"	2"	41"	82 lbs.	\$552.85
9-030-36	36"	2"	45"	91 lbs.	\$589.95
9-030-40	40"	2"	49"	95 lbs.	\$610.20
9-030-42	42"	2"	51"	99 lbs.	\$620.35
9-030-48	48"	2"	57"	106 lbs.	\$687.85
9-030-60	60"	2"	69"	127 lbs.	\$759.40

Cylinder Definitions


Bore - Inside diameter of cylinder

Stroke - How far a cylinder extends out

R-length - Distance in inches between pin centers when cylinder is retracted

Rod Diameter - Diameter of cylinder rod

Single Acting - Cylinder is powered one way



Double Acting - Cylinder is powered both ways (two way)

Crosstube End - Round tube welded perpendicular to cylinder

Single Eye End - For mounting between two mounting ears.

Clevis End - Two mounting ears