

### 14 HP Kohler Engine

ITEM 28-2012  
**\$799.95**

• New, KOHLER Command Pro series horizontal shaft engine. Engine features overhead valves, cast iron cylinder liner, dual ball bearings, mechanical governor, electronic ignition, fuel valve and easy to use controls. Four stage air cleaner. Automatic low oil shutdown system. EPA and California EXH/EVP SORE compliant.

**SPECIFICATIONS**

- Model CH440-3275
- Engine Family NKHXS.4292GB
- Power 14 HP
- Torque 22.7 ft.-lb.
- Bore/Stroke 89mm/69mm
- Disp. 420 cc
- Speed 3600 RPM
- Start 12 Volt Electric Start and Recoil
- Charging System 10 Amps w/Regulator
- Fuel Tank 7.39 qt.
- Shaft Horizontal
- Shaft 1" dia. x 3<sup>31</sup>/<sub>64</sub>" keyway, tapped 3/8"-24 UNF
- Base Mount Four hole on 7<sup>11</sup>/<sub>16</sub>" x 3<sup>1</sup>/<sub>4</sub>" centers
- Accessory Mount Inner 4 bolt on 5" B.C. Outer 4 bolt on 6.5" B.C.
- Size 18" x 16<sup>1</sup>/<sub>4</sub>" x 18<sup>1</sup>/<sub>2</sub>"
- Shpg. 135 lbs.

Truck freight only.



### 10 HP Briggs & Stratton Engine

ITEM 28-2009  
**\$549.95**

• New, BRIGGS & STRATTON Vanguard commercial series engine. Features include cast iron cylinder sleeve, float carburetor, electronic ignition, overhead valves, air cleaner, compression release, engine mounted controls, accessory mount and fuel shut off. EPA compliant and California EXH/EVP SORE compliant.

**SPECIFICATIONS**

- Model 19L2320110F1
- Power 10 HP (Gross)
- Disp. 305 cc
- Speed 3600 RPM
- Start Recoil
- Shaft Horizontal
- Shaft 1" diam. x 3<sup>31</sup>/<sub>64</sub>" w/ keyway tapped 7/16"-20
- Accessory Mount Inner 4 bolt on 3<sup>5</sup>/<sub>8</sub>" B.C. Middle 4 bolt on 5" B.C. Outer 4 bolt on 6.5" B.C.
- Fuel Tank 3.8 qt. (3.6L)
- Size 12<sup>1</sup>/<sub>2</sub>" x 16<sup>1</sup>/<sub>16</sub>" x 16"
- Dimensional Shpg. 70 lbs.



### 6.5 HP Briggs & Stratton Engine

ITEM 28-2008  
**\$399.95**

• New, BRIGGS & STRATTON XR950 Professional series engine. Features include cast iron cylinder sleeve, electronic ignition, overhead valves, ball bearing crankshaft, air cleaner, manual or remote throttle, manual choke, muffler, fuel shut off valve. EPA and California EXH/EVP SORE compliant.

**SPECIFICATIONS**

- Model 130G370130F1
- Power 6.5 HP (Gross) at 3600 RPM
- Torque 9.5 ft.-lbs.
- Disp. 208 cc
- Speed 3600 RPM
- Start 12 Volt Electric Start and Recoil
- Charging System 3 Amps
- Shaft Horizontal
- Shaft 3/4" diam. x 2<sup>27</sup>/<sub>64</sub>" w/ keyway tapped 5/16"-24
- Accessory Mount 4 Bolt on 3<sup>5</sup>/<sub>8</sub>" B.C.
- Fuel Tank 3.2 qt.
- Size 11<sup>3</sup>/<sub>8</sub>" x 14<sup>7</sup>/<sub>8</sub>" x 15"
- Dimensional Shpg. 58 lbs.



### 13.5 HP Briggs & Stratton Engine

ITEM 28-2011  
**\$649.95**

• New, BRIGGS & STRATTON XR Professional series horizontal shaft engine. Engine feature overhead valves, cast iron sleeve liner, ball bearing supported crankshaft, muffler, mechanical governor, electronic ignition, fuel valve and easy to use controls. Not for sale in California.

**SPECIFICATIONS**

- Model 25T2370085F1
- Engine Family XR Professional
- Power 13.5 HP (Gross)
- Torque 21.0 ft.-lbs (Gross)
- Disp. 420 cc
- Speed 3600 RPM
- Start 12 Volt Electric Start and Recoil
- Charging System 10 Amps
- Fuel Tank 1.709 Gallon
- Shaft Horizontal
- Shaft 1" dia. x 3<sup>31</sup>/<sub>64</sub>" keyed, tapped 7/16"-20 UNF
- Accessory Mount Inner 4 bolt on 5" B.C. Outer 4 bolt on 6.5" B.C.
- Size 12<sup>1</sup>/<sub>4</sub>" X 20<sup>3</sup>/<sub>8</sub>" x 18<sup>1</sup>/<sub>4</sub>"
- Shpg. 131 lbs.

Truck freight only.



### 8.5 HP Honda Engine

ITEM 28-2005  
**\$449.95**

• New, HONDA GX series horizontal shaft engine. Replacement engine for generator use and other applications using a tapered shaft. Engines feature overhead valves, cast iron sleeve liner, ball bearing supported crankshaft, mechanical governor, low-oil sensor, electronic ignition, ON/OFF switch and solenoid operated Eco Throttle to control engine RPM from idle to rated speed. No muffler or fuel tank.

**SPECIFICATIONS**

- Model GX270 RT1 VMT2
- Engine Family GX
- Power 8.5 HP at 3600 RPM
- Torque 14.1 ft.-lbs at 2500 RPM
- Disp. 270 cc
- Speed 3600 RPM
- Start Recoil
- Fuel Tank None
- Shaft Horizontal
- Shaft 22mm dia. x 4<sup>11</sup>/<sub>64</sub>" tapered 2<sup>1</sup>/<sub>4</sub>"ft tapped 5/16"-24 UNF
- Accessory Mount Inner 4 bolt on 5" B.C. Outer 4 bolt on 6.5" B.C.
- Size 12<sup>1</sup>/<sub>2</sub>" X 17" X 16<sup>1</sup>/<sub>2</sub>"
- Shpg 60 lbs.



### 5.5 ft.-lbs. Gross Torque Briggs & Stratton Engine

ITEM 28-2010  
**\$129.95**

• New, BRIGGS & STRATTON vertical shaft recoil start engine. Features include muffler, aluminum cylinder, fuel tank, mechanical governor, and primer bulb. Fixed speed. Compliance positive stop. EPA and California EXH/EVP SORE compliant.

**SPECIFICATIONS**

- Model 09P7020259F1
- Engine Series E550
- Torque 5.5 ft.-lbs. (Gross)
- HP 3.35 HP (Gross, Calculated)
- Disp. 140 cc.
- Speed 3200 RPM
- Start Recoil
- Shaft Vertical
- Shaft 7/8" dia. x 2<sup>7</sup>/<sub>16</sub>" w/ keyway, 2 woodruff key slots, tapped 3/8"-24
- Mount 3 holes on 8" B.C.
- Fuel Tank 0.8 qt.
- Size 13<sup>7</sup>/<sub>8</sub>" x 12<sup>1</sup>/<sub>4</sub>" x 9<sup>5</sup>/<sub>8</sub>"
- Dimensional Shpg. 52 lbs.



### 11.5 HP Briggs & Stratton Engine

ITEM 28-2007  
**\$549.95**

• New, BRIGGS & STRATTON XR Professional series engine. Engine feature overhead valves, cast iron sleeve liner, dual ball bearing supported crankshaft, muffler, governor, fuel valve and easy to use controls. EPA and California EXH/EVP SORE compliant.

**SPECIFICATIONS**

- Model 25N1370014F1
- Power 11.5 HP (Gross)
- Torque 16.5 ft.-lbs (Gross)
- Disp. 420 cc
- Speed 3600 RPM
- Start 12 Volt Electric Start and Recoil
- Charging System 10 Amps w/Regulator
- Fuel Tank 3.2 Qt.
- Shaft Horizontal
- Shaft 1" dia. x 3<sup>31</sup>/<sub>64</sub>" keyed, tapped 7/16"-20 UNF
- Accessory Mount Inner 4 bolt on 5" B.C. Outer 4 bolt on 6.5" B.C.
- Size 13<sup>3</sup>/<sub>8</sub>" X 19<sup>1</sup>/<sub>4</sub>" X 18"
- Shpg. 131 lbs.

Truck freight only.



### Honda Fuel Tank

ITEM 28-1663-A  
**\$14.95**

• New. Painted steel tank. Base mount with two threaded studs and two tapped holes. Large plated steel cap with chain retainer included.

• Original equipment on HONDA Model GX140, GX160 and GX200 engines.

**SPECIFICATIONS**

- Capacity 3.3 quarts
- Fuel Port 1/4" hose barb
- Filler Opening 1<sup>5</sup>/<sub>8</sub>"
- Size 9<sup>1</sup>/<sub>2</sub>" x 8<sup>1</sup>/<sub>4</sub>" x 5"
- Shpg. 5 lbs.



### 4-Bolt Engine To Pump Mounts



• New, SPEECO aluminum pump mounts for connecting gas engines to hydraulic pumps with 4F17 flange (2" sq. bolt pattern and 1.78" dia.)

ITEM 1-5580

**SPECIFICATIONS**

- Model S40081200
- Engine Mount 3<sup>5</sup>/<sub>8</sub>" bolt circle and 1<sup>5</sup>/<sub>8</sub>" pilot

- Engine HP Range 3-6.5 HP
- Total Length 4<sup>1</sup>/<sub>8</sub>"
- Size 4<sup>1</sup>/<sub>2</sub>" x 4" x 4"
- Shpg. 1 lb.

ITEM 1-5580-C

**SPECIFICATIONS**

- Model 578475
- Engine Mount 3<sup>5</sup>/<sub>8</sub>" bolt circle

**\$14.95**

ITEM 1-6107

**SPECIFICATIONS**

- Model 578475
- Engine Mount 3<sup>5</sup>/<sub>8</sub>" bolt circle

**\$14.95**

ITEM 1-5949

**SPECIFICATIONS**

- Model S40081800
- Engine Mount 5" bolt circle
- Engine HP Range 8-13 HP

**\$14.95**

**\$18.95**

- Pump Mount 4F17
- Total Length 5<sup>1</sup>/<sub>4</sub>"
- Size 5<sup>1</sup>/<sub>4</sub>" x 4<sup>5</sup>/<sub>8</sub>" x 4<sup>5</sup>/<sub>8</sub>"
- Shpg. 6 lbs.

### 30" Throttle Control Cable

ITEM 1-2331  
**\$4.95**

• New throttle-control cable with control handle assembly. Handle detent at full throttle position. Stop, slow-fast, and choke positions.

**SPECIFICATIONS**

- 0.055" dia. cable in 0.190" O.D. steel jacket
- 1<sup>1</sup>/<sub>2</sub>" total pull distance
- 30" max. cable length
- Overall handle size: 2<sup>1</sup>/<sub>2</sub>" x 9<sup>1</sup>/<sub>16</sub>" x 3"
- Two bolt mount on handle assembly on 1<sup>1</sup>/<sub>2</sub>" centers
- Shpg. 1 lb.



Find additional engines at  
[www.surpluscenter.com](http://www.surpluscenter.com)