



Hydraulic Quick Couplers and Tips

• Brand new SAFEWAY. Two piece couplers. ITEM 9-6314 and 928-C are two way sleeve type. Can be disconnected by pulling sleeve either direction. Ball check design prevents leakage when disconnected.

*** Safeway coupler adapters for common quick coupler brands on page 80.**

Thread	Complete Coupler							Extra Tip			
	ITEM	Flow	PSI	Model	Type	Shpg	Price	ITEM	Model	Shpg.	Price
1/4" NPT	9-1626	3	5000	S10-2	Poppet	1 lb.	\$38.55	9-1626-A	S101-2	1/2 lb.	\$14.05
1/4" NPT	9-6314	3	3000	S40-2	Ball	1 lb.	\$22.95	9-5924	S41-2	1/2 lb.	\$5.90
3/8" NPT	9-6347	6	3000	S20-3	Ball	1 lb.	\$25.70	9-6347-A	S41-3	1/2 lb.	\$7.60
1/2" NPT	928	12	3000	S20-4	Ball	1 1/2 lbs.	\$24.05	928-AA	S71-4	1/2 lb.	\$8.50
3/4" NPT	928-C	12	3000	S40-6	Ball	1 1/2 lbs.	\$36.20	928-D	S71-6	1 lb.	\$11.55

Flush Face ISO 16028 Quick Coupler & Accessories


• Brand new, HORIZON KSP1 Series flush face quick coupler. Includes body and tip. Used on skid-steer loaders, construction and agricultural equipment. Plated steel construction. Interchangeable with other brands that conform to ISO 16028. Temp. range -25° C to 125° C. Pressure: Working 3000 PSI max., Burst 12000 PSI



Complete Coupler						Body Only		Extra Tip		Dust Cap		Dust Plug	
ITEM	Body Size	Ports	GPM	Shpg.	Price	ITEM	Price	ITEM	Price	ITEM	Price	ITEM	Price
9-12275	1/4"	1/4" NPT	3.17	1 lb.	\$30.95	9-12275-B	\$21.55	9-12275-T	\$9.45	9-12275-C	\$2.10	9-12275-P	\$2.30
9-12276	3/8"	3/8" NPT	6.07	1.5 lbs.	\$36.95	9-12276-B	\$24.80	9-12276-T	\$11.65	9-12276-C	\$2.20	9-12276-P	\$2.35
9-8288	1/2"	1/2" NPT	11.9	3 lbs.	\$43.95	9-8288-B	\$29.65	9-8288-T	\$14.25	9-8288-C	\$2.35	9-8288-P	\$2.45
9-8313	3/4"	3/4" NPT	26.4	4 lbs.	\$91.05	9-8313-B	\$58.75	9-8313-T	\$32.30	9-8313-C	\$2.75	9-8313-P	\$2.70
9-8720	1"	1" NPT	49.9	6 lbs.	\$130.95	9-8720-B	\$84.80	9-8720-T	\$45.80	9-8720-C	\$2.90	9-8720-P	\$2.95

Thread-To-Connect Couplings & Accessories

• Brand new, HORIZON KST Series thread-to-connect coupling. Includes body and tip. Thread-to-connect design can be connected under pressure, with little or no spillage. Interchangeable half-for-half with the following: Parker 6100, Perfecting W, Faster FB, Safeway S51, Snaptime 78, Tomco A51 And Aeroquip 5100. Pressure: working 3000 PSI max., burst 9000 PSI.



Complete Coupler						Body Only		Extra Tip		Dust Cap		Dust Plug	
ITEM	Body Size	Ports	GPM	Shpg.	Price	ITEM	Price	ITEM	Price	ITEM	Price	ITEM	Price
9-12277	3/4"	3/4" NPT	16.3	3 lbs.	\$72.95	9-12277-B	\$36.40	9-12277-T	\$36.40	9-12277-C	\$10.10	9-12277-P	\$9.90
9-8314	1"	1" NPT	42.2	5 lbs.	\$91.95	9-8314-B	\$47.65	9-8314-T	\$43.60	9-8314-C	\$17.00	9-8314-P	\$15.55
9-12278	1 1/4"	1 1/4" NPT	58.1	5 lbs.	\$127.95	9-12278-B	\$65.65	9-12278-T	\$61.60	9-12278-C	\$16.60	9-12278-P	\$15.85
9-12279	1 1/2"	1 1/2" NPT	79	7 lbs.	\$179.95	9-12279-B	\$84.35	9-12279-T	\$95.10	9-12279-C	\$41.95	9-12279-P	\$18.20

Hydraulic Hose Sleeve

• Brand new, Protec Nylon Hose Sleeve. Self-renewing, abrasion-resistant fabric sleeve meets ISO 6945 abrasion standards and has MSHA IC 171/1 flame resistance approval. Protects hydraulic hoses and provide limited burst and containment protection. Black Nylon Sleeve is easily installed over hose securing the ends with nylon cable ties or band-clamps. Ends should be heat sealed to prevent fraying. Temperature Range -40° to 194°F Available for hydraulic hose sizes 1/4" to 2". Sold by the foot or 300 ft. rolls.



SAE 12 Flush Face Quick Coupler Set

ITEM 9-16294
\$24.95



• New, Flush face quick coupler. Includes body and tip. Flush face design is easily cleaned, minimizes oil spillage during disconnection and air inclusion during connection. One-handed, push-to-connect convenience. Commonly used on many models of skid-steer loaders and construction and agricultural equipment. Plated steel construction. Interchangeable with Parker FEM, Faster FF, Holmburg Series A and other brands of quick couplings that conform to International Standard ISO 16028 dimensional requirements.

SPECIFICATIONS

- ISO Standard 16028
- ISO Body Size
- Ports SAE 12
- Tip Diameter 0.96"
- Pressure, Working 3000 PSI Max
- Burst, Pressure 12000 PSI
- Flow 11.9 GPM Max
- Temperature Range -25° C to 125° C
- Oil Spillage (at disconnect) 0.07 cc
- Coupler O.D. 1.72"
- Coupled Length 6 3/4"
- Shpg. 3 lbs.

By the Foot					300 Ft. Roll		
Item Number	I.D.	Hose Size	Shpg per ft.	Price per Ft.	Item Number	Shpg.	Price
9-12496-4	0.90"	1/4"	1/10	\$1.10	9-12496-4-300R	10 lbs.	\$250.00
9-12496-6	1.00"	3/8"	1/10	\$1.20	9-12496-6-300R	10 lbs.	\$265.00
9-12496-8	1.25"	1/2"	1/8	\$1.25	9-12496-8-300R	12 lbs.	\$295.00
9-12496-12	1.53"	3/4"	1/8	\$1.50	9-12496-12-300R	19 lbs.	\$355.00
9-12496-16	1.75"	1"	1/8	\$1.65	9-12496-16-300R	18 lbs.	\$385.00
9-12496-20	2.07"	1 1/4"	1/4	\$1.85	9-12496-20-300R	21 lbs.	\$430.00
9-12496-24	2.38"	1 1/2"	1/4	\$2.25	9-12496-24-300R	24 lbs.	\$535.00
9-12496-32	2.96"	2"	1/4	\$2.70	9-12496-32-300R	31 lbs.	\$760.00