



## Diaphragm Pumps

• New, PENTAIR HYPRO medium pressure diaphragm pumps. Pump design offers compatability with many chemicals, smooth mechanical operation, longer operational pump life and consistent performance. The 9915 series diaphragm pumps have additional diaphragms to produce smoother flow with little to no pressure loss, producing more consistent and efficient spray coverage. Hardened black oxide aluminum heads, manifold, and case. Duramax diaphragm, crown-shaped pistons, and double piston rings. 316 Stainless steel spherical profiled valve poppet.

### Two Diaphragm

### Three Diaphragm

### Three Diaphragm

**6.3 GPM,  
290 PSI**

**ITEM 2-1492  
\$179.95**

**SPECIFICATIONS**

- Model Number 9915-DP252
- Number of Diaphragms 2
- Max. Flow 6.3 GPM
- Max. Pressure 290 PSI
- Max. RPM 650
- Required HP 1.4



- Max. Fluid Temperature 140°F/60°C
- Inlet Port 1 1/2" NPT
- Outlet Port 1/2" NPT
- Input Shaft 3/4" Solid Shaft
- Size 9.4" x 9.3" x 8.6"
- Shpg 19 lbs.

**ITEM 2-1493**

- Same as ITEM 2-1492 Except:

**SPECIFICATIONS**

- Model Number 9915-DP252GRGI58
- Number of Diaphragms 2
- Max. RPM 3450
- Input Shaft Pump Gearbox

- 5/8" Hollow Shaft
- Gearbox Mount Four, 0.347" holes on 3/8" bolt circle
- Size 12" x 9.4" x 8.8"
- Shpg 21 lbs.

**\$199.95**

**7.1 GPM,  
290 PSI**

**ITEM 2-1494  
\$149.95**

**SPECIFICATIONS**

- Model Number 9915-DP302
- Number of Diaphragms 2
- Max. Flow 7.1 GPM
- Max. Pressure 290 PSI
- Max. RPM 650
- Required HP 1.6



- Max. Fluid Temperature 140°F/60°C
- Inlet Port 1 1/2" NPT
- Outlet Port 1/2" NPT
- Input Shaft Flange
- Size 8.1" x 9.4" x 8.6"
- Shpg 17 lbs.

**ITEM 2-1495**

- Same as ITEM 2-1494 Except:

**SPECIFICATIONS**

- Model Number 9915-DP302AP-A

- Input Shaft 3/4" Solid Shaft
- Shpg 20 lbs.

**\$159.95**

**ITEM 2-1496**

- Same as ITEM 2-1494 above with a 6:1 gear reducer for attaching to a 5 HP gas engine with 3/4" keyed shaft

**SPECIFICATIONS**

- Model Number 9915-DP302GRGI
- Max. RPM 3450
- Input Shaft Pump Gearbox

- Gearbox Mount Four, 0.347" holes on 3 5/8" bolt circle
- Size 15" x 9.4" x 10.4"
- Shpg 22 lbs.

**\$199.95**

**9.8 GPM,  
580 PSI**

**ITEM 2-1487  
\$199.95**

**SPECIFICATIONS**

- Model Number 9915-D403
- Number of Diaphragms 3
- Max. Flow 9.8 GPM
- Max. Pressure 580 PSI
- Max. RPM 550
- Required HP 3.9



- Max. Fluid Temperature 140°F/60°C
- Inlet Port 1 1/2" NPT
- Outlet Port 1/2" NPT
- Input Shaft Flange
- Size 10" x 8.8" x 7.6"
- Shpg 23 lbs.

**13.5 GPM,  
580 PSI**

**ITEM 2-1488  
\$229.95**

**SPECIFICATIONS**

- Model Number 9915-D503
- Number of Diaphragms 3
- Max. Flow 13.5 GPM
- Max. Pressure 580 PSI
- Max. RPM 550
- Required HP 5.4



- Max. Fluid Temperature 140°F/60°C
- Inlet Port 1 3/8" NPT
- Outlet Port 3/4" NPT
- Input Shaft Flange
- Size 9.7" x 12" x 10.5"
- Shpg 38 lbs.

**ITEM 2-1489**

- Same as ITEM 2-1488 Except:

**SPECIFICATIONS**

- Model Number 9915-DP503AP-A
- Inlet Port 1 3/8" NPT

- Outlet Port 3/4" NPT
- Input Shaft 1" Solid Shaft
- Size 9.7" x 12" x 10.5"
- Shpg 40 lbs.

**\$349.95**

**ITEM 2-1490**

- Same as ITEM 2-1488 above with a 6:1 gear reducer for attaching to a 8-13 HP gas engine with 1" keyed shaft

**SPECIFICATIONS**

- Model Number 9915-D503GRGI
- Max. RPM 3450
- Required HP 5.4
- Max. Fluid Temperature 140°F/60°C

- Input Shaft Pump Gearbox Controller 1" Hollow Shaft
- Gearbox Mount Twelve, 0.424" holes on 6 1/2" bolt circle
- Size 18.8" x 13.2" x 12.7"
- Shpg 55 lbs.

**\$399.95**

**27.9 GPM,  
725 PSI**

**ITEM 2-1481  
\$499.95**

**SPECIFICATIONS**

- Model Number 9915-DP1063
- Number of Diaphragms 3
- Max. Flow 27.9 GPM
- Max. Pressure 725 PSI
- Max. RPM 550
- Required HP 13.9



- Max. Fluid Temperature 140°F/60°C
- Inlet Port 1 1/2" NPT
- Outlet Port 3/4" NPT
- Input Shaft 1 3/8" 6-Spline shaft
- Size 15.2" x 15.2" x 14.6"
- Shpg 118 lbs.

Truck freight only.

**ITEM 2-1482**

- Same as ITEM 2-1481 Except:

**SPECIFICATIONS**

- Model Number 9915-DP1063AP-A

- Input Shaft 1 3/8" 6-Spline shaft and 1" keyed shaft

**\$529.95**

**8.1 GPM,  
580 PSI**

**ITEM 2-1484  
\$159.95**

**SPECIFICATIONS**

- Model Number 9915-D303
- Number of Diaphragms 3
- Max. Flow 8.1 GPM
- Max. Pressure 580 PSI
- Max. RPM 650
- Required HP 3.2



- Max. Fluid Temperature 140°F/60°C
- Inlet Port 1 1/2" NPT
- Outlet Port 1/2" NPT
- Input Shaft Flange
- Size 7.6" x 8.8" x 10"
- Shpg 24 lbs.

**ITEM 2-1485**

- Same as ITEM 2-1484 Except:

**SPECIFICATIONS**

- Model Number 9915-D303AP-A

- Input Shaft 3/4" Solid Shaft
- Size 10" x 8.8" x 7.6"
- Shpg 23 lbs.

**\$179.95**

**ITEM 2-1486**

- Same as ITEM 2-1494 above with a 6:1 gear reducer for attaching to a 5 HP gas engine with 3/4" keyed shaft

**SPECIFICATIONS**

- Model Number 9915-D303GRGI
- Max. RPM 3450
- Input Shaft Pump Gearbox

- Gearbox Mount Four, 0.353" holes on 3/8" bolt circle
- Size 16" x 10.9" x 10.8"
- Shpg 32 lbs.

**\$279.95**

### Four Diaphragm

**38.8 GPM,  
725 PSI**

**ITEM 2-1483  
\$699.95**

**SPECIFICATIONS**

- Model Number 9915-DP1054
- Number of Diaphragms 4
- Max. Flow 38.8 GPM
- Max. Pressure 725 PSI
- Max. RPM 550
- Required HP 19.3



- Max. Fluid Temperature 140°F/60°C
- Inlet Port 1 1/2" NPT
- Outlet Port 3/4" NPT
- Input Shaft 1 3/8" 6-Spline shaft
- Size 15.2" x 15.8" x 16.9"
- Shpg 131 lbs.

Truck freight only.

**10 GPM Double  
Diaphragm  
Pump  
\$49.95**

**ITEM 2-1582**

- New. Shurflo model 477-400-02 air-operated double diaphragm pump. Dual diaphragm design and pneumatic spool valve. Contains specialized elastomers, allowing compatibility with the most caustic or acidic fluids. Rubber vibration damper mounting feet. Can run dry without damage.

**SPECIFICATIONS**

- Pressure 40-100 PSI
- Max Flow 10 GPM @ 100 PSI
- Liquid Ports 1/2" & 3/4" hose barb fittings included

- Air Port 1/4" barb
- Mount Four bolt on 2 1/4" x 4 5/8" centers
- Size 7" x 4 1/8" x 7 3/8"
- Shpg 4.6 lbs.

**Performance Charts and  
Accessories can be  
found online at  
www.surpluscenter.com**