RV/Mobile Home Adapter

ITEM 11-3225

 New, Eletricord (Leviton) model C-1427-009-BL.

Male end plugs into 30 amp 125V outlet and converts to standard 15 amp female.

SPECIFICATIONS

- Conductor Gauge 12
- Conductor Count 3
- Length 9"
- Jacketing Type STW
- End 1 30 Amp 125 volt male
- End 2 15 Amp 125 volt female
- Shpg. 1 lbs.

16/3 Power Cord ITEM 11-3550 \$18.99

 New, three conductor power cord. SJTW smooth jacket. Weather resistant for outdoor use.

SPECIFICATIONS

- Wire #16 AWG, 3 conductors
- End 1 NEMA three-prong connector, Female
- End 2 NEMA three-prong connector, Male
- Jacket Type SJTW, Orange
- Length 50'
- · Shpg 3 lbs.







\$24.60

\$24.60

\$24.60

11-3512-A 11-3512-B 11-3512-C 3-Button Control Station

240 VAC max.

• Brand new, RELAY & CONTROL. Steel housing with 3 momentary push buttons. NEMA 1 enclosure. Knockouts for 1" conduit on top/bottom. • Contact Rating 5 amps @

SPECIFICATIONS FOR ALL

• Shpg. 1 lb. • Size 23/8" x 113/16" x 55/16"

ITEM 11-3512-A Model PBS-601

Top Button Green OPEN Middle Button Green DOWN Lower Button Red STOP

ITEM 11-3512-B

Model PBS-602 Top Button Green UP Middle Button Green DOWN Lower Button Red STOP

ITEM 11-3512-C Model PBS-603

Top Button Green FORWARD Middle Button Green REVERSE Lower Button Red STOP

Two Button Start Stop Station

ITEM 11-3659

 Brand new, RELAY & CONTROL model SS-1. Steel housing with 2 momentary push buttons. Use with magnetic starters. NEMA 1 enclosure. Knockouts for 1"

SPECIFICATIONS

- 240 VAC max.
- Top Button Green START
- Contact Rating 5 amps @ Lower Button Red STOP • Size 23/8" x 11/2" x 4"

• Shpg. 1 lb.

18/3 Power Cord

ITEM 11-3734



• New. WELL SHIN, 10', Three-conductor UL listed power cord. SVT outdoor jacket.

SPECIFICATIONS

- Wire #18 AWG. 3 conductors
- Plug WS-001, 3-prong male
 Length 10'
- Rating 10 Amp, 250V
- Connector End WS-002, 3-pin female
- Jacket Type SVT
- Shpg 0.55 lb.

14/3 Male to Dual Female Power Cord Adapter ITEM 11-3457 4

 New, E-ZEELOCK. Converts extension cords from single to dual outlets. Unique cord lock to prevent cords pulling away from all 3 connectors.

SPECIFICATIONS

- Length 2 Ft.
- Shpg. 11/2 lbs.

18/2 Power ≥ Cords

 New, two conductor power cord. SPT jacket. Use for lamps, clocks, etc.

- **SPECIFICATIONS** Two prong male plug
- 18 gauge conductors
- Shpg. 1/4 lb.

ITEM 11-3369-A ITEM 11-3369-B ITEM 11-3369-C

White, 9 ft. long Brown, 12 ft. long Brown, 9 ft. long

18/3 **Power** Cord

• New, 3 conductor power cord. SJT smooth jacket. White lead has another lead piggybacking off first 1/4" spade connector.

ITEM 11-3401 **SPECIFICATIONS**

- Conductor Gauge 18
- Conductor Count 3
- Length Black 6½", White 11" to 181/2", Green 9"
- Jacketing Type SJT
- End 1 3 prong male
- End 2 Black lead 3/16 spade connector, white leads have 1/4" spade connector. Green lead has 1/4" ring connector.
- Shpg. 11/2 lbs.

6' HDMI Cable

ITEM 11-3463 \$1.99



- **SPECIFICATIONS** Length 6'
- End 1 HDMI A Male



- End 2 HDMI A Male
- Shpg. 1/4 lb.

18/3 16" Power Cord

ITEM 11-3609 \$2.95



 New, three conductor power cord. SJT type jacket.


SPECIFICATIONS

- Conductor Gauge 18
- Conductor Count 3
- Length 16 in.
- Jacketing Type SJT End 1 Stripped leads
- End 2 IEC C14
- Shpq. 1/4 lb.

8' 16/3 IEC Power Cord



ITEM 11-3516



Jacketing Type SJT

• End 1 NEMA 5-15P

SPECIFICATIONS

- Conductor Gauge 16
- Conductor Count 3
- Length 96"
- Max Temperature 105°C Shpg. 1 lb.
- End 2 IEC 60320/C13

4' Power Cord

ITEM 11-3398-4 **\$8.95**



SPECIFICATIONS

- Conductor 3 Gauge 8
- · Length 4 ft.
- Jacketing Type SRDT
- Conductor 1&2 Gauge 6
 End 1 NEMA 10-50P plug.
 - End 21/4" ID brass ring connectors
 - . Shpg. 2 lbs.

12 VDC Battery_ **Isolator Switch**

ITEM 11-3741

 New, battery isolator switch. Circuit closes when key is locked in place. Removable twist-lock plastic key.

SPECIFICATIONS

- Model Number 1636000033

isolator

- Contacts SPST • Contact Rating 100 Amps • Face Size 2.29" dia.
- @ 12 VDC
- Switch Positions Two
- Mounting Two ¼" holes Switch Type Rotary

 Termination Two M8-1.25 studs

Action Maintained

 Mounting Depth 1½" • Shpg 0.25 lbs.

Momentary 2 Button Pendant Switch

ITEM 11-3709 \$39.05

 Brand new. Handheld two button momentary pendant switch. Normally open contacts rated 5 Amps at 250 volt AC. For power-up, gravity down powerpacks (single acting). Weatherproof plastic housing and 2 magnets on the back of the pendant. Ideal for remote control of winches, hoists, hydraulic power units, etc.

- **SPECIFICATIONS** Pushbuttons (2) Normally
- Cord 18/3, 15 feet long Size 2" x 25%" x 6½"
- open
- Contact Rating 5 Amp. 250 Volts AC
- terminals · Shpg. 2.5 lbs.

12 Volt DC Wireless 😞 Remote



ITEM 11-3737

 Brand new, DALTON G3-H10 wireless remote 3 or 4 wire control. Potted and water resistant. "Learning" transmitter easily syncs to receiver. Antenna and remote included. 10 amp in-line fuse on battery input wire.

- Brand Dalton
- Model Number G3-H10
- Part Number PSN-208
- Voltage 12 Volt DC
- Range 100' max.
- · Switch On/Off
- Mount Four 0.2" holes on 43/8" x 27/8" centers
- Size 57/8" x 33/8" x 1"









SPECIFICATIONS

- Shpg 0.8 lbs.