

ÜŠÄ

 Brand new SPX STONE. Hydraulic power packs for operating hydraulic cylinders. Steel reservoir tank with inlet strainer, magnet and filtered filler/breather. Built in check valve and adjustable relief valve. See chart for details about control valves, tank size and pressure ratings.

### SPECIFICATIONS (all models)

. Flow rate 1.3 GPM at max PSI

• 12 VDC motor

· Needle bearings

· Intermittent duty



			Relief Valve	Tank Size				
ITEM	Valve Type	Ports	Factory Set	Cap.	Useable	Size	Shpg.	Price
9-1478	Single Acting Lever Operated	3⁄8″ NPT	2500 PSI	3 qt.	2.3 qt.	21" x 9" x 7"	38 lbs.	<i>\$552.30</i>
9-1479	Single Acting 12 Volt DC w/handheld remote	SAE 6	2500 PSI	3 qt.	2.3 qt.	21" x 8" x 6"	39 lbs.	<i>\$587.15</i>
9-7412	Single Acting 12 Volt DC w/handheld remote	SAE 6	2500 PSI	2.5 gal.	1.6 gal.	25" x 8 <sup>7</sup> / <sub>16</sub> " x 8"	40 lbs.	<i>\$626.60</i>
9-1480	Double Acting 12 Volt DC (does not include remote)	SAE 6	2500 PSI	3 qt.	2.3 qt.	21" x 8" x 7"	40 lbs.	<i>\$615.55</i>
9-7413	Double Acting 12 Volt DC (does not include remote)	SAE 6	2500 PSI	2.5 gal.	1.6 gal.	25" x 8" x 7"	41 lbs.	<i>\$635.60</i>
9-7411	None (use with external valve)	SAE 6	2500 PSI	2.5 gal.	1.6 gal.	25" x 7" x 8"	40 lbs.	<i>\$556.70</i>

## 2 HP 115/230 VAC Hydraulic Power Packs A

• Brand new, SPX hydraulic power packs. All models include motor, gear pump and steel reservoir tank with filtered filler/breather. Horizontal mount. Select from a variety of valve options in chart below.

### SPECIFICATIONS (all models)

- 2 HP TEFC motor • 115/230 VAC, 1 Ph.
- 3450 RPM • 22/11 Amps
- · Continuous duty

Relief Valve

• Port(s) SAE 6





**Price** \$762.60 \$824.80

ITEM Pressure/Flow **Factory Set** Valve Type Useable Size Cap. Shpg. 9-7136 2.5 GPM @ 1000 PSI 1300 PSI None (use with external valve) 39" x 9" x 9% 55 lbs. 4 gal. 3.03 gal. 9-7137 1.3 GPM @ 2000 PSI 2500 PSI Single Acting release, 115 Volt AC 2.5 gal. 1.6 gal. 30" x 9" x 9% 52 lbs. 9-7138 2.5 gal. \$970.65 1.3 GPM @ 2000 PSI 2500 PSI Double Acting 4 way, 115 Volt AC 1.6 gal. 30" x 9" x 9% 53 lbs. 9-7135 1.3 GPM @ 2000 PSI 2500 PSI None (use with external valve) 2.5 gal. 1.6 gal. 30" x 9" x 93%" 51 lbs. \$763.55

## 10 ft. Hand Held Remote Controls A for DC Powerpacks



### ITEM 9-1441-S

\$64.75

• For single acting, 3 wire style

Shpg. 4 lbs. 9-1479, 9-7412 \$184.20

ITEM 9-1441-D • For double acting, 3 wire style

Shpg. 4 lbs.

9-1480, 9-7413

### ITEM 9-8845

• Brand new two pushbutton (4 wire) hand held control made for use with double acting hydraulic power packs with two coil solenoid valve. Magnets on back for mounting to steel surfaces. 10 foot power cord. Shpg. 4 lbs.

# 230 VAC **Hvdraulic** Powerpack A ITEM 9-7139 \$750.25

 Brand new SPX hydraulic powerpack ideal for use in automobile hoists, lifts and other applications. Cartridge style check valve for load-holding. Momentary "ON" pushbutton switch for raising with a manual lever for lowering. Vertical mount.

### **SPECIFICATIONS**

- 2 HP TENV motor
- 208-230 VAC, 1 Ph.
- 15-18 Amps
- Int. duty
- 2.25 GPM @ 2,000 PSI max output
- 2300 PSI maximum
- 2300 PSI fixed relief valve setting
- · 4 gallon plastic reservoir (3 gallon usable)
- SAE 6 port
- Mount vertical
- Size 10½" x 7" x 31½"
- Shpg. 60 lbs.

## 12 VDC Snow Plow Powerpack A



### ITEM 9-8411

 Brand new, SPX Model DC-80SPC. Power pack with built-in 12 volt DC solenoid valves for operating snow plows. Provides power up, hold and gravity down for single acting cylinder blade lift plus left and right control for two single acting cylinders or one double acting cylinder for blade angle. Horizontal mount.

### **SPECIFICATIONS**

- Voltage 12 VDC
- · Amperage 300 amps

able set @ 2000 PSÍ

- 1500 PSI • Reservoir 1.5 qt. useable

• Cross-over Relief Valve

- Ports Cylinder SAE 6
- Duty Intermittent
- Flow 1.7 GPM at 1750 PSI
  Mnt 2 bolt base on 3¼" c/c Orientation Horizontal Pressure 3500 PSI max.
- Size 14¾" x 81/8" x 71/4" . Main Relief Valve Adjust-• Shpg. 36 lbs.