


BUCHER WUXI Hydraulics Two Stage Hydraulic Pumps

• Brand new BUCHER WUXI Hydraulics, two stage HI/LO pressure hydraulic gear pumps. Ideal for applications such as log splitters, presses and other equipment where rapid movement of the cylinder at low pressure is required prior to automatically switching to the high pressure mode to meet load requirements



SPECIFICATIONS FOR ALL


- Pump type gear
- Rotation CW
- Press. 3000 PSI max.
- Speed 3600 RPM max.
- Unloading pressure 650 PSI
- Mount 4 bolt USA 4F17
- Rqd. filtration 25 micron
- Shaft 1/2" dia. x 1 1/2" keyed
- Cast Iron Front and Aluminum Body

ITEM	Flow (GPM)		Engine Power Required	Inlet	Outlet	Size	Shpg.	Price
	LO Stage	HI Stage						
9-12373-11	11	3.2	5 HP	1" Hosebarb	1/2" NPT	5" x 5 1/8" x 3 3/8"	10 lbs.	\$149.95
9-12373-13	13	3.2	6.5 HP	1" Hosebarb	1/2" NPT	5 3/8" x 5 1/8" x 3 3/8"	11 lbs.	\$154.20
9-12373-16	16	3.5	8 HP	1" Hosebarb	1/2" NPT	5 3/4" x 5 1/8" x 3 3/8"	12 lbs.	\$162.75

MTE 2 Stage Hydraulic Pumps



• Brand new, MTE HYDRAULICS two stage HI/LO pressure hydraulic gear pump. Ideal for applications such as log splitters, presses and other equipment where rapid movement of the cylinder at low pressure is required prior to automatically switching to the high pressure mode. The change from LO to HI pressure is automatic with the LO stage pressure preset at 700 PSI. Made in USA.



2 Bolt SAE A

SPECIFICATIONS

- Rotation CW
- Pump type gear
- Speed 3600 RPM max.
- Pressure 3000 PSI max.
- Rqd. filtration 25 micron
- Shaft 1 1/2" long keyed

4 Bolt USA 4F17


ITEM	Flow (GPM)		Engine Power Required	Unloading Pressure	Inlet	Outlet	Shaft Dia.	Mount	Size	Shpg.	Price
	LO Stage	HI Stage									
9-7972-7	7	1.8	4 HP	500 PSI	3/4" NPT	1/2" NPT	1/2"	4 bolt 4F17	5 1/16" x 3" x 3 1/16"	10 lbs.	\$195.80
9-7972-11	11	1.8	5 HP	700 PSI	1" Hosebarb	1/2" NPT	1/2"	4 bolt 4F17	6" x 4" x 3 1/16"	10 lbs.	\$196.35
9-7972-13	13	3	6.5 HP	500 PSI	1" Hosebarb	1/2" NPT	1/2"	4 bolt 4F17	6 1/4" x 4" x 3 1/16"	12 lbs.	\$197.05
9-7972-16	16	3	8 HP	500 PSI	1" Hosebarb	1/2" NPT	1/2"	4 bolt 4F17	6 9/16" x 4" x 3 1/16"	12 lbs.	\$197.65
9-7973	22	6.3	12 HP	500 PSI	1 1/4" Hosebarb	3/4" NPT	5/8"	2 bolt SAE A	6 1/4" x 6 1/4" x 4 5/8"	22 lbs.	\$424.90



FLUID COMPONENTS, INC.

Dynamic Two Stage Hydraulic Pumps

• Brand new DYNAMIC, two stage HI/LO pressure hydraulic gear pumps. Ideal for applications such as log splitters, presses and other equipment where rapid movement of the cylinder at low pressure is required prior to automatically switching to the high pressure mode to meet load requirements



2 Bolt SAE A

SPECIFICATIONS FOR ALL

- Pump type gear
- Rotation CW
- Press. 3000 PSI max.
- Speed 3600 RPM max.
- Unloading pressure 650 PSI
- Overhung shaft load up to 90 lbs.
- Rqd. filtration 25 micron
- Shaft 1/2" dia. x 1 1/2" keyed
- Mount 4 bolt USA 4F17

4 Bolt USA 4F17

ITEM	Flow (GPM)		Engine Power Required	Inlet	Outlet	Shaft Dia.	Mount	Size	Shpg.	Price
	LO Stage	HI Stage								
9-7503-8	8	2	5 HP	1" Hosebarb	1/2" NPT	1/2"	4 bolt 4F17	4 3/4" x 5 1/8" x 3 3/8"	10 lbs.	\$187.40
9-7503-11	11	3.4	5 HP	1" Hosebarb	1/2" NPT	1/2"	4 bolt 4F17	5 1/4" x 5 1/8" x 3 3/8"	10 lbs.	\$194.25
9-7503-13	13	3.4	6.5 HP	1" Hosebarb	1/2" NPT	1/2"	4 bolt 4F17	5 9/16" x 5 1/8" x 3 3/8"	11 lbs.	\$202.00
9-7503-16	16	4	8 HP	1" Hosebarb	1/2" NPT	1/2"	4 bolt 4F17	6" x 5 1/8" x 3 3/8"	12 lbs.	\$222.10
9-7970	22	7	12 HP	1" NPT	3/4" NPT	5/8"	2 bolt SAE A	6 9/16" x 6 1/4" x 4 1/16"	22 lbs.	\$322.85
9-7971	28	7	16 HP	1" NPT	3/4" NPT	5/8"	2 bolt SAE A	6 9/16" x 6 1/4" x 4 1/16"	23 lbs.	\$352.50

• New, two stage HI/LO pressure hydraulic gear pump. Cast iron front with aluminum body. Ideal for applications such as log splitters, presses and other equipment where rapid movement of the cylinder at low pressure is required prior to automatically switching to the high pressure mode to meet load requirements.

SPECIFICATIONS FOR ALL

- Pump type gear
- Rotation CW
- Speed 3600 RPM max.
- Shaft 1/2" dia. x 1 1/2" keyed
- Rated 3000 PSI
- Mount 4 bolt USAF17



New BUCHER WUXI

ITEM	Flow (GPM)		Engine Power Required	Unloading Pressure	Inlet	Outlet	Size	Shpg.	Price
	LO Stage	HI Stage							
9-12876	14.1	1.7	6.5 HP	400-900 PSI	1" Hosebarb	1/2" NPT	5 1/4" x 7" x 3 3/8"	11 lbs.	\$89.95
9-12877	18.5	2.8	9.5 HP	400-900 PSI	1" Hosebarb	1/2" NPT	5 7/8" x 7" x 3 3/8"	13 lbs.	\$99.95