

2.5" x 16" x 1.5"



ITEM 9-16372

\$159.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.5" x 16"
- Pressure 3000 PSI max.
- Rod Dia. 1.5"
- Ports SAE 6
- Retracted Length 26"
- Rod End: Thru-Hole
- Width 1"
- Base End: Tang
- Width 1.511"
- Pin Holes 1"
- Shpg. 32 lbs.

2.5" x 16.625" x 1.5"



ITEM 9-16499

\$159.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.5" x 16.625"
- Pressure 3000 PSI max.
- Rod Dia. 1.5"
- Ports JIC 6
- Retracted Length 25.25"
- Rod End: Tang
- Width 2.255"
- Base End: Thru-Hole
- Width 2.75"
- Pin Holes 1.25"
- Shpg. 36 lbs.

2.5" x 20" x 1.25"



ITEM 9-16157

\$99.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.5" x 20"
- Pressure 2500 PSI max.
- Rod Dia. 1.25"
- Rod Thickness 1.25"
- Ports 1/4" NPT
- Retracted Length 30.5"
- Clevis Ends
- Pin Holes 1"
- Shpg. 29 lbs.

2.5" x 20" x 1.25"



ITEM 9-20757

\$119.95

SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 2.5" x 20"
- Pressure 3000 PSI max.
- Rod Dia. 1.25"
- Ports SAE 6
- Retracted Length 30.25"
- Clevis Ends
- Pin Holes 1"
- Shpg. 32 lbs.

2.5" x 24" x 1.5"



ITEM 9-7696

\$159.99

SPECIFICATIONS

- New, Double Acting
- Bore/Stroke 2 1/2" x 24"
- Pressure 3000 PSI
- Rod dia. 1 1/2"
- Ports SAE 8
- Retracted Length 50 1/4"
- Rod crosstube 2 3/4" wide pin hole 1 1/2"
- Base tang 1 1/2" wide pin hole 2 3/8"
- Shpg. 62 lbs.

2.5" x 30" x 1.5"



ITEM 9-16627

\$179.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.5" x 30"
- Pressure 3000 PSI max.
- Rod Dia. 1.5"
- Ports SAE 8
- Retracted Length 39"
- Rod End: Tang
- Width 2.875"
- Base End: Crosstube
- Width 2.875"
- Pin Holes 1.5"
- Shpg. 46 lbs.

2.75" x 15.75" x 1.75"



ITEM 9-9227

\$119.95

SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore/Stroke 2 3/4" x 15 3/4"
- Pressure 3000 PSI
- Rod dia. 1 1/4"
- Ports SAE 4
- Retracted lgth. 40 7/8"
- Rod ends thru-hole, both 27/32" wide
- Pin hole 3/4"
- Cylinder body mount 4 bolt 19 1/16" x 3 1/8" center 3/16"-16 tapped mtg. holes
- Shpg. 45 lbs.

2.75" x 20" x 1.5"



ITEM 9-16578

\$129.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.75" x 20"
- Pressure 2500 PSI max.
- Rod Dia. 1.5"
- Ports SAE 6
- Retracted Length 28"
- Cross-Tube Ends
- Rod End: Width 3"
- Base End: Width 3"
- Pin Holes 0.75"
- Shpg. 40 lbs.

2.75" x 21.25" x 1.5"



ITEM 9-16630

\$149.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.75" x 21.25"
- Pressure 3000 PSI max.
- Rod Dia. 1.5"
- Ports SAE 8
- Retracted Length 28.75"
- Rod End: Tang
- Width 2"
- Base End: Crosstube
- Width 3.5"
- Pin Holes 1.5"
- Shpg. 40 lbs.

2.75" x 30" x 1.5"



ITEM 9-16631

\$199.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.75" x 30"
- Pressure 3000 PSI max.
- Rod Dia. 1.5"
- Ports SAE 8
- Retracted Length 39"
- Rod End: Tang
- Width 2.875"
- Base End: Crosstube
- Width 3.25"
- Pin Holes 1.5"
- Shpg. 50 lbs.

Double Acting Hydraulic Trunnion Cylinder

- Double acting with trunnion mount on gland end. Two SUN counterbalance valves installed on rod end manifold block.

2.75" x 186" x 2"



ITEM 9-5584

\$599.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2 3/4" x 186"
- Pressure 2500 PSI
- Rod Dia. 2"
- Ports SAE 8
- Base to pin retracted lgth. (pin next to gland) 211"
- Counterbalance valves set at 1000 and 1200 PS
- Trunnion to crosstube pin retracted lgth. 6 1/8" (pin next to gland)
- Base end plain w/bracket
- Rod end steel manifold block
- Block dimensions 8 3/4" x 8" x 3 1/2"
- Two pin holes 1 1/4" Pin centers 3"
- Trunnion end rectangle male pins
- Outside pin width 10 1/2"
- Pin size 1 7/8" x 2 1/4"
- Pin length 1 1/4"
- Overall lgth. 215 1/2"
- Actual Weight 290 lbs.
- Shpg. 400 lbs.

Truck freight only

2.76" x 16.34" x 1.57"



ITEM 9-16032

\$79.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.76"(70mm) x 16.34"(415mm)
- Pressure 3000 PSI
- Rod Dia. 1.57 (40mm)
- Ports M20 x 3
- Retracted Length 28.25"
- Rod End: Threaded
- Thread Size-Pitch M36 x 3
- Thread Length 3"
- Base End: Tang
- Width 1.57"
- Pin Hole 1.77"(45mm)
- Shpg. 43 lbs.

3" x 2.5" x 1.5"



ITEM 9-16393

\$129.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 2.5"
- Pressure 3000 PSI max.
- Rod Dia. 1.5"
- Ports SAE 8
- Retracted Length 12.75"
- Clevis Ends
- Pin Holes 1"
- Shpg. 21 lbs.

3" x 6.125" x 1.5"



ITEM 9-2191

\$76.50

SPECIFICATIONS

- Unused, old inventory
- Double acting
- Bore/stroke 3" x 6 1/8"
- Retracted lgth. 21 3/4"
- 1 3/8" self aligning
- Swivel eye both ends
- Pressure 2500 PSI
- Rod end width 2"
- Rod diam. 1 1/2"
- Base end width 2 1/2"
- Ports SAE 8
- Shpg. 45 lbs.

**Bore** - Inside diameter of cylinder


**Stroke** - How far a cylinder extends out

**R-length** - Distance in inches between pin centers when cylinder is retracted

**Rod Diameter** - Diameter of cylinder rod

**Single Acting** - Cylinder is powered one way

Cylinders Definitions



**Double Acting** - Cylinder is powered both ways (two way)

**Crosstube End** - Round tube welded perpendicular to cylinder

**Single Eye End** - For mounting between two mounting ears.

**Clevis End** - Two mounting ears