



No. Teeth	Item Number	Bushing	Diameters		Type	Max. Bore	Dimensions						
			Outside Diameter	Pitch Diameter			L1	L2	C	Y	G	X	T
11	1-5697-60JA11	JA	3.000	2.662	B	1-1/4	1-1/8	1-1/8	2-1/16	35/64	11/64	5/8	0.459
12	1-5697-60JA12	JA	3.250	2.898	B	1-1/4	1-1/8	1-1/8	2-1/16	35/64	11/64	5/8	0.459
13	1-5697-60JA13	JA	3.490	3.134	B	1-1/4	1-1/8	1-1/8	2-1/16	35/64	11/64	5/8	0.459
14	1-5697-60SH14	SH	3.740	3.371	B	1-5/8	1-7/16	1-7/16	2-11/16	51/64	23/64	13/16	0.459
15	1-5697-60SH15	SH	3.980	3.607	B	1-5/8	1-7/16	1-7/16	2-11/16	51/64	23/64	13/16	0.459
16	1-5697-60SH16	SH	4.220	3.844	B	1-5/8	1-7/16	1-7/16	2-11/16	51/64	23/64	13/16	0.459
17	1-5697-60SDS17	SDS	4.460	4.082	B	2	1-1/2	1-1/2	3-3/16	55/64	19/64	3/4	0.459
18	1-5697-60SDS18	SDS	4.700	4.319	B	2	1-1/2	1-1/2	3-3/16	55/64	19/64	3/4	0.459
19	1-5697-60SDS19	SDS	4.950	4.557	B	2	1-1/2	1-1/2	3-3/16	55/64	19/64	3/4	0.459
20	1-5697-60SDS20	SDS	5.190	4.794	B	2	1-1/2	1-1/2	3-3/16	55/64	19/64	3/4	0.459
21	1-5697-60SDS21	SDS	5.430	5.032	B	2	1-1/2	1-1/2	3-3/16	55/64	19/64	3/4	0.459
22	1-5697-60SDS22	SDS	5.670	5.270	B	2	1-1/2	1-1/2	3-3/16	55/64	19/64	3/4	0.459
23	1-5697-60SDS23	SDS	5.910	5.508	B	2	1-1/2	1-1/2	3-3/16	55/64	19/64	3/4	0.459
24	1-5697-60SDS24	SDS	6.150	5.746	B	2	1-1/2	1-1/2	3-3/16	55/64	19/64	3/4	0.459
25	1-5697-60SDS25	SDS	6.390	5.984	B	2	1-1/2	1-1/2	3-3/16	55/64	19/64	3/4	0.459
26	1-5697-60SK26	SK	6.630	6.222	B	2-5/8	2-1/8	2-1/8	3-7/8	1-27/64	51/64	1-1/4	0.459
27	1-5697-60SK27	SK	6.870	6.460	B	2-5/8	2-1/8	2-1/8	3-7/8	1-27/64	51/64	1-1/4	0.459
28	1-5697-60SK28	SK	7.110	6.699	B	2-5/8	2-1/8	2-1/8	3-7/8	1-27/64	51/64	1-1/4	0.459
30	1-5697-60SK30	SK	7.590	7.175	B	2-5/8	2-1/8	2-1/8	3-7/8	1-27/64	51/64	1-1/4	0.459
32	1-5697-60SK32	SK	8.070	7.652	B	2-5/8	2-1/8	2-1/8	3-7/8	1-27/64	51/64	1-1/4	0.459
35	1-5697-60SK35	SK	8.780	8.367	B	2-5/8	2-1/8	2-1/8	3-7/8	1-27/64	51/64	1-1/4	0.459
36	1-5697-60SK36	SK	9.020	8.605	B	2-5/8	2-1/8	2-1/8	3-7/8	1-27/64	51/64	1-1/4	0.459
40	1-5697-60SK40	SK	9.980	9.559	B	2-5/8	2-1/8	2-1/8	3-7/8	1-27/64	51/64	1-1/4	0.459
42	1-5697-60SF42	SF	10.460	10.036	B	2-15/16	2-1/4	2-1/4	4-5/8	1-35/64	51/64	1-1/4	0.459
45	1-5697-60SF45	SF	11.180	10.752	B	2-15/16	2-1/4	2-1/4	4-5/8	1-35/64	51/64	1-1/4	0.459
48	1-5697-60SF48	SF	11.890	11.467	B	2-15/16	2-1/4	2-1/4	4-5/8	1-35/64	51/64	1-1/4	0.459