



HANDLE KIT (ONE PER SPOOL)



HIGH PRESSURE CARRY-OVER PLUG

- PRODUCT NOTES:
1. THREE SPOOL VALVE ASSY, 4-WAY 3-POSITION CYLINDER SPOOLS, SPRING CENTER ACTION.
(POWER BEYOND AND CLOSED CENTER CONVERTIBLE)
 2. MAX OPERATING PRESSURE: 3500 PSI
RELIEF PRESSURE SETTING: 2500 PSI @ 6 GPM FLOW (ADJUSTMENT RANGE: 2000-3500 PSI)
MAX TANK PRESSURE: 500 PSI
NOMINAL FLOW RATING: 8 GPM
MAX OPERATING TEMPERATURE: 180°F
 3. PORT SIZE (INLET/OUTLET, WORK PORTS, POWER BEYOND):
#8 SAE/ORB (3/4-16UNF-2B)
 4. TOP INLET PORT, TOP OUTLET PORT AND POWER BEYOND PORT ARE TO BE SEALED WITH STEEL PLUGS.
 5. NO PAINT
 6. VALVE SHIPPED IN OPEN CENTER CONFIGURATION (HIGH PRESSURE CARRY-OVER PLUG IS TO BE SHIPPED UNINSTALLED).
 7. HANDLE KITS ARE TO BE SHIPPED UNATTACHED.
 8. FILTRATION RECOMMENDATIONS: ISO 4406 19/17/14
 9. NOTE: TORQUE ON CAPSCREWS HOLDING ON GFN HANDLE HOUSINGS AND GFN END CAPS TO BE 10-12 IN-LBS.